

SAFETY DATA SHEET

Ardenbrite Quick Drying Base Coat

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name

Product type

: Ardenbrite Quick Drying Base Coat

Product description

: Coating. : Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

	Identified uses
Industrial uses Consumer uses Professional uses	

1.3 Details of the supplier of the safety data sheet

Manufactured by Tor Coatings Limited Portobello Industrial Estate Birtley County Durham United Kingdom DH3 2RE Telephone no.: +44 (0) 191 411 3146 Fax no.: +44 (0) 191 411 3147 enquiries@tor-coatings.com www.ardenbrite.com e-mail address of person : rpmeurohas@ro-m.com responsible for this SDS

1.4 Emergency telephone number

Supplier	
Telephone number	: +44 (0) 207 858 1228
Hours of operation	: 24/7

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Product definition : Mixture <u>Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</u> Skin Sens. 1, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 16 for the full text of the H statements declared above. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830 Ardenbrite Quick Drying Base Coat

SECTION 2: Hazards identification

Hazard pictograms	:	^
Signal word	:	Warning
Hazard statements	1	May cause an allergic skin reaction.
Precautionary statements		
General	:	P102 - Keep out of reach of children. P103 - Read label before use. P101 - If medical advice is needed, have product container or label at hand.
Prevention	:	P261 - Avoid breathing spray. P280 - Wear protective gloves and eye protection: No Code(s) - gloves nitrile rubber Safety glasses with side shields.
Response	:	P302 - IF ON SKIN: P352 - Wash with plenty of soap and water. P333 - If skin irritation or rash occurs: P313 - Get medical attention.
Storage	1	Not applicable.
Disposal	1	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	1	Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
Supplemental label elements	1	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		

2.3 Other hazards

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

			Classification	
Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
2-(2-butoxyethoxy) ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	≤3	Eye Irrit. 2, H319	[1] [2]
ammonia	REACH #: 01-2119488876-14 EC: 215-647-6	≤0.3	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	[1]

SECTION 3: Composition/information on ingredients

	CAS: 1336-21-6 Index: 007-001-01-2		Aquatic Acute 1, H400 (M=1)	
Reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	EC: 611-341-5 CAS: 55965-84-9 Index: 613-167-00-5	≤0.1	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the

concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

General	: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Eye contact	 Immediately flush eyes with running water for at least 7 minutes, keeping eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in nonallergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

Over-exposure signs/symptoms

Eye contact : No specific data.

Date of issue/Date of revision :	5/3/2017	Date of previous issue	: 5/3/2017	Version	: 1.03	3/15
----------------------------------	----------	------------------------	------------	---------	--------	------

SECTION 4: First aid measures

Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
4.3 Indication of any imm	ediate medical attention and special treatment needed
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefigh	ig measures			
5.1 Extinguishing media				
Suitable extinguishing media	Recommended: alcohol-resistant foam, CO ₂ , powders, water spray.			
Unsuitable extinguishing media	Do not use water jet.			
5.2 Special hazards arising f	n the substance or mixture			
Hazards from the substance or mixture	Fire will produce dense black smoke.Exposure to decomposition products may cause a health hazard.Appropriate breathing apparatus may be required.Cool closed containers exposed to fire with water.			
Hazardous thermal decomposition products	Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides			
5.3 Advice for firefighters				
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident there is a fire. No action shall be taken involving any personal risk or without suitable training.			
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.			
Additional information	No unusual hazard if involved in a fire.			

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	te	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid contact of spilt material with soil and prevent runoff entering surface waterways. See section 13 for waste disposal information.

6.3 Methods and material for containment and cleaning up

Date of	issue/Date of revision	: 5/3/2017	Date of previous issue	: 5/3/2017	Version : 1.03	4/15
---------	------------------------	------------	------------------------	------------	----------------	------

SECTION 6: Accidental release measures

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dyke spilt material or otherwise contain it to ensure runoff does not reach a waterway. Place spilt material in an appropriate container for disposal. Preferably clean with a detergent. Avoid using solvents. Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe : Keep away from heat, sparks and flame. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or handling mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Do not store below the following temperature: 0°C (32°F). Store in a dry, cool and wellventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

Recommendations: Not available.Industrial sector specific: Not available.solutions: Not available.

SECTION 8: Exposure controls/personal protection

required.

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-(2-butoxyethoxy)ethanol	EH40/2005 WELs (United Kingdom (UK), 12/2011). TWA: 10 ppm 8 hours. STEL: 15 ppm 15 minutes. TWA: 67.5 mg/m ³ 8 hours. STEL: 101.2 mg/m ³ 15 minutes.
procedures atmosphere or b of the ventilation protective equip the following: E the assessment limit values and atmospheres - C of exposure to c (Workplace atm for the measure	ontains ingredients with exposure limits, personal, workplace biological monitoring may be required to determine the effectiveness in or other control measures and/or the necessity to use respiratory ment. Reference should be made to monitoring standards, such as uropean Standard EN 689 (Workplace atmospheres - Guidance for of exposure by inhalation to chemical agents for comparison with measurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 iospheres - General requirements for the performance of procedures ment of chemical agents) Reference to national guidance nethods for the determination of hazardous substances will also be

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
2-(2-butoxyethoxy)ethanol	DNEL	Long term Inhalation	67.5 mg/m³	Workers	Local
	DNEL	Long term Inhalation	67.5 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	20 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	50.6 mg/m ³	Consumers	Local
	DNEL	Long term Inhalation	34 mg/m³	Consumers	Local
	DNEL	Long term Inhalation	34 mg/m³	Consumers	Systemic
	DNEL	Long term Dermal	10 mg/kg bw/day	Consumers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
2-(2-butoxyethoxy)ethanol	Fresh water Marine Fresh water sediment Marine water sediment Sewage Treatment Plant	1 mg/l 0.1 mg/l 4 mg/kg 0.4 mg/kg 200 mg/l	- - - - -

8.2 Exposure controls

Appropriate engineering controls

: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

Individual protection measures

Date of issue/Date of revision

: 5/3/2017

SECTION 8: Exposure controls/personal protection

•	• •
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Recommended: safety glasses with side-shields (EN 166)

Skin protection

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Gloves	: For prolonged or repeated handling, use the following type of gloves:
	Recommended: > 8 hours (breakthrough time): nitrile rubber (0.5mm) The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN 374-3 : 2003
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Wear overalls or long sleeved shirt. (EN 467)
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: organic vapour (Type A) and particulate filter (EN 141).
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	: Yellowish-brown.
Odour	: Mild.
Odour threshold	: Not available.
рН	: 7 to 8

1)

SECTION 9: Physical and chemical properties

Melting point/freezing point	1	Not available.
Initial boiling point and boiling range	:	Not available.
Flash point	:	Not applicable.
Evaporation rate	:	<1 (butyl acetate =
Flammability (solid, gas)	:	Not available.
Upper/lower flammability or explosive limits	:	Not applicable.
Vapour pressure	:	Not available.
Vapour density	:	>1 [Air = 1]
Relative density	:	1.23
Solubility(ies)	:	Not available.
Solubility in water	:	Miscible in water.
Partition coefficient: n-octanol/ water	:	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	Not available.
Explosive properties	:	Not applicable.
Oxidising properties	:	Not available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity			
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.		
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).		
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.		
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.		
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.		
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced. If involved in a fire, toxic gases including CO, CO2 and smoke can be generated.		

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
2-(2-butoxyethoxy)ethanol	LD50 Dermal LD50 Oral	Rabbit Rat	2700 mg/kg 4500 mg/kg	-
ammonia	LC50 Inhalation Vapour LC50 Inhalation Vapour LC50 Inhalation Vapour	Human/30 min Rat Rat	5000 mg/m ³ 7035 mg/m ³ 2000 mg/m ³	0.5 hours 30 minutes 4 hours
Reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	LD50 Oral LD50 Oral	Rat Rat	350 mg/kg 53 mg/kg	-

Conclusion/Summary Acute toxicity estimates

Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-(2-butoxyethoxy)ethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Eyes - Severe irritant	Rabbit	-	20 milligrams	-
ammonia	Eyes - Severe irritant	Rabbit	-	250 Micrograms	-
	Eyes - Severe irritant	Rabbit	-	0.5 minutes 1 milligrams	-
Reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Skin - Severe irritant	Human	-	0.01 Percent	-
Conclusion/Summary		-	-	-	·

oonolasion#oanniary	
Skin	: Based on available data, the classification criteria are not met.
Eyes	: Based on available data, the classification criteria are not met.
Respiratory	: Based on available data, the classification criteria are not met.
Sensitisation	
Conclusion/Summary	
Skin	: May cause an allergic skin reaction.
Respiratory	: Based on available data, the classification criteria are not met.
Mutagenicity	
Conclusion/Summary	: Based on available data, the classification criteria are not met.
Carcinogenicity	
Conclusion/Summary	: Based on available data, the classification criteria are not met.
Reproductive toxicity	
Conclusion/Summary	: Based on available data, the classification criteria are not met.
Teratogenicity	
Conclusion/Summary	: Based on available data, the classification criteria are not met.
Specific target organ toxic	<u>y (single exposure)</u>

	Product/ingredient name	Category	Route of exposure	Target organs
ammonia		Category 3	Not applicable.	Respiratory tract irritation

Date of issue/Date of revision

SECTION 11: Toxicological information

Specific target organ toxici	<u>y (repeated exposure)</u>
Not available.	
Aspiration hazard	
Not available.	
Delayed and immediate effect	ts as well as chronic effects from short and long-term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	<u>ects</u>
Not available.	
Conclusion/Summary	: Based on available data, the classification criteria are not met.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Other information	: Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment, but contains substance(s) hazardous to the environment. See section 3 for details.

Product/ingredient name	Result	Species	Exposure
2-(2-butoxyethoxy)ethanol	Acute EC50 2850 mg/l	Daphnia spec.	48 hours
	Acute IC50 >100 mg/l	Algae	96 hours
	Acute LC50 1300000 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
ammonia	Acute EC50 110 mg/l	Daphnia spec.	48 hours
	Acute LC50 7 mg/l	Fish	48 hours
	Acute LC50 17 mg/l	Fish	24 hours
	Acute LC50 15000 µg/l Fresh water	Fish - Gambusia affinis - Adult	96 hours
Reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Acute EC50 0.027 mg/l	Algae - Selenastrum capricornutum	72 hours
.,	Acute EC50 0.126 mg/l Acute LC50 0.28 mg/l Acute LC50 0.188 mg/l Acute NOEC 0.098 mg/l	Daphnia spec. Fish Fish Fish	48 hours 96 hours 96 hours 96 hours

SECTION 12: Ecological information

Conclusion/Summary

: Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	D	Dose	Inoculum
Reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	OECD 301D	>60 % - Readily - 28	8 days -		-
Conclusion/Summary		as not been tested for inherently biodegrad		on. According to	EC criteria:
Product/ingredient name	Aquatic half-life		Photolysis		Biodegradability
2-(2-butoxyethoxy)ethanol ammonia Reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	-		- - -		Readily Readily Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-(2-butoxyethoxy)ethanol ammonia Reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	1 -1.3 -0.83 to 0.75	- -	low low low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Nonvolatile liquid.

12.5 Results of PBT and vPvB assessment		
PBT	: Not applicable.	
vPvB	: Not applicable.	

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance.

13.1 Waste treatment methods

Product

SECTION 13: Disposal considerations

Methods of disposal	The generation of waste should be avoided or minimised wherever possib Disposal of this product, solutions and any by-products should at all times with the requirements of environmental protection and waste disposal legi and any regional local authority requirements. Dispose of surplus and nor recyclable products via a licensed waste disposal contractor. Waste should disposed of untreated to the sewer unless fully compliant with the requirer all authorities with jurisdiction.	comply islation n- uld not be
Hazardous waste	Yes.	
Disposal considerations	Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code onger apply and the appropriate code should be assigned. For further information, contact your local waste authority.	

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation		
08 01 15*	aqueous sludges containing paint or varnish containing organic solvents or other hazardous substances		
Packaging			
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.		
Disposal considerations	: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Not emptied containers are hazardous waste.		
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.		

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

12/15

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830 Ardenbrite Quick Drying Base Coat

SECTION 14: Transport information

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

VOC for Ready-for-Use : Exempt Mixture

Europe inventory : At least one component is not listed.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

References

: EH40/2005 Workplace exposure limits Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC) Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

CN code : 3209 10 00

International lists

National inventory Australia

: Not determined.

SECTION 15: Regulatory information

•	-
Canada	: Not determined.
China	: Not determined.
Japan	: Not determined.
Malaysia	: Not determined.
New Zealand	: Not determined.
Philippines Republic of Korea	Not determined.Not determined.
Taiwan	: Not determined.
Turkey	: Not determined.
United States	: Not determined.
	No Observiced Opfate Assessment has been serviced out

15.2 Chemical safety

: No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1, H317	Calculation method

Full text of H-phrases referred to in sections 2 and 3

Full text of abbreviated H statements	:	H301 H311 H314 H317 H318 H319 H331 H335 H400 H410	Toxic if swallowed. Toxic in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Toxic if inhaled. May cause respiratory irritation. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.
Full text of classifications [CLP/GHS]	:	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Eye Dam. 1, H318 Eye Irrit. 2, H319 Skin Corr. 1B, H314 Skin Sens. 1, H317 STOT SE 3, H335	ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 ACUTE AQUATIC HAZARD - Category 1 LONG-TERM AQUATIC HAZARD - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 1B SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3
Date of printing	:	5/8/2017	·

SECTION 16: Other information

Date of issue/ Date of	:	5/3/2017
revision		
Date of previous issue	:	5/3/2017
Version	:	1.03

Notice to reader

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.