

## DESCRIPTION

Johnstone's Trade Black Bitumen is a corrosion resisting, waterproofing paint formulated for exterior use on a variety of substrates including metal, stone and concrete surfaces. Once dry it provides a waterproof and weather resistant coating.

## RECOMMENDED USES



Corrosion resistant protective finish for metal and concrete.

## SPECIAL PROPERTIES

Excellent water resistance.

## COLOUR RANGE

Black.

## FINISH

Mid-sheen.

## VOLUME SOLID

47%

## COVERAGE



Johnstone's Trade Black Bitumen will cover approximately 8-10 square metres per litre depending on the nature and porosity of the surface being painted.

## FILM THICKNESS

Wet: 85µm, dry: 40µm.

## DRYING TIME



Recoat after 24 hours under normal conditions.

## TRANSPORTATION & STORAGE

Johnstone's Trade Black Bitumen may weather to a matt finish, which in no way impairs the protective qualities of the paint. Do not overcoat with other solvent based paints as bleeding may occur. To avoid the risk of spillage, always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

## THINNER

Cleaner : White Spirit

## VOC CONTENT

EU limit value for this product (Cat A/I): 500g/l (2010). This product contains max 500g/l VOC.



## KEY PROPERTIES

- Anti-Corrosive
- Helps increase water resistance

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Any rust should be removed by wire brushing. Wear a suitable face mask when creating dust. Prime bare surfaces with an appropriate Johnstone's Trade Primer. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).

## APPLICATION



Ensure maximum ventilation during application and drying. Not recommended for interior use on large surface areas, or in confined spaces. Easy to apply by brush or roller. 2 coats are recommended on new work. Do not apply over tar based products or surfaces that can rise above 65°C.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354

## SIZE

2.5 Litre and 5 Litre.