

DESCRIPTION

Johnstone's Trade Quick Dry Zinc Phosphate Primer is a quick drying, single pack anti corrosive primer for steel. Suitable for use under a wide variety of conventional finishes combining excellent adhesion and ease of application.

RECOMMENDED USES



An anti-corrosive primer for ferrous metals and all suitably prepared non-ferrous substrates.

SPECIAL PROPERTIES

Excellent anti-corrosive properties on properly prepared steel.

COLOUR RANGE

Red Oxide; Grey; White.

FINISH

Matt.

VOLUME SOLID

34%

COVERAGE



Johnstone's Trade Quick Dry Zinc Phosphate Primer will cover approximately 11 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 75µm, dry: 35µm.

DRYING TIME



Recoat after 14-16 hours, under normal conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

THINNER

Cleaner: White Spirit

VOC CONTENT

EU limit value for this product (Cat A/i): 500 g/l (2010) This product contains max 450 g/l VOC



KEY PROPERTIES

- Anti-corrosive primer for steel
- Excellent adhesion
- Excellent rust inhibitor

PREPARATION

STEEL: Blast cleaned to SIS-Sa2 '2 1/2' minimum or mechanically prepared to SIS-St 3 minimum. Previous suitable coats should be clean, dry and abraded if necessary. All surfaces to be painted should be clean, dry and free from loose or flaking material. Existing rust or millscale should be removed from iron and steel. Loose or defective paint should be removed, stripping to the bare surface if necessary. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure maximum ventilation during application and drying. Not recommended for interior use on large surface areas, or in confined spaces. Stir thoroughly before use. Easy to apply by brush. To ensure the best results the brush should be fully loaded. Do not thin.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZE

2.5 Litre and 5 Litre (White available in 5 Litre only).