



# Technical Data

## Acrypol + Solar White Roof Coating

### Ref. RC 3006

<b>Purpose</b>	A high performance waterproof roof coating for use on most types of conventional roof structures, which can be applied on damp substrates in inclement weather conditions. Contains fibres to bridge cracks in substrate.
<b>Composition</b>	Acrylic resin pigmented with specially selected opacifying pigments, fillers and fibres in a suitable solvent.
<b>Application</b>	Brush or squeegee. For spraying application, consult manufacturer.
<b>Volume Solids Percentage</b>	50% ± 2%
<b>Recommended Minimum Film Thickness</b>	1000 microns wet                      500 microns dry
<b>Theoretical Spreading Rate At Above Thickness</b>	1sq. metre per kg at 500 microns dry film thickness.
<b>Drying Time</b>	24 hours at 18°C - 21°C. Drying time will be extended at lower temperatures.
<b>Recoating Time</b>	24 hours at 18°C - 21°C.
<b>Cleaning Solvent</b>	AC 4001 Acrypol Cleaner.
<b>Storage Properties</b>	Several years in original unopened containers.
<b>Flash Point</b>	> 32°C & ≤ 55°C.
<b>Colour</b>	Solar White.
<b>Finish</b>	Sheen.
<b>Surface Preparation</b>	Refer to specification.
<b>Suitable Further Coating</b>	Coat on coat.
<b>Pack Availability</b>	5 kg and 20 kg.
<b>Safety Precautions</b>	See Product Safety Data Sheet: Acrypol Plus
<b>Additional Data</b>	The details and information contained herein, are to the best of our knowledge correct but may from time to time be subject to revision. We will endeavour to keep customers informed of any changes that may occur but we advise that if in any doubt, contact is made with the manufacturer to establish the data is of the latest available. We would point out that whilst we have striven to ensure the details are as accurate as possible, we offer no guarantee as application conditions and techniques are beyond our control.