

LACACOTE WOOD SANDING SEALER

Page: 1

Compilation date: 19/08/2005

Revision date: 23/01/2017

Revision No: 2

# Section 1: Identification of the substance/mixture and of the company/undertaking

# 1.1. Product identifier

Product name: LACACOTE WOOD SANDING SEALER

Product code: 05-774-9028

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Used as a furniture sealer

1.3. Details of the supplier of the safety data sheet

ay talankana ny m	•
Email:	info@mylands.co.uk
Fax:	020 8761 5700
Tel:	020 8670 9161
	SE27 0HQ
	LONDON
	WEST NORWOOD
	26 ROTHSCHILD STREET
Company name:	JOHN MYLAND LIMITED

# 1.4. Emergency telephone number

# Section 2: Hazards identification

# 2.1. Classification of the substance or mixture

Classification under CLP:	Flam. Liq. 2: H225
---------------------------	--------------------

Most important adverse effects: Highly flammable liquid and vapour.

### 2.2. Label elements

Label elements under CLP:

Hazard statements: H225: Highly flammable liquid and vapour.

Hazard pictograms: GHS02: Flame



Signal words: Danger

**Precautionary statements:** P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240: container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.

## LACACOTE WOOD SANDING SEALER

Rinse skin with water.

P370+378: In case of fire: Use for extinction.

## 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

# 3.2. Mixtures

#### Hazardous ingredients:

#### **ETHANOL**

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-578-6	64-17-5	Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	70-90%

# Section 4: First aid measures

# 4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

## 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

## 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

# Section 5: Fire-fighting measures

## 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

# 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

Page: 2

# LACACOTE WOOD SANDING SEALER

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

# Section 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Turn leaking containers leakside up to prevent the escape of liquid. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

## Section 7: Handling and storage

#### 7.1. Precautions for safe handling

**Handling requirements:** Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

# 7.3. Specific end use(s)

Specific end use(s): No data available.

# Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### Hazardous ingredients:

## ETHANOL

#### Workplace exposure limits:

Respirable dust

State 8 hour T	VA 15 min. STEL	8 hour TWA	15 min. STEL
----------------	-----------------	------------	--------------

# LACACOTE WOOD SANDING SEALER

						Page:	4
UK	19	20 mg/m3	-	-		-	
DNEL/PNEC Val	ues						
	DNEL / PNEC	No data av	ailable.				
8.2. Exposure c	ontrols						
Engineer	ing measures:	The floor o	f the storage room must be i	mpermeable to prevent the	escape of liquids.		
			y protection not required.				
На	nd protection:	Protective	gloves.				
E	ye protection:	Safety glas	sses.				
S	kin protection:	Protective	clothing.				
Section 9: Physic	cal and chemic	cal proper	ties				
9.1. Information	on basic physi	cal and che	emical properties				
	State:	Liquid					
	Colour:	-					
	Odour:	Perceptible	e odour				
	Flash point°C:	12		V	<b>DC g/I:</b> 650		
9.2. Other inform	nation						
Othe	er information:	No data av	ailable.				
Section 10: Stabi	lity and reacti	vity					
10.1. Reactivity							
	Reactivity:	Stable und	er recommended transport o	r storage conditions.			
10.2. Chemical s	stability						
Che	mical stability:	Stable und	er normal conditions.				
10.3. Possibility	of hazardous r	eactions					
Hazard	ous reactions:	Hazardous	reactions will not occur und	er normal transport or stora	ge conditions.		
		Decompos	ition may occur on exposure	to conditions or materials li	isted below.		
10.4. Conditions	s to avoid						
Condi	tions to avoid:	Heat.					
10.5. Incompatil	ole materials						
Mate	erials to avoid:	Strong oxid	dising agents. Strong acids.				
10.6. Hazardous	decompositior	n products					
Haz. deco	mp. products:	In combust	tion emits toxic fumes.			_	
Section 11: Toxic	cological infor	mation					

# LACACOTE WOOD SANDING SEALER

Page: 5

## 11.1. Information on toxicological effects

#### Hazardous ingredients:

#### ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

# Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

#### 12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

## 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

# Section 13: Disposal considerations

13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

# Section 14: Transport information

# LACACOTE WOOD SANDING SEALER

	· 490. 0
14.1. UN number	
UN number:	UN1263
14.2. UN proper shipping name	
Shipping name:	PAINT
14.3. Transport hazard class(es	s)
Transport class:	3
14.4. Packing group	
Packing group:	II
14.5. Environmental hazards	
Environmentally hazardous:	No Marine pollutant: No
14.6. Special precautions for us	ser
Special precautions:	No special precautions.
Tunnel code:	D/E
Transport category:	2
Section 15: Regulatory information	ation
15.1. Safety, health and enviror	nmental regulations/legislation specific for the substance or mixture
<u>-</u>	
Specific regulations:	
15.2. Chemical Safety Assessn	ient
Section 16: Other information	
Other information	
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	453/2010.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H225: Highly flammable liquid and vapour.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.

Page: 6