



## SAFETY DATA SHEET

### 600/V607 - CHLORINATED RUBBER THINNERS

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** 600/V607 - CHLORINATED RUBBER THINNERS

**Product number** 600/V607/15/CR

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** As a paint thinner/cleaner

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** TEAL & MACKRILL LIMITED  
LOCKWOOD STREET  
HULL  
HU2 0HN

+44(0)1482 320194(T)

+44(0)1482 219266(F)

info@teamac.co.uk

**Contact person** Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

##### 1.4. Emergency telephone number

**Emergency telephone** +44 (0) 1482 320194 (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

**SDS No.** 10704

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC/1272/2008)

**Physical hazards** Flam. Liq. 3 - H226

**Health hazards** STOT SE 3 - H335, H336 Asp. Tox. 1 - H304

**Environmental hazards** Aquatic Chronic 2 - H411

**Classification (67/548/EEC or 1999/45/EC)** Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.

##### 2.2. Label elements

###### Pictogram



**Signal word**

Danger

## 600/V607 - CHLORINATED RUBBER THINNERS

<b>Hazard statements</b>	<p>H226 Flammable liquid and vapour.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H335 May cause respiratory irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p>
<b>Precautionary statements</b>	<p>P102 Keep out of reach of children.</p> <p>P101 If medical advice is needed, have product container or label at hand.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
<b>Contains</b>	Hydrocarbons, C9, aromatics
<b>Supplementary precautionary statements</b>	<p>P240 Ground/ bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical equipment.</p> <p>P242 Use only non-sparking tools.</p> <p>P243 Take precautionary measures against static discharge.</p> <p>P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P312 Call a POISON CENTER/ doctor if you feel unwell.</p> <p>P331 Do NOT induce vomiting.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P391 Collect spillage.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P405 Store locked up.</p>

### 2.3. Other hazards

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>Hydrocarbons, C9, aromatics</b>		<b>60-100%</b>
CAS number: —	EC number: 918-668-5	REACH registration number: 01-2119455851-35-xxxx
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Liq. 3 - H226	Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.	
STOT SE 3 - H335, H336		
Asp. Tox. 1 - H304		
Aquatic Chronic 2 - H411		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General information</b>	Remove affected person from source of contamination. Get medical attention if any discomfort continues.
----------------------------	---

## 600/V607 - CHLORINATED RUBBER THINNERS

<b>Inhalation</b>	Remove affected person from source of contamination. Get medical attention if any discomfort continues. Place unconscious person on their side in the recovery position and ensure breathing can take place. If breathing stops, provide artificial respiration.
<b>Ingestion</b>	Place unconscious person on their side in the recovery position and ensure breathing can take place. Give plenty of water to drink. Never give anything by mouth to an unconscious person. Get medical attention immediately.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Inhalation</b>	Vapours in high concentrations are anaesthetic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Central nervous system depression.
<b>Ingestion</b>	Aspiration of product into lungs can cause fatal chemical pneumonitis.
<b>Skin contact</b>	Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.

### 4.3. Indication of any immediate medical attention and special treatment needed

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m <sup>3</sup> . Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.
<b>Hazardous combustion products</b>	During fire, toxic gases (CO, CO <sub>2</sub> ) are formed.

### 5.3. Advice for firefighters

<b>Protective actions during firefighting</b>	Avoid breathing fire gases or vapours. Use water to keep fire exposed containers cool and disperse vapours. Control run-off water by containing and keeping it out of sewers and watercourses.
<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Avoid inhalation of vapours and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	---

### 6.2. Environmental precautions

<b>Environmental precautions</b>	Avoid the spillage or runoff entering drains, sewers or watercourses.
----------------------------------	---

### 6.3. Methods and material for containment and cleaning up

## 600/V607 - CHLORINATED RUBBER THINNERS

### Methods for cleaning up

Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Absorb in vermiculite, dry sand or earth and place into containers. Disposal should be carried out in accordance with the Hazardous Waste Regulations. If any liquid enters the drainage system or watercourse inform local authorities, Fire Brigade and Environment Agency.

### 6.4. Reference to other sections

**Reference to other sections** Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Do not use in confined spaces without adequate ventilation and/or respirator. Eliminate all sources of ignition. Keep away from heat, sparks and open flame. Avoid inhalation of vapours and contact with skin and eyes.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep away from heat, sparks and open flame. Store in tightly-closed, original container in a dry, cool and well-ventilated place.

**Storage class** Flammable liquid storage. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 250 litres of liquids with a flashpoint above 32C but below 55C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate, marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.

### 7.3. Specific end use(s)

**Usage description** Take precautionary measures against static discharges.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

#### Hydrocarbons, C9, aromatics

Long-term exposure limit (8-hour TWA): WEL 19 ppm 100 mg/m<sup>3</sup> vapour

WEL = Workplace Exposure Limit

#### Hydrocarbons, C9, aromatics

#### DNEL

Consumer - Oral; Long term systemic effects: 11 mg/kg/day  
 Consumer - Dermal; Long term systemic effects: 11 mg/kg/day  
 Consumer - Inhalation; Long term systemic effects: 32 mg/m<sup>3</sup>  
 Industry - Dermal; Long term systemic effects: 25 mg/kg/day  
 Industry - Inhalation; Long term systemic effects: 100 mg/m<sup>3</sup>

#### PNEC

No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.

### 8.2. Exposure controls

## 600/V607 - CHLORINATED RUBBER THINNERS

### Protective equipment



### Appropriate engineering controls

Provide adequate general and local exhaust ventilation. This product must not be handled in a confined space without adequate ventilation.

### Eye/face protection

The following protection should be worn: Wear chemical splash goggles.

### Hand protection

Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. It is recommended that gloves are made of the following material: Polyvinyl chloride (PVC). Nitrile gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin. Neoprene gloves are recommended. Frequent changes are recommended.

### Other skin and body protection

Wear suitable protective clothing as protection against splashing or contamination.

### Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Do not smoke in work area.

### Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

Appearance	Clear liquid.
Colour	Colourless.
Odour	Organic solvents.
Odour threshold	Not available.
pH	Not applicable.
Melting point	Not applicable.
Initial boiling point and range	140 - 200°C @ 760 mm Hg
Flash point	43°C CC (Closed cup).
Evaporation rate	0.16 (butyl acetate = 1)
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.7 g/100 g Upper flammable/explosive limit: 7.0 g/100 g
Vapour pressure	0.29 kPa @ °C
Vapour density	~ 4.2
Relative density	0.882 @ 15°C
Bulk density	882 kg/m³
Solubility(ies)	Immiscible with water Miscible with the following materials: Organic solvents.
Partition coefficient	Not available.

## 600/V607 - CHLORINATED RUBBER THINNERS

**Auto-ignition temperature** 450°C

**Viscosity** <30 seconds 3mm ISO cup s @ 25°C

### 9.2. Other information

**Molecular weight** 122

**Volatility** 100

**Volatile organic compound** This product contains a maximum VOC content of 880 g/litre.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures and when used as recommended.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Not determined.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:  
Acids. Oxidising agents.

### 10.5. Incompatible materials

**Materials to avoid** Strong alkalis. Strong acids. Strong oxidising agents.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Inhalation** Vapour may irritate respiratory system/lungs. Vapours in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. The product contains organic solvents. Overexposure may depress the central nervous system, causing dizziness and intoxication. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis. May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

**Ingestion** Harmful: may cause lung damage if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

**Skin contact** May cause defatting of the skin but is not an irritant. Repeated exposure may cause skin dryness or cracking. Not a skin sensitiser.

**Eye contact** No specific health hazards known.

**Route of entry** Inhalation

### Toxicological information on ingredients.

#### Hydrocarbons, C9, aromatics

#### Acute toxicity - oral

## 600/V607 - CHLORINATED RUBBER THINNERS

Acute toxicity oral (LD<sub>50</sub> mg/kg) 3,592.0

Species Rat

ATE oral (mg/kg) 3,592.0

### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 3,160.0

Species Rabbit

ATE dermal (mg/kg) 3,160.0

### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 6,193.0

Species Rat

ATE inhalation (vapours mg/l) 6,193.0

### Serious eye damage/irritation

Serious eye damage/irritation Slightly irritating.

### Respiratory sensitisation

Respiratory sensitisation Not sensitising.

### Skin sensitisation

Skin sensitisation Not sensitising.

### Carcinogenicity

Carcinogenicity There is no evidence that the product can cause cancer.

### Specific target organ toxicity - single exposure

Target organs Central nervous system Respiratory system, lungs

### Aspiration hazard

Aspiration hazard Kinematic viscosity <= 20.5 mm<sup>2</sup>/s.

## SECTION 12: Ecological Information

Ecotoxicity Dangerous for the environment if discharged into watercourses.

### 12.1. Toxicity

#### Ecological information on ingredients.

#### Hydrocarbons, C9, aromatics

Toxicity Toxic to aquatic organisms

Acute toxicity - fish LC<sub>50</sub>, 96 hours: 9.2 mg/l, Fish

Acute toxicity - aquatic invertebrates EC<sub>50</sub>, 48 hours: 3.2 mg/l, Daphnia magna

## 600/V607 - CHLORINATED RUBBER THINNERS

### 12.2. Persistence and degradability

#### Ecological information on ingredients.

##### Hydrocarbons, C9, aromatics

<b>Persistence and degradability</b>	The product is readily biodegradable.
<b>Biodegradation</b>	- 78 Degradation (%): 28 days

### 12.3. Bioaccumulative potential

<b>Partition coefficient</b>	Not available.
------------------------------	----------------

#### Ecological information on ingredients.

##### Hydrocarbons, C9, aromatics

<b>Bioaccumulative potential</b>	No data available on bioaccumulation.
----------------------------------	---------------------------------------

### 12.4. Mobility in soil

<b>Mobility</b>	The product contains organic solvents which will evaporate easily from all surfaces.
-----------------	--

#### Ecological information on ingredients.

##### Hydrocarbons, C9, aromatics

<b>Mobility</b>	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
-----------------	---

### 12.5. Results of PBT and vPvB assessment

<b>Results of PBT and vPvB assessment</b>	This substance is not classified as PBT or vPvB according to current EU criteria.
---	---

#### Ecological information on ingredients.

##### Hydrocarbons, C9, aromatics

<b>Results of PBT and vPvB assessment</b>	This substance is not classified as PBT or vPvB according to current EU criteria.
---	---

### 12.6. Other adverse effects

#### Ecological information on ingredients.

##### Hydrocarbons, C9, aromatics

<b>Other adverse effects</b>	Not determined.
------------------------------	-----------------

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>General information</b>	Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Do not puncture or incinerate even when empty.
<b>Disposal methods</b>	Dispose of contents/container in accordance with national regulations.



## 600/V607 - CHLORINATED RUBBER THINNERS

### Waste class

When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11\* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11\* (SOLVENT BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

### SECTION 14: Transport information

**General** This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.

#### 14.1. UN number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

#### 14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT

Proper shipping name (IMDG) PAINT

Proper shipping name (ICAO) PAINT

Proper shipping name (ADN) PAINT

#### 14.3. Transport hazard class(es)

ADR/RID class 1263

IMDG class 3

ICAO class/division 3

#### Transport labels



#### 14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



#### 14.6. Special precautions for user

EmS F-E, S-E

## 600/V607 - CHLORINATED RUBBER THINNERS

Tunnel restriction code (D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78  
and the IBC Code

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	Control of Substances Hazardous to Health Regulations 2002 (as amended). Dangerous Substances and Explosive Atmospheres Regulations 2002.
<b>EU legislation</b>	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
<b>Guidance</b>	Workplace Exposure Limits EH40. Approved Classification and Labelling Guide (Sixth edition) L131.

#### 15.2. Chemical safety assessment

### SECTION 16: Other information

<b>Revision comments</b>	Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 453/2010 Revision to sections 2, 8, 11 & 12 for reclassification of solvents.
<b>Issued by</b>	Technical Dept. (P.E.)
<b>Revision date</b>	15/04/2016
<b>Revision</b>	5
<b>Supersedes date</b>	11/05/2012
<b>SDS number</b>	10704
<b>SDS status</b>	Approved.
<b>Signature</b>	Initials .....
<b>Risk phrases in full</b>	R10 Flammable. R37 Irritating to respiratory system. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.
<b>Hazard statements in full</b>	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.