Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 453/2010 - United Kingdom (UK)

SAFETY DATA SHEET

COLRON REFINED FINISHING WAX

SECTION 1: Identification of the substance/mixture and of the company/undertaking

| 1.1 Product identifier | |
|------------------------|--------------------------------|
| Product name | : COLRON REFINED FINISHING WAX |
| Product code | : RON004199 |

| 1.2 Relevant identified uses | of the substance or mixture and uses advised against |
|------------------------------|--|
| Material uses | : Paint or paint related material. |

| 1.3 Details of the supplier of the safety data sheet | National contact | | |
|---|---|--|--|
| Sherwin Williams Diversified Brands Limited Thorncliffe Park Chapeltown Sheffield S35 2YP | Sherwin Williams Diversified Brands Limited Thorncliffe Park Chapeltown Sheffield S35 2YP | | |
| e-mail address of person : SDS@Ronseal.co.u responsible for this SDS | uk | | |
| 1.4 Emergency telephone number | | | |

| National advisory body/Poison Centre | | | | |
|--------------------------------------|---|--|--|--|
| Telephone number | : National Poisons Information Service +44 844 892 0111 / 112 | | | |
| <u>Supplier</u> | | | | |
| Telephone number | : +44 (0)114 246 7171 (08:30 - 17:00) | | | |

SECTION 2: Hazards identification

| 2.1 Classification of the sub | ostance or mixture | | |
|---|---|--|--|
| Product definition | : Mixture | | |
| Classification according to | D Regulation (EC) No. 1272/2008 [CLP/GHS] | | |
| Flam. Liq. 3, H226 STOT SE 3, H336 (Narcotic Aquatic Chronic 3, H412 | effects) | | |
| Ingredients of unknown toxicity | : Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 5.3% | | |
| Ingredients of unknown ecotoxicity | Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 5.3% | | |
| Classification according to | Directive 1999/45/EC [DPD] | | |
| The product is classified as | adangerous according to Directive 1999/45/EC and its amendments. | | |
| Classification | : R10 R66, R67 R52/53 | | |
| Physical/chemical hazards | : Flammable. | | |
| Human health hazards | Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. | | |
| Environmental hazards | : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. | | |
| See Section 16 for the full text of the R phrases or H statements declared above. | | | |
| See Section 11 for more det | ailed information on health effects and symptoms. | | |

SECTION 2: Hazards identification

| 2.2 Label elements | |
|---|---|
| Hazard pictograms | |
| Signal word | : Warning |
| Hazard statements | Flammable liquid and vapour. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects. |
| Precautionary statements | |
| General | : Keep out of reach of children. If medical advice is needed, have product container or label at hand. |
| Prevention | : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. |
| Response | : IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| Storage | : |
| Disposal | Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Hazardous ingredients | : Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics |
| Supplemental label elements | : Repeated exposure may cause skin dryness or cracking. |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : Not applicable. |
| Special packaging requirem | <u>ents</u> |
| Containers to be fitted with child-resistant fastenings | : Not applicable. |
| Tactile warning of danger | : Not applicable. |
| 2.3 Other hazards | |
| •·· · · · · · · | |

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

:

3.2 Mixture

| | | | Cla | assification | |
|--|--|------------|------------|--|------|
| Product/ingredient name | Identifiers | % | 67/548/EEC | Regulation (EC) No. 1272/2008 [CLP] | Туре |
| Hydrocarbons, C9-C11, n-alkanes, | REACH #: 01-2119463258-33 | >=50 - <75 | R10 | Flam. Liq. 3, H226 | [1] |
| isoalkanes, cyclics, < 2% aromatics | EC: 265-150-3 | | Xn; R65 | STOT SE 3, H336 (Narcotic effects) | |
| | CAS: 64742-48-9 Index: 649-327-00-6 | | R66, R67 | Asp. Tox. 1, H304 | |
| Hydrocarbons, C9-C12, n-alkanes, | REACH #: 01-2119458049-33 | >=20 - <25 | R10 | Flam. Liq. 3, H226 | [1] |
| isoalkanes, cyclics, | EC: 265-191-7 | | Xn; R65 | Asp. Tox. 1, H304 | |
| Date of issue/Date of revisio | n : 09, Jun, 2014. | Ve | ersion :1 | | 2/13 |

| COLRON REFINED FINISHING WAX | | | | |
|------------------------------|--|---|---|--|
| SECTION 3: Com | position/information or | n ingredients | | |
| aromatics (2-25%) | CAS: 64742-88-7 Index: 649-405-00-X | R66 N; R51/53 | Aquatic Chronic 2, H411 | |
| | | See Section 16 fo the full text of the phrases declared above. | R- the full text of the H statements declared above. | |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

| 4.1 Description of first aid me | eas | sures |
|---------------------------------|-----|--|
| General | : | In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice. |
| Eye contact | : | Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention. |
| Inhalation | : | Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. |
| Skin contact | : | Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. |
| Ingestion | : | If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting. |
| | | If swallowed, rinse mouth with water (only if the person is conscious). Get immediate medical attention. |
| Protection of first-aiders | : | No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |
| | | |

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

| 9, Jun, 2014. | Version | :1 |
|---------------|---------------|-----------------------|
| | 9, Jun, 2014. | 9, Jun, 2014. Version |

SECTION 4: First aid measures

Specific treatments : No specific treatment.

See toxicological information (Section 11)

| SECTION 5: Firefighting | easures | |
|--|---|----|
| 5.1 Extinguishing media Suitable extinguishing media | Recommended: alcohol-resistant foam, carbon dioxide, powders. | |
| Unsuitable extinguishing media | Do not use water jet. | |
| 5.2 Special hazards arising f | the substance or mixture | |
| Hazards from the substance or mixture | Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. | |
| | Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. | |
| Hazardous thermal decomposition products | Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen. | |
| | Appropriate breathing apparatus may be required. | |
| 5.3 Advice for firefighters | | |
| Special protective actions for fire-fighters | Cool closed containers exposed to fire with water. Do not release runoff from fire drains or watercourses. | to |
| Special protective equipment for fire-fighters | Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear. | |

SECTION 6: Accidental release measures

| 6.1 Personal precautions, pro | te | ctive equipment and emergency procedures |
|--|----|---|
| For non-emergency personnel | : | Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8. |
| | : | Keep unnecessary and unprotected personnel from entering. |
| For emergency responders | : | If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| 6.2 Environmental precautions | : | Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations. |
| 6.3 Methods and material for containment and cleaning up | : | Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents. |
| 6.4 Reference to other sections | : | See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information. |

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

| 7.1 Precautions for safe handling | Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses. Information on fire and explosion protection Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. |
|--|--|
| 7.2 Conditions for safe storage, including any incompatibilities | Store in accordance with local regulations. Notes on joint storage Keep away from: oxidising agents, strong alkalis, strong acids. Additional information on storage conditions Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Contaminated absorbent material may pose the same hazard as the spilt product. Store in accordance with: Dangerous Substances and Explosive Atmospheres Regulations 2002 (DSEAR) |
| 7.3 Specific end use(s) Recommendations | : Not available. |

Industrial sector specific : Not available. *solutions*

Good housekeeping standards, regular safe removal of waste materials will minimise the risks of spontaneous combustion and other fire hazards.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

SECTION 8: Exposure controls/personal protection

| Recommended monitoring procedures | : | If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required. |
|--------------------------------------|-----|--|
| DNELs/DMELs | | |
| No DNELs/DMELs available. | | |
| PNECs | | |
| No PNECs available | | |
| 8.2 Exposure controls | | |
| Appropriate engineering controls | | Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn. |
| | : | Users are advised to consider national Occupational Exposure Limits or other equivalent values. |
| Individual protection measu | res | <u>S</u> |
| Hygiene measures | : | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. |
| Eye/face protection | : | Use safety eyewear designed to protect against splash of liquids. |
| Skin protection | | |
| Hand protection | | Wear suitable gloves tested to EN374. |
| Gloves | : | Short Term Exposure less than 10 minutes Continuous use Nitrile gloves. Hazardous ingredients Section 3 For more than 4 hours of protection in the presence of Butanone Acetone or Methyl isobutyl ketone Butyl gloves 0.7mm For more than 4 hours of protection in the presence of Aromatic solvent use polyvinyl alcohol (PVA) gloves. |
| | | Long Term Exposure Spill / For prolonged or repeated handling, use PE / PE Laminate gloves > 8 hours (breakthrough time) . |
| | | There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. |
| | | Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used |
| | | correctly. The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be |
| | | applied once exposure has occurred. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. |
| Body protection | : | Personnel should wear antistatic clothing made of natural fibres or of high- temperature-resistant synthetic fibres. |
| | | |

SECTION 8: Exposure controls/personal protection

| | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods. |
|------------------------------------|--|
| Other skin protection | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : Approved/certified respirator with organic vapour cartridge. Filter type: A2P2 (EN14387). |
| Environmental exposure controls | : Do not allow to enter drains or watercourses. |

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

SECTION 9: Physical and chemical properties

| 9.1 Information on basic physical | l a | nd chemical properties |
|--|-----|--|
| <u>Appearance</u> | | |
| Physical state | : | Liquid. |
| Colour | : | White to yellowish. |
| Odour | : | Hydrocarbon. [Strong] |
| Odour threshold | : | Not Available (Not Tested). |
| pН | : | Testing not technically possible. |
| Melting point/freezing point | : | Not Available (Not Tested). |
| Initial boiling point and boiling range | : | Not Available (Not Tested). |
| | | Closed cup: 39°C |
| Flash point Evaporation rate | | Slower than Ether Phase |
| • | | |
| Flammability (solid, gas) Burning time | | Not Available (Not Tested). Not Available (Not Tested). |
| Burning rate | | Not Available (Not Tested). |
| Upper/lower flammability or | | Not Available (Not Tested). |
| explosive limits | • | Not Available (Not Tested). |
| Vapour pressure | : | Not Available (Not Tested). |
| Vapour density | : | Not Available (Not Tested). |
| Relative density | : | Not Available (Not Tested). |
| Solubility(ies) | : | Not Available (Not Tested). |
| Solubility in water | : | Not Available (Not Tested). |
| Partition coefficient: n-octanol/ water | : | Not Available (Not Tested). |
| Auto-ignition temperature | : | Not Available (Not Tested). |
| Decomposition temperature | : | Not Available (Not Tested). |
| Viscosity | : | Not Available (Not Tested). |
| Explosive properties | : | Not Available (Not Tested). |
| Oxidising properties | : | Under normal conditions of storage and use, hazardous |
| | | |

9.2 Other information

reactions will not occur.

| SECTION 10: Stability and reactivity | | | | | | |
|--|--|--|--|--|--|--|
| 10.1 Reactivity | : No specific test data related to reactivity available for this product or its ingredients. | | | | | |
| 10.2 Chemical stability | : Stable under recommended storage and handling conditions (see Section 7). | | | | | |
| 10.3 Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. | | | | | |
| 10.4 Conditions to avoid | : When exposed to high temperatures may produce hazardous decomposition products. | | | | | |
| 10.5 Incompatible materials | : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids. | | | | | |
| 10.6 Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. | | | | | |
| Pofor to Soction 7. HANDLIN | IC AND STOPACE and Section & EVENSURE CONTROL S/REDSONAL | | | | | |

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|------------------------|---------|------------|----------|
| Hydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics, < 2% aromatics | LC50 Inhalation Vapour | Rat | 8500 mg/m³ | 4 hours |
| | LD50 Oral | Rat | >6 g/kg | - |

Acute toxicity estimates

No data available

Irritation/Corrosion

No data available

Sensitisation

No data available

Mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

SECTION 11: Toxicological information

No data available

Teratogenicity

No data available

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|--|------------|-------------------|------------------|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics | Category 3 | Not applicable. | Narcotic effects |

Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category | Route of | Target organs |
|-------------------------|----------|----------|---------------|
| | | exposure | |

No data available

| Aspiration hazard | | | | |
|---|--------------------------------|--|--|--|
| Product/ingredient name | Result | | | |
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics | ASPIRATION HAZARD - Category 1 | | | |
| Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) | ASPIRATION HAZARD - Category 1 | | | |

Other information

: Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

12.2 Persistence and degradability

| Product/ingredient name | Test | Result | | Dose | | Inoculum |
|-------------------------|-------------------|--------|------------|------|--------|------------|
| No data available | | | | | | |
| Product/ingredient name | Aquatic half-life | | Photolysis | | Biodeg | radability |
| No data available | | | 1 | | | |

12.3 Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|---|--------|------------|-----------|
| Hydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics, < 2% aromatics | - | 10 to 2500 | high |

12.4 Mobility in soil

| Soil/water partition coefficient (Koc) | : Not available. |
|--|------------------|
| Mobility | : Not available. |

12.5 Results of PBT and vPvB assessment

| PBT | : Not applicable. |
|------|-------------------|
| vPvB | : Not applicable. |

SECTION 12: Ecological information

| 12.6 C |)ther a | dverse | effects |
|--------|---------|--------|---------|
|--------|---------|--------|---------|

: No known significant effects or critical hazards.

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

| <u>Product</u> | | |
|---|---|--|
| Methods of disposal | : | The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. |
| Hazardous waste | : | Yes. |
| European waste catalogue (EWC) | : | waste paint and varnish containing organic solvents or other dangerous substances 08 01 11* |
| Disposal considerations | : | Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority. |
| Packaging | | |
| Methods of disposal | : | The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. |
| Disposal considerations | : | Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions. |
| European waste catalogue (EWC) Contaminated packaging | : | Recycling possible. Ensure packaging is completely empty before recycling. Dispose of uncured residues in the same way as the product itself. Plastic articles 15 01 02 - metallic packaging 15 01 04 - mixed packaging 15 01 06. 15 01 10* packaging containing residues of or contaminated by dangerous substances |
| Special precautions | : | This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. |

SECTION 14: Transport information

| | ADR/RID | IMDG | ΙΑΤΑ |
|---|------------------------|-------------|--------|
| 14.1 UN number | UN1263 | UN1263 | UN1263 |
| 14.2 UN proper shipping name | PAINT | PAINT | PAINT |
| 14.3 Transport Hazard Class(es)/ Label(s) | 3 | 3 | 3 |
| 14.4 Packing group | 111 | 111 | |
| Date of issue/Date of rev | ision : 09, Jun, 2014. | Version : 1 | 10/1 |

| COLRON REFINED FINISHING WAX | | | |
|-----------------------------------|--|-----|-----|
| SECTION 14: Transport information | | | |
| 14.5 Environmental hazards | No. | No. | No. |
| Additional information | Special provisions 640 (E) <u>Tunnel code</u> (D/E) | - | - |

Do not carry by air without prior consent of the airline

14.6 Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk: Not available.according to Annex II ofMARPOL 73/78 and the IBCCode

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market

and use of certain dangerous substances, mixtures and articles

Other EU regulations

| Seveso II Directive | : This product is controlled under the Seveso II Directive. |
|------------------------------------|--|
| 15.2 Chemical Safety Assessment | : This product contains substances for which Chemical Safety Assessments are still required. |

SECTION 16: Other information

Indicates information that has changed from previously issued version.

| Abbreviations and | : ATE = Acute Toxicity Estimate |
|-------------------|---|
| acronyms | CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. |
| | 1272/2008] |
| | DMEL = Derived Minimal Effect Level |
| | DNEL = Derived No Effect Level |
| | EUH statement = CLP-specific Hazard statement |
| | PBT = Persistent, Bioaccumulative and Toxic |
| | PNEC = Predicted No Effect Concentration |
| | RRN = REACH Registration Number |
| | vPvB = Very Persistent and Very Bioaccumulative |

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | | Justification |
|---|---|---|
| Flam. Liq. 3, H226 STOT SE 3, H336 (Narcotic effects) Aquatic Chronic 3, H412 | | On basis of test data Calculation method Calculation method |
| Full text of abbreviated H statements | H304 May be H336 (Narcotic May cau effects) H411 Toxic to | able liquid and vapour. fatal if swallowed and enters airways. use drowsiness or dizziness. (Narcotic effects) o aquatic life with long lasting effects. I to aquatic life with long lasting effects. |
| Full text of classifications [CLP/GHS] | | LONG-TERM AQUATIC HAZARD - Category 2 LONG-TERM AQUATIC HAZARD - Category 3 ASPIRATION HAZARD - Category 1 FLAMMABLE LIQUIDS - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 |
| Full text of abbreviated R phrases | R66- Repeated exposure R67- Vapours may cause R51/53- Toxic to aquatic of aquatic environment. | e lung damage if swallowed. may cause skin dryness or cracking. drowsiness and dizziness. organisms, may cause long-term adverse effects in the ic organisms, may cause long-term adverse effects in the |
| Full text of classifications [DSD/DPD] | : Xn - Harmful N - Dangerous for the env | vironment |

PREPARATION OF SURFACES PRIOR TO FINISHING Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood or metal as they may contain harmful lead. Where possible, wet flatting methods or chemical strippers should be used to avoid the creation of dust. When dry flatting cannot be avoided and local exhaust ventilation is not available, a dust respirator to BS 2091, fitted with a particulate cartridge, and suitable for lead dust, should be worn.

People not involved with the work should be excluded from the area, until thorough cleaning has been carried out. Children and pregnant women should particularly be excluded.

Refer to the Control of Lead at Work Regulations regarding protective clothing and personal hygiene measures. Dusts should be contained and effectively and thoroughly cleaned up.

| Date of printing | : 20, Jan, 2015. |
|---------------------------------|--|
| Date of issue/ Date of revision | : 09, Jun, 2014. |
| Date of previous issue | : No previous validation. |
| | If there is no previous validation date please contact your supplier for more information. |
| Version | : 1 |
| Notice to reader | |

SECTION 16: Other information

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.