

QUICK DRY MASONRY PAINT

Page: 1

Compilation date: 27/08/2015

**Revision date: 26/02/2018** 

Revision No: 3

## Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: QUICK DRY MASONRY PAINT

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd

Waterloo Road Cricklewood London

NW27TX

United Kingdom

Tel: +44 (0)208 450 4666

Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

### 1.4. Emergency telephone number

Emergency tel: .+44(0)2084504666 (Office hours only)

# Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CLP: -: EUH208

Most important adverse effects: Contains 5-chloro-2-methyl-2h-isothiazol-3-one(acticide fsn). May produce an allergic

reaction.

## 2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains 5-chloro-2-methyl-2h-isothiazol-3-one(acticide fsn). May produce an

allergic reaction.

Precautionary statements: P102: Keep out of reach of children.

P302+352: IF ON SKIN: Wash with plenty of water/soap. P301+310: IF SWALLOWED: Immediately call a doctor.

P262: Do not get in eyes, on skin, or on clothing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P280: Wear protective gloves and eye protection.

QUICK DRY MASONRY PAINT

Page: 2

#### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

### Section 3: Composition/information on ingredients

#### 3.2. Mixtures

### **Hazardous ingredients:**

#### 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE

| EINECS | CAS        | PBT / WEL | CLP Classification                 | Percent |
|--------|------------|-----------|------------------------------------|---------|
| -      | 55965-84-9 | -         | Skin Corr. 1B: H314; Skin Sens. 1: | 0.200%  |
|        |            |           | H317                               |         |

#### Section 4: First aid measures

### 4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and

footwear immediately unless stuck to skin.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: No data available.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# 4.3. Indication of any immediate medical attention and special treatment needed

# Section 5: Fire-fighting measures

## 5.1. Extinguishing media

**Extinguishing media:** Dry chemical powder. Alcohol resistant foam. Water spray. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

## 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

### Section 6: Accidental release measures

QUICK DRY MASONRY PAINT

Page: 3

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised

personnel. Do not attempt to take action without suitable protective clothing - see section

8 of SDS. Mechanically ventilate the spillage area whilst avoiding the formation of

explosive concentrations - see section 9 of SDS.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a suitable container.

#### 6.4. Reference to other sections

#### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from direct sunlight. Keep container

tightly closed. Ensure a retention tank is installed.

Suitable packaging: Must only be kept in original packaging.

## 7.3. Specific end use(s)

# Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

Workplace exposure limits: No data available.

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

## 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure a retention tank is installed.

Respiratory protection: Respiratory protection not required. Self-contained breathing apparatus must be

available in case of emergency.

Hand protection: Protective gloves.Eye protection: Safety glasses.Skin protection: Protective clothing.

### Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Liquid

QUICK DRY MASONRY PAINT

Page: 4

Colour: Various

Odour: Low.

Evaporation rate: No data available.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Miscible

Viscosity: Viscous

Boiling point/range°C: 100 Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: >93 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

**Relative density:** 1.24-1.25 @ 20 C **pH:** No data available.

VOC g/I: No data available.

#### 9.2. Other information

Other information: No data available.

### Section 10: Stability and reactivity

#### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

## 10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat.

### 10.5. Incompatible materials

Materials to avoid: Oxidising agents. Strong acids.

# 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

### **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

Toxicity values: No data available.

### Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: No data available.

QUICK DRY MASONRY PAINT

Page: 5

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

#### Section 13: Disposal considerations

## 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

# **Section 14: Transport information**

14.1. UN number

**UN number: NOT CLASSIFIED** 

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

### QUICK DRY MASONRY PAINT

Page: 6

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

#### Section 16: Other information

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.