

**AkzoNobel** 

## **SAFETY DATA SHEET**

### POLYFILLA EXPANDING FOAM

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1. Product identifier

Product name : POLYFILLA EXPANDING FOAM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product use : Aerosol.

1.3. Details of the supplier of the safety data sheet

ICI Paints AkzoNobel, Wexham Road,

Slough, Berkshire, SL2 5DS, U.K.

Tel.: +44 (0) 333 222 70 70 www.polycelltrade.co.uk

e-mail address of person responsible for this SDS

: polycell.advice@akzonobel.com

1.4 Emergency telephone number

**Telephone number** : Slough +44 (0) 1753 550000

Version : 4.09

Date of previous issue : 27-8-2020

## SECTION 2: Hazards identification

## 2.1 Classification of the substance or mixture

**Product definition**: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aerosol 1, H222, H229 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373

Ingredients of unknown

: 0%

toxicity

Ingredients of unknown : 0%

ecotoxicity

See Section 16 for the full text of the H statements declared above.

Date of issue/Date of revision : 31-8-2020 Page: 1/15

## **SECTION 2: Hazards identification**

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms







Signal word : Danger

**Hazard statements** : H222 - Extremely flammable aerosol.

H332 - Harmful if inhaled.

H319 - Causes serious eye irritation.

H315 - Causes skin irritation.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 - May cause an allergic skin reaction. H362 - May cause harm to breast-fed children.

H351 - Suspected of causing cancer. H335 - May cause respiratory irritation.

H373 - May cause damage to organs through prolonged or repeated exposure.

H413 - May cause long lasting harmful effects to aquatic life.

H229 - Pressurised container: May burst if heated.

### **Precautionary statements**

General: P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

**Prevention**: P201 - Obtain special instructions before use.

P280 - Wear protective gloves. Wear eye or face protection. P211 - Do not spray on an open flame or other ignition source.

P260 - Do not breathe dust or mist.

P263 - Avoid contact during pregnancy or while nursing.

P251 - Do not pierce or burn, even after use.P352 - Wash with plenty of soap and water.

P340 - Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

P351 - Rinse cautiously with water for several minutes.

P338 - Remove contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a POISON CENTER or doctor if you feel unwell.

Storage : P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50

°C/122 °F.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national or international regulations.

**Hazardous ingredients** 

Supplemental label

elements

Response

elements Supplemental label

Supplemental label elements (CEPE)

: Formaldehyde, oligomeric reaction products with aniline and phosgene

: Not applicable.

: Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should

avoid contact, including dermal contact, with this product.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

## **Special packaging requirements**

Containers to be fitted with child-resistant

: Not applicable.

fastenings

Tactile warning of danger : Yes, applicable.

Date of issue/Date of revision : 31-8-2020 Page: 2/15

## **SECTION 2: Hazards identification**

#### 2.3 Other hazards

Other hazards which do not result in classification

: None known.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
Formaldehyde, oligomeric reaction products with aniline and phosgene	EC: 500-079-6 CAS: 32055-14-4 Index: 615-005-00-9	≥50 - ≤75	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373	[1]
Alkanes, C14-17, chloro	REACH #: 01-2119519269-33 EC: 287-477-0 CAS: 85535-85-9 Index: 602-095-00-X	≥10 - ≤25	Lact., H362 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1) EUH066	[1]
dimethyl ether	REACH #: 01-2119472128-37 EC: 204-065-8 CAS: 115-10-6 Index: 603-019-00-8	≥10 - ≤25	Flam. Gas 1, H220 Press. Gas Comp. Gas, H280	[2]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

## <u>Type</u>

**Eye contact** 

Inhalation

**Skin contact** 

Ingestion

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

## 4.1 Description of first aid measures

General : In all cases of doub anything by mouth

: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

Date of issue/Date of revision : 31-8-2020

Page: 3/15

## **SECTION 4: First aid measures**

#### **Protection of first-aiders**

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains methylenediphenyl diisocyanate. May produce an allergic reaction.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

See toxicological information (Section 11)

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media

: Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.

Unsuitable extinguishing media

: Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous combustion products

: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters

: Appropriate breathing apparatus may be required.

Date of issue/Date of revision : 31-8-2020 Page: 4/15

## **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

For emergency responders:

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**6.2 Environmental precautions** 

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

## 7.1 Precautions for safe handling

Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.

Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

## 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

## Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

## Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### 7.3 Specific end use(s)

**Recommendations**: Not available.

Date of issue/Date of revision : 31-8-2020 Page: 5/15

## **SECTION 7: Handling and storage**

Industrial sector specific

: Not available.

solutions

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

## Occupational exposure limits

Product/ingredient name	Exposure limit values
dimethyl ether	EH40/2005 WELs (United Kingdom (UK), 12/2011).
	STEL: 958 mg/m³ 15 minutes.
	STEL: 500 ppm 15 minutes.
	TWA: 400 ppm 8 hours.
	TWA: 766 mg/m³ 8 hours.

## Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

DNEL DNEL	Long term Inhalation Short term	0,05 mg/m³	Workers	Systemic
DNEL				
DNEL	Short term			
		0,1 mg/m³	Workers	Systemic
DNEL		0.025 mg/	Concumora	Local
DINEL		,	Consumers	Local
DNEL			Consumers	Local
	Inhalation	o,oog		
DNEL	Long term	6,7 mg/m <sup>3</sup>	Workers	Systemic
	Inhalation			
DNEL	Long term Dermal		Workers	Systemic
DNEL	l on a torm		Canaumara	Cyatamia
DINEL	•	z mg/m²	Consumers	Systemic
DNFI		28 75 mg/	Consumers	Systemic
5.122	Long tomi oran		Concamore	Cycloniic
DNEL	Long term Oral	0,58 mg/	Consumers	Systemic
		kg bw/day		
DNEL	•		Workers	Systemic
DNE			0	0
DNEL		471 mg/m <sup>3</sup>	Consumers	Systemic
	DNEL DNEL DNEL DNEL DNEL	Inhalation Long term Inhalation Short term Inhalation Long term Inhalation Long term Inhalation Long term Dermal DNEL Long term Inhalation Long term Inhalation Long term Oral DNEL Long term Oral DNEL Long term Inhalation	Inhalation Long term Inhalation Short term Inhalation ONEL ONEL ONEL Cong term Inhalation I	Inhalation Long term Inhalation Short term Inhalation ONEL ONEL ONEL ONEL ONEL ONEL ONEL ONEL

## **PNECs**

Date of issue/Date of revision : 31-8-2020 Page: 6/15

## **SECTION 8: Exposure controls/personal protection**

Product/ingredient name	Compartment Detail	Value	Method Detail
Formaldehyde, oligomeric reaction products with aniline and phosgene	Fresh water	1 mg/l	Assessment Factors
	Marine water	0,1 mg/l	Assessment Factors
	Sewage Treatment Plant	1 mg/l	Assessment Factors
	Soil	1 mg/kg dwt	Assessment Factors
Alkanes, C14-17, chloro	Fresh water	1 μg/l	Assessment Factors
	Marine water	0,2 µg/l	Assessment Factors
	Sewage Treatment Plant	80 μg/l	Assessment Factors
	Fresh water sediment	13 mg/kg	Assessment Factors
	Marine water sediment	2,6 mg/kg dwt	Assessment Factors
	Soil	11,9 mg/kg dwt	Assessment Factors
	Secondary Poisoning	10 mg/kg	Assessment Factors
dimethyl ether	Fresh water	0,155 mg/l	Assessment Factors
	Marine water	0,016 mg/l	Assessment Factors
	Sewage Treatment Plant	160 mg/l	Assessment Factors
	Fresh water sediment	0,681 mg/kg dwt	-
	Marine water sediment	0,069 mg/kg dwt	-
	Soil	0,045 mg/kg dwt	-

#### 8.2 Exposure controls

Appropriate engineering controls

: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## Eye/face protection Skin protection

: Use safety eyewear designed to protect against splash of liquids.

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton ® or Nitrile, thickness ≥ 0.38 mm.

When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended.

Recommended gloves: Nitrile, thickness ≥ 0.12 mm.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

**Body protection** 

Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Date of issue/Date of revision : 31-8-2020 Page: 7/15

## **SECTION 8: Exposure controls/personal protection**

#### OLD LEAD-BASED PAINTS:

When surfaces are to be prepared for painting, account should be taken of the age of the property and the possibility that lead-pigmented paint might be present. There is a possibility that ingestion or inhalation of scrapings or dust arising from the preparation work could cause health effects. As a working rule you should assume that this will be the case if the age of the property is pre 1960.

Where possible wet sanding or chemical stripping methods should be used with surfaces of this type to avoid the creation of dust. When dry sanding cannot be avoided, and effective local exhaust ventilation is not available, it is recommended that a dust respirator is worn, that is approved for use with lead dusts, and its type selected on the basis of the COSHH assessment, taking into account the Workplace Exposure Limit for lead in air. Furthermore, steps should be taken to ensure containment of the dusts created, and that all practicable measures are taken to clean up thoroughly all deposits of dusts in and around the affected area.

Respiratory protection in case of dust or spray mist formation. (particle filter EN143 type P2) Respiratory protection in case of vapour formation. (half mask with combination filter A2-P2 til concentrations of 0,5 Vol%.)

The current Control of Lead at Work Regulations approved code of practice should be consulted for advice on protective clothing and personal hygiene precautions. Care should also be taken to exclude visitors, members of the household and especially children from the affected area, during the actual work and the subsequent clean up operations. All scrapings, dust, etc. should be disposed of by the professional painting contractor as Hazardous Waste.

Extra precautions will also need to be taken when burning off old lead-based paints because fumes containing lead will be produced. It is recommended that a respirator, approved for use with particulate fumes of lead is selected on the basis of the COSHH assessment, taking into account the Workplace Exposure Limit for lead in air. Similar precautions to those given above about sanding should be taken with reference to protective clothing, disposal of scrapings and dusts, and exclusion of other personnel and especially children from the building during actual work and the subsequent clean up operations.

Avoid the inhalation of dust. Wear suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

**Environmental exposure** controls

: Do not allow to enter drains or watercourses.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

**Appearance** 

Physical state : Liquid.

Colour : Various: See label.

Odour : Characteristic.

Odour threshold : Not available.

pH : Not available.

Melting point/freezing point : Not available.

Initial boiling point and boiling : Not available.

range

Flash point : Not applicable.

Evaporation rate : Not available.

Date of issue/Date of revision : 31-8-2020 Page: 8/15

## SECTION 9: Physical and chemical properties

Upper/lower flammability or

explosive limits

: Lower: 3% Upper: 16%

: Not available. Vapour pressure : Not available. Vapour density

**Relative density** : 0.986

: Insoluble in the following materials: cold water. Solubility(ies)

Partition coefficient: n-octanol/ : Not available.

water

**Auto-ignition temperature** : Not available. **Decomposition temperature** : Not available.

: Kinematic (room temperature): 10,13 cm<sup>2</sup>/s **Viscosity** 

**Explosive properties** : Not available. **Oxidising properties** : Not available.

9.2. Other information

Solubility in water : Not available.

Type of aerosol : Foam

## SECTION 10: Stability and reactivity

10.1 Reactivity

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

: Keep away from the following materials to prevent strong exothermic reactions: 10.5 Incompatible materials

oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products : Decomposition products may include the following materials: carbon monoxide,

carbon dioxide, smoke, oxides of nitrogen.

## SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains methylenediphenyl diisocyanate. May produce an allergic reaction.

**Acute toxicity** 

Date of issue/Date of revision : 31-8-2020 Page: 9/15

## **SECTION 11: Toxicological information**

Product/ingredient name	Result	Species	Dose	Exposure
Formaldehyde, oligomeric reaction products with aniline and phosgene	LC50 Inhalation	Rat - Male, Female	0,31 mg/l	4 hours
	LD50 Dermal	Rabbit - Male, Female	>9400 mg/kg	-
dimethyl ether	LD50 Oral LC50 Inhalation Gas.	Rat - Male Rat	>10000 mg/kg 308000 mg/m³	- 4 hours

**Conclusion/Summary** 

: Not available.

**Acute toxicity estimates** 

Not available.

## **Irritation/Corrosion**

Pr	oduct/ingredient name	Result	Species	Score	Exposure	Observation
rea	maldehyde, oligomeric ction products with line and phosgene	Skin - Mild irritant	Rabbit	-	-	-

Conclusion/Summary

: Not available.

## **Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
Formaldehyde, oligomeric reaction products with aniline and phosgene	skin	Guinea pig	Not sensitizing
, , , , , , , , , , , , , , , , , , ,	Respiratory	Rat	Sensitising

**Conclusion/Summary** 

: Not available.

**Mutagenicity** 

**Conclusion/Summary** 

: Not available.

## **Carcinogenicity**

Product/ingredient name	Result	Species	Dose	Exposure
Formaldehyde, oligomeric reaction products with aniline and phosgene	Positive - Inhalation - TD	Rat - Male, Female	-	-

**Conclusion/Summary** 

: Not available.

Reproductive toxicity

Conclusion/Summary : Not a

: Not available.

**Teratogenicity** 

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
131079	Category 3	Not applicable.	Respiratory tract irritation
Formaldehyde, oligomeric reaction products with aniline and phosgene	Category 3	Not applicable.	Respiratory tract irritation

## Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
131079 Formaldehyde, oligomeric reaction products with aniline and phosgene	5 - 7		Not determined Not determined

## **Aspiration hazard**

Date of issue/Date of revision : 31-8-2020 Page: 10/15

## **SECTION 11: Toxicological information**

Not available.

Other information : Not available.

## **SECTION 12: Ecological information**

## 12.1 Toxicity

Do not allow to enter drains or watercourses.

Product/ingredient name	Result	Species	Exposure
Formaldehyde, oligomeric reaction products with aniline and phosgene	Acute EC50 >1,64 mg/l	Algae	72 hours
	Acute EC50 >1 mg/l Acute EC50 >100 mg/l Acute LC50 >1 mg/l Chronic NOEC >10 mg/l	Daphnia - Daphnia magna Micro-organism Fish - Danio rerio Daphnia - Daphnia magna	24 hours 3 hours 96 hours 21 days

**Conclusion/Summary** 

: No known significant effects or critical hazards.

## 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Formaldehyde, oligomeric reaction products with aniline and phosgene	OECD 302 302C Inherent Biodegradability: Modified MITI Test (II)	0 % - Not readily - 288 days	-	-

**Conclusion/Summary** 

: Based on available data, the classification criteria are not met.

### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Formaldehyde, oligomeric reaction products with aniline and phosgene	-	200	low
dimethyl ether	0,1	-	low

### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility

: Not available.

#### 12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

P: Not available. B: Not available. T: Not available.

vPvB : Not applicable.

vP: Not available. vB: Not available.

## **12.6 Other adverse effects** : No known significant effects or critical hazards.

Date of issue/Date of revision : 31-8-2020 Page: 11/15

## **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal** : The gene

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

#### **Hazardous waste**

: Yes

**Disposal considerations** 

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no

longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

#### **European waste catalogue (EWC)**

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
16 05 04*	gases in pressure containers (including halons) containing hazardous substances

#### **Packaging**

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Disposal considerations** 

: Using information provided in this safety data sheet, advice should be obtained from

the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or

national legal provisions.

Type of packaging		European waste catalogue (EWC)
Container	15 01 10*	packaging containing residues of or contaminated by hazardous substances

#### **Special precautions**

: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## **SECTION 14: Transport information**

Information pertaining to IATA and ADN is considered not relevant since the material is not packaged in the correct approved packaging required of these methods of transport.

ADR	IMDG
UN1950	UN1950
AEROSOLS	AEROSOLS
2	2.1
-	-
Not applicable.	Not applicable.
	UN1950  AEROSOLS  2  -

Date of issue/Date of revision : 31-8-2020 Page: 12/15

Information pertaining to IATA and ADN is considered not relevant since the material is not packaged in the correct approved packaging required of these methods of transport.

No.	No.		
	Not available.		
Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.			
Not applicable.	F-D,S-U		
14.7 Transport in bulk : Not applicable. according to Annex II of MARPOL and the IBC Code			
Tunnel code (D)	-		
	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.  Not applicable.  Ik : Not applicable.  Il of C Code  Tunnel code		

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed, or the component present is below its threshold.

Substances of very high concern

None of the components are listed, or the component present is below its threshold.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

**VOC for Ready-for-Use** : Not applicable.

**Mixture** 

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Aerosol dispensers :

3

## **SECTION 15: Regulatory information**



#### Extremely flammable

#### **Seveso Directive**

This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.

#### **International regulations**

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

15.2 Chemical safety

assessment

: No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

CEPE code : 1

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative

## Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aerosol 1, H222, H229	Expert judgment
Acute Tox. 4, H332	On basis of test data
Skin Irrit. 2, H315	Expert judgment
Eye Irrit. 2, H319	Expert judgment
Resp. Sens. 1, H334	Expert judgment
Skin Sens. 1, H317	Expert judgment
Carc. 2, H351	Expert judgment
STOT SE 3, H335	Expert judgment
STOT RE 2, H373	Expert judgment

Full text of abbreviated H statements

Date of issue/Date of revision : 31-8-2020 Page: 14/15

## **SECTION 16: Other information**

H220	Extremely flammable gas.
H222, H229	Extremely flammable aerosol. Pressurised container: May burst if
	heated.
H280	Contains gas under pressure; may explode if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if
	inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H362	May cause harm to breast-fed children.
H373	May cause damage to organs through prolonged or repeated
	exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

## Full text of classifications [CLP/GHS]

ACUTE TOXICITY (inhalation) - Category 4 Acute Tox. 4, H332 Aerosol 1, H222, H229 **AEROSOLS - Category 1** SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 Aquatic Acute 1, H400 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 Aquatic Chronic 1, H410 Carc. 2, H351 CARCINOGENICITY - Category 2 **EUH066** Repeated exposure may cause skin dryness or cracking. Eve Irrit. 2, H319 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 Flam. Gas 1, H220 FLAMMABLE GASES - Category 1 Lact., H362 REPRODUCTIVE TOXICITY - Effects on or via lactation GASES UNDER PRESSURE - Compressed gas Press. Gas Comp. Gas, H280 Resp. Sens. 1, H334 **RESPIRATORY SENSITISATION - Category 1** SKIN CORROSION/IRRITATION - Category 2 Skin Irrit. 2, H315 Skin Sens. 1, H317 SKIN SENSITISATION - Category 1 **STOT RE 2, H373** SPECIFIC TARGET ORGAN TOXICITY - REPEATED **EXPOSURE - Category 2** SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE **STOT SE 3, H335** (Respiratory tract irritation) - Category 3

Date of printing : 2-9-2020 Date of issue/ Date of : 31-8-2020

revision

Date of previous issue : 27-8-2020 Version : 4.09

#### **Notice to reader**

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.

## **Head Office**

AkzoNobel Decorative Coatings BV, Christian Neefestraat 2, 1077 WW Amsterdam, The Netherlands

Date of issue/Date of revision : 31-8-2020