SAFETY DATA SHEET

2 PART WOODFILLER HARDENER

Page: 1

Compilation date: 04-05-2017

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: 2 PART WOODFILLER HARDENER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC9b: Fillers, putties, plasters, modelling clay.

1.3. Details of the supplier of the safety data sheet

Company name: Tembe DIY Products Ltd

13 Delta Court

Sky Business Park

Doncaster

DN9 3GN

United Kingdom

Tel: +44 (0) 1302 770 234

Email: aaron.moore@tembediy.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 1302 770 234

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Acute 1: H400; Eye Irrit. 2: H319; Org. Perox. EF: H242; Skin Sens. 1: H317 Most important adverse effects:

2.2. Label elements

Label elements: Hazard statements:

Hazard pictograms:

Heating may cause a fire. May cause an allergic skin reaction. Causes serious eye irritation. Very toxic to aquatic life.

Page: 2

[cont...]

H242: Heating may cause a fire.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H400: Very toxic to aquatic life.

GHS02: Flame

GHS07: Exclamation mark

GHS09: Environmental



Signal words:WarningPrecautionary statements:P102: Keep out of reach of children.P501: Dispose of contents/container to hazardous or special waste collection point.P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition
sources. No smoking.P220: Keep away from combustible materials.P273: Avoid release to the environment.P280: Wear protective gloves/protective clothing/eye protection/face protection.P302+352: IF ON SKIN: Wash with plenty of water/.P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove
contact lenses, if present and easy to do. Continue rinsing.P333+313: If skin irritation or rash occurs: Get medical advice/attention.P420: Store away from other materials.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

DIBENZOYL PEROXIDE

	EINECS	CAS	PBT / WEL	CLP Classification	Percent
	202-327-6	94-36-0	-	Skin Sens. 1: H317; Org. Perox. B: H241; Eye Irrit. 2: H319	30-50%
oct	ion 4. First aid	mossuros			

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion:	Wash out mouth with water. Consult a doctor.
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with

skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not create dust.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DIBENZOYL PEROXIDE

Workplace exposure limits:

Vorkplace exposure limits:						
	State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL	
	UK	5 mg/m3	-	-	-	

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste Colour: White

SAFETY DATA SHEET

2 PART WOODFILLER HARDENER

Page: 5

Odour:	Barely	perceptible	odour
--------	--------	-------------	-------

Oxidising: Oxidising (by EC criteria)

Solubility in water: Insoluble

Flash point°C: 23 - 60

Relative density: 1.1

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. SADT = 50 Degrees Celcius. This is the lowest

temperature at which self accelerating decomposition may occur. Contact with

incompatible substances can cause decomposition at or below the SADT.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Bases. Strong acids. Reducing agents. Amines.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DIBENZOYL PEROXIDE

ORL	MUS	LD50	5700	mg/kg
ORL	RAT	LD50	7710	mg/kg

Relevant hazards for product:

Hazard	Route	Basis	

Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

	Species	Test	Value	Units
	Daphnia magna	48H EC50	0.11	mg/l
	RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	0.0602	mg/l
12	2 Persistence and degradability			

12.2. Persistence and degradability

Persistence and degradability: Readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Very toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Page: 7

Section 14: Transport information

14.1. UN number

UN number: UN3108

14.2. UN proper shipping name

Shipping name: ORGANIC PEROXIDE, TYPE E, SOLID

14.3. Transport hazard class(es)

Transport class: 5.2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

SAFETY DATA SHEET

2 PART WOODFILLER HARDENER

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D Transport

category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assess	15.2. Chemical Safety Assessment		
Chemical safety assessment:	A chemical safety assessment has not been carried out for the substance or the mixture		
	by the supplier.		

Section 16: Other information

ther information	
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H241: Heating may cause a fire or explosion.
	H242: Heating may cause a fire.
	H317: May cause an allergic skin reaction.
	H319: Causes serious eye irritation.
	H400: Very toxic to aquatic life.
•	The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage
	resulting from handling or from contact with the above product.

Page: 8