

COO-VAR®

PAINTS, PRIMERS AND SPECIALISED COATINGS

SAFETY DATA SHEET

101/W101 - ACID ETCH FOR FLOORS

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 101/W101 - ACID ETCH FOR FLOORS

Product number 101/W101/1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Etchant / cleaner.

1.3. Details of the supplier of the safety data sheet

Supplier COO-VAR
Lockwood Street
Hull
HU2 0HN
+44 (0) 1482 328053(T)
+44 (0) 1482 219266(F)
info@coo-var.co.uk

Contact person Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 328053 Coo-Var (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SDS No. 10622

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Corr. 1B - H314 STOT SE 3 - H335

Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H314 Causes severe skin burns and eye damage.
H335 May cause respiratory irritation.

101/W101 - ACID ETCH FOR FLOORS

Precautionary statements	<p>P102 Keep out of reach of children.</p> <p>P101 If medical advice is needed, have product container or label at hand.</p> <p>P260 Do not breathe fume.</p> <p>P280 Wear protective gloves, eye and face protection.</p> <p>P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
---------------------------------	---

Contains HYDROCHLORIC ACID (<20%)

Supplementary precautionary statements P403+P233 Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

HYDROCHLORIC ACID (<20%)	30-50%
CAS number: 7647-01-0	EC number: 231-595-7
	REACH registration number: 01-2119458860-33-XXXX
Classification	Classification (67/548/EEC or 1999/45/EC)
Skin Corr. 1B - H314	C;R34 Xi;R37
STOT SE 3 - H335	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues. Place unconscious person on their side in the recovery position and ensure breathing can take place. Consult a physician for specific advice.
Ingestion	Rinse nose, mouth and throat with water. Consult a physician for specific advice.
Skin contact	Remove affected person from source of contamination. Rinse immediately with plenty of water. Remove contaminated clothing.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Consult a physician for specific advice.

4.2. Most important symptoms and effects, both acute and delayed

General information	Get medical attention promptly if symptoms occur after washing.
Inhalation	Irritation of nose, throat and airway.
Ingestion	May cause chemical burns in mouth and throat.

101/W101 - ACID ETCH FOR FLOORS

Skin contact May cause serious chemical burns to the skin.

Eye contact Severe irritation, burning and tearing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Water spray.

5.2. Special hazards arising from the substance or mixture

Specific hazards Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent escape of liquid.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Contain spillages using bunding.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

101/W101 - ACID ETCH FOR FLOORS

Usage precautions

Avoid spilling. Avoid contact with skin and eyes. Avoid the formation of mists. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Do not use in confined spaces without adequate ventilation and/or respirator. Observe any occupational exposure limits for the product or ingredients. Avoid inhalation of vapours and spray/mists. Do not eat, drink or smoke when using the product. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep containers upright. Store in tightly closed original container in a dry, cool and well-ventilated place.

Storage class Acid reactive storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

HYDROCHLORIC ACID (<20%)

Short-term exposure limit (15-minute): OES 8 mg/m³ respirable dust

Long-term exposure limit (8-hour TWA): 8 mg/m³ respirable dust

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Personal protection

Unprotected persons should be kept away from treated areas.

Eye/face protection

Wear chemical splash goggles.

Hand protection

To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturer's performance data suggest that the optimum glove for use should be: Rubber (natural, latex). Thickness: > 0.75 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 240 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.

Other skin and body protection

Wear appropriate clothing to prevent reasonably probable skin contact.

Hygiene measures

No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.

101/W101 - ACID ETCH FOR FLOORS

Respiratory protection No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists. In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with combination filter (type A2/P3).

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Thin Clear liquid.
Colour	Red.
Odour	Characteristic. Acidic.
pH	pH (concentrated solution): <2
Melting point	Not determined.
Initial boiling point and range	100°C @ 760 mm Hg
Flash point	°C Not applicable.
Evaporation rate	Not determined.
Flammability (solid, gas)	No specific test data are available.
Upper/lower flammability or explosive limits	No specific test data are available.
Vapour pressure	Not determined.
Relative density	1.04 - 1.06 @ @ 20°C
Solubility(ies)	Soluble in water.
Partition coefficient	No specific test data are available.
Auto-ignition temperature	No information available.
Viscosity	non-viscous @ °C
Explosive properties	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

Volatility	100
Volatile organic compound	No information required.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity The following materials may react with the product: Alkalis. The following materials may react strongly with the product: Alkaline earth metals. Powdered metal.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Will not occur

10.4. Conditions to avoid

101/W101 - ACID ETCH FOR FLOORS

Conditions to avoid Avoid heat. Toxic chlorine gas produced by contact with sodium hypochlorite

10.5. Incompatible materials

Materials to avoid Oxydising agents and strongly acidic materials.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances:
Vapours/gases/fumes of: Hydrogen chloride (HCl).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation Vapour from this product may be hazardous by inhalation. Vapour may irritate respiratory system/lungs.

Ingestion Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.

Skin contact This product is strongly irritating. Prolonged contact may cause burns.

Eye contact Irritating to eyes.

Acute and chronic health hazards This product is corrosive. This product may cause skin and eye irritation. Prolonged contact may cause burns.

Route of exposure Inhalation Ingestion. Skin and/or eye contact.

SECTION 12: Ecological Information

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The product is biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient No specific test data are available.

12.4. Mobility in soil

Mobility Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information When handling waste, the safety precautions applying to handling of the product should be considered. Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

101/W101 - ACID ETCH FOR FLOORS

Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Waste class	Neutralised empty packages, are categorised as non-hazardous waste, with code 15 01 02(plastic packaging) or 15 01 04 (metal packaging)

SECTION 14: Transport information

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.

14.1. UN number

UN No. (ADR/RID)	1789
UN No. (IMDG)	1789
UN No. (ICAO)	1789

14.2. UN proper shipping name

Proper shipping name (ADR/RID) HYDROCHLORIC ACID (LESS THAN 25%)

Proper shipping name (IMDG) HYDROCHLORIC ACID (LESS THAN 25%)

Proper shipping name (ICAO) HYDROCHLORIC ACID (LESS THAN 25%)

14.3. Transport hazard class(es)

ADR/RID class	8
IMDG class	8

Transport labels



14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

ADR transport category	2
Tunnel restriction code	(E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

101/W101 - ACID ETCH FOR FLOORS

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ATE: Acute Toxicity Estimate.
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
 CAS: Chemical Abstracts Service.
 DNEL: Derived No Effect Level.
 GHS: Globally Harmonized System.
 ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.
 IMDG: International Maritime Dangerous Goods.
 LC₅₀: Lethal Concentration to 50 % of a test population.
 PBT: Persistent, Bioaccumulative and Toxic substance.
 PNEC: Predicted No Effect Concentration.
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
 RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
 SVHC: Substances of Very High Concern.
 vPvB: Very Persistent and Very Bioaccumulative.
 MARPOL 73/78: International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978.
 cATpE: Converted Acute Toxicity Point Estimate.
 EC₅₀: 50% of maximal Effective Concentration.

Classification abbreviations and acronyms

Acute Tox. = Acute toxicity
 Aquatic Acute = Hazardous to the aquatic environment (acute)
 Aquatic Chronic = Hazardous to the aquatic environment (chronic)
 Asp. Tox. = Aspiration hazard
 Eye Dam. = Serious eye damage
 Eye Irrit. = Eye irritation
 Met. Corr. = Corrosive to metals
 Resp. Sens. = Respiratory sensitisation
 Skin Corr. = Skin corrosion
 Skin Irrit. = Skin irritation
 Skin Sens. = Skin sensitisation
 STOT RE = Specific target organ toxicity-repeated exposure
 STOT SE = Specific target organ toxicity-single exposure

Revision comments

Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830

Issued by

Technical Dept. (P.E.)

Revision date

02/08/2018

Revision

7

101/W101 - ACID ETCH FOR FLOORS

Supersedes date	30/07/2015
SDS number	10622
SDS status	Approved.
Hazard statements in full	H314 Causes severe skin burns and eye damage. H335 May cause respiratory irritation.
Signature	Initials_____

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.