

QUICK DRY RADIATOR ENAMEL

Page: 1

Compilation date: 03/06/2013

Revision date: 06/01/2020

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: QUICK DRY RADIATOR ENAMEL

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd

Waterloo Road Cricklewood London

NW2 7TX

United Kingdom

Tel: +44 (0)208 450 4666

Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

1.4. Emergency telephone number

Emergency tel: .+44(0)2084504666 (Office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Sens. 1: H317; -: EUH208

Most important adverse effects: Contains texanol, a mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one [ec no 247-500-7]

and 2-methyl-2h-isothiazol-3-o. May produce an allergic reaction. May cause an allergic

skin reaction.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains texanol, a mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one [ec no

247-500-7] and 2-methyl-2h-isothiazol-3-o. May produce an allergic reaction.

H317: May cause an allergic skin reaction.

Hazard pictograms: GHS07: Exclamation mark



Signal words: Warning

Precautionary statements: P102: Keep out of reach of children.

QUICK DRY RADIATOR ENAMEL

Page: 2

P301+P312: IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

P280: Wear protective gloves and eye protection.

P262: Do not get in eyes, on skin, or on clothing.

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

2-(2-BUTOXYETHOXY)ETHANOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-961-6	112-34-5	-	Eye Irrit. 2: H319	3.820%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Dry chemical powder. Carbon dioxide. Alcohol resistant foam. Use water spray to cool

containers. Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

QUICK DRY RADIATOR ENAMEL

Page: 3

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised

personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Eliminate all sources of ignition. Mechanically ventilate the spillage area whilst

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Wash the ground with an appropriate self-

avoiding the formation of explosive concentrations - see section 9 of SDS.

emulsifying solvent.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance.

Smoking is forbidden.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. KEEP AWAY FROM FREEZING, minimum storage

temperature 5 degrees C. Keep away from direct sunlight. Keep container tightly closed.

Suitable packaging: Glass. Coated steel.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2-(2-BUTOXYETHOXY)ETHANOL

Workplace exposure limits: Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
-------	------------	--------------	------------	--------------

QUICK DRY RADIATOR ENAMEL

Page: 4

UK	67.5 mg/m3	101.2 mg/m3	-	-
----	------------	-------------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure a retention tank is installed. **Respiratory protection:** Respiratory protection not required. Self-contained breathing apparatus must be

available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses with side-shields.

Skin protection: Protective clothing, PVC.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Various

Odour: Barely perceptible odour

Evaporation rate: No data available.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Miscible

Flash point°C: >93

Viscosity: Non-viscous

Boiling point/range°C: 100 Melting point/range°C: No data available.

Flammability limits %: lower: No data available.

upper: No data available.Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

Relative density: 1.017-1.027 @ 20 C **pH:** 7.5 - 8.0

VOC g/I: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

QUICK DRY RADIATOR ENAMEL

Page: 5

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2-(2-BUTOXYETHOXY)ETHANOL

ORL	MUS	LD50	6050	mg/kg
ORL	RAT	LD50	4500	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Soluble in water. Volatile. Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

QUICK DRY RADIATOR ENAMEL

Page: 6

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: Not hazardous

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH208: Contains texanol, a mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one [ec no

247-500-7] and 2-methyl-2h-isothiazol-3-o. May produce an allergic reaction.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.