

Prestonett Wood Filler

Beissier

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : Prestonett Wood Filler

1.2. Relevant identified uses of the substance or mixture and uses advised against

Waterborne painting filler for interior use

1.3. Details of the supplier of the safety data sheet

Registered company name : BEISSIER SAS.

Address : Quartier de la gare.77760.LA CHAPELLE LA REINE.FRANCE.

Telephone : +33 1 60 39 61 10. Fax : +33 1 60 39 61 11.

beissier.fds@beissier.fr

www.beissier.fr

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA / <http://www.centres-antipoison.net>.

Other emergency numbers

UK - National Poisons Information Service Phone :

44 / 191 22 5131

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

May produce an allergic reaction (EUH208).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Additional labeling :

EUH208

Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE. May produce an allergic reaction.

EUH208

Contains MIXTURE OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE [EC NO. 247-500-7] AND 2-METHYL-2HISOTHIAZOL-3-ONE [EC NO. 220-239-6] (3:1). May produce an allergic reaction.

EUH210

Safety data sheet available on request.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) \geq 0.1% published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Preparation based on synthetic dispersion, mineral fillers and additives

Prestonett Wood Filler

Composition :

Identification	(EC) 1272/2008	Note	%
INDEX: 1317_65_3 CAS: 1317-65-3 EC: 215-279-6 CARBONATE DE CALCIUM NATUREL		[1]	50 <= x % < 100
INDEX: 613_088_00_6 CAS: 2634-33-5 EC: 220-120-9 1,2-BENZISOTHIAZOL-3(2H)-ONE	GHS07, GHS05, GHS09 Dgr Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Acute 1, H400 M Acute = 1		0 <= x % < 2.5
INDEX: 613-167-00-5 CAS: 55965-84-9 MIXTURE OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE [EC NO. 247-500-7] AND 2-METHYL-2HISOTHIAZOL-3-ONE [EC NO. 220-239-6] (3:1)	GHS06, GHS05, GHS09 Dgr Acute Tox. 3, H331 Acute Tox. 3, H311 Acute Tox. 3, H301 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1		0 <= x % < 2.5

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

If the person is unconscious, place in recovery position and call a doctor

Remove to fresh air, keep the person warm and at rest. If breathing has stopped, effect mouth-to-mouth resuscitation. Give nothing by mouth.

In the event of splashes or contact with eyes :

Refer the patient to an ophthalmologist if it appears pain or visual impairment

Rinse immediately with plenty of water for 10 minutes

In the event of splashes or contact with skin :

In the event of an allergic reaction, seek medical attention.

Remove contaminated clothing

Wash skin thoroughly with water

Do not use solvents or thinners

In the event of swallowing :

Seek medical attention, showing the label.

Keep at rest. Do not induce vomiting

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

Prestonett Wood Filler

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- carbon dioxide (CO₂)
- powder
- sprayed water or water mist

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Use self-contained breathing apparatus and protective clothing

Prevent effluent from entering sewers or waterways

Cool in closed containers exposed to fire.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

Ensure adequate ventilation

Avoid contact with skin and eyes

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Prevent any material from entering drains or waterways.

If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with statutory procedures.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

Cf 8 & 13

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Avoid contact with eyes, skin and inhalation of spray mist

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Prestonett Wood Filler

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

Stock in accordance with the label.

Storage

Keep away from frost and heat sources

Packaging

Always keep in packaging made of an identical material to the original.

After use, the containers should be closed and stored upright.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Care must be taken to comply with the statutory provisions of the Labour Code for all types of dust in the atmosphere (total, respirable alveolar)

Occupational exposure limits :

- France (INRS - ED984 :2016) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
1317-65-3	-	10	-	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1317-65-3	4 mg/m3				

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

Prestonett Wood Filler

- Respiratory protection

In case of airless spraying :
Do not breathe vapors
Ensure adequate ventilation
If sanding, do not inhale the dust and be equipped with a mask type P3.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state :	Paste.
Color:	White
Odour:	Low emission level

Important health, safety and environmental information

pH :	Not stated. Slightly basic.
pH (aqueous solution) :	8.0
Boiling point/boiling range :	Not specified.
Flash point interval :	Not relevant.
Vapour pressure (50°C) :	Not relevant.
Density :	1.7
Water solubility :	Dilutable.
Melting point/melting range :	Not specified.
Self-ignition temperature :	Not specified.
Decomposition point/decomposition range :	Not specified.
% VOC :	<0.1

9.2. Other information

VOC (g/l) :	>0.1
-------------	------

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid :
- frost

10.5. Incompatible materials

Keep away from :
- strong oxidising agents
- strong reducing agents

10.6. Hazardous decomposition products

The thermal decomposition may release/form :
- carbon monoxide (CO)
- carbon dioxide (CO₂)

Prestonett Wood Filler

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

No data available.

11.1.1. Substances

Presence of biocides for preservation of the product can cause allergies or sensitization in sensitive individuals

11.1.2. Mixture

Skin corrosion/skin irritation :

A prolonged or repeated contact with skin or mucous membranes may cause irritation, redness, dermatitis ...

Serious damage to eyes/eye irritation :

Splashes may cause irritation and reversible damage

Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

when sanding, there may be formation of dust. Prolonged inhalation may cause an irritation of the throat, nose and lungs for sensitive people

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

All flow into drains or watercourses should be avoided.

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

08 04 99 wastes not otherwise specified

Prestonett Wood Filler

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number

-

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

-

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

-

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2016/1179. (ATP 9)

- Container information:

No data available.

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Reference : E0423

Wording of the phrases mentioned in section 3 :

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Prestonett Wood Filler

Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.