

SAFETY DATA SHEET Brush Mate Fluid (including Vapour Mate impregnated pads)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Brush Mate Fluid

Product number 1609

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Solvent for Industrial Use

1.3. Details of the supplier of the safety data sheet

Supplier

Gordon Products Ltd 100

Main Street Frodsham Cheshire WA6 7AR

+44 (0)1928 732 158 (Tel)

Contact person info@brushmate.co.uk

1.4. Emergency telephone number

Emergency telephone 0870 190 6777 (National Chemical Emergency Centre) +44 (0)1270 502891

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Flam. Liq. 3 - H226

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335, H336 STOT RE 1 - H372 Asp. Tox.

1 - H304

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Hazard pictograms











Signal word

Danger

Hazard statements H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.

Precautionary statements P260 Do not breathe vapour/ spray.

P262 Do not get in eyes, on skin, or on clothing. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

The material and container must be disposed of as hazardous waste.

Supplemental label information

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics, BUTANOL-norm,

HYDROCARBONS, C9, aromatics, CYCLOHEXANONE

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-

30-60%

25%) aromatics

CAS number: — EC number: 919-446-0

Classification

Flam. Liq. 3 - H226 STOT SE 3 - H336 STOT RE 1 - H372 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

BUTANOL-norm 10-30%

CAS number: 71-36-3 EC number: 200-751-6

Classification

Flam. Lig. 3 - H226

Acute Tox. 4 - H302

Skin Irrit. 2 - H315

Eye Dam. 1 - H318

STOT SE 3 - H335, H336

BRUSH MATE FLUID

HYDROCARBONS, C9, aromatics 10-30%

CAS number: — EC number: 918-668-5

Classification

Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

CYCLOHEXANONE 1-5%

CAS number: 108-94-1 EC number: 203-631-1

Classification

Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Dam. 1 - H318

2, 6 di-tert-butyl-p-cresol (BHT)

CAS number: 128-37-0 EC number: 204-881-4

M factor (Acute) = 1 M factor (Chronic) = 1

Classification

Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments Benzene may be present but always below 0.1%

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. If breathing stops, provide

artificial respiration. Never give anything by mouth to an unconscious person.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. If breathing stops, provide

artificial respiration. Get medical attention if any discomfort continues.

Ingestion Rinse mouth thoroughly with water. Do not induce vomiting. Aspiration hazard if swallowed.

Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis. Get

medical attention immediately.

Skin contact Remove contaminated clothing and rinse skin thoroughly with water. Get medical attention if

any discomfort continues.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

General information No additional symptoms or effects are anticipated.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog. Water spray, fog or mist.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is flammable. Heating may generate flammable vapours. Vapours may form

explosive mixtures with air. Vapours may be ignited by a spark, a hot surface or an ember.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances: Oxides

of carbon.

5.3. Advice for firefighters

Protective actions during firefighting

Keep up-wind to avoid fumes. Fight fire from safe distance or protected location. Move containers from fire area if it can be done without risk. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and

keeping it out of sewers and watercourses. Do not use water jet as an extinguisher, as this will

spread the fire.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

No smoking, sparks, flames or other sources of ignition near spillage. Do not breathe vapour.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Inform the relevant

authorities if this occurs.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots,

> clothing or apron, as appropriate. Wash thoroughly after dealing with a spillage. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Do not allow to enter drains, sewers or watercourses. Inform authorities if large amounts are

involved. Spillage may be stored as chemical waste in approved area.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

BRUSH MATE FLUID

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Keep away from heat, sparks and open

flame. Static electricity and formation of sparks must be prevented. Storage tanks and other containers must be earthed. Protect electric equipment against sparking in case of risk of

explosion. Container must be kept tightly closed when not in use.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Keep container tightly closed. Keep away from

food, drink and animal feeding stuffs. Avoid contact with oxidising agents. Keep away from oxidising materials, heat and flames. Earth container and transfer equipment to eliminate sparks from static electricity. Keep only in the original container. Suitable container materials: Mild steel. Stainless steel. Do not use containers made of the following materials: aluminium,

copper, PVC.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Usage description Storage tanks must be positioned within a bunded area.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

Long-term exposure limit (8-hour TWA): WEL 350 mg/m³

BUTANOL-norm

Short-term exposure limit (15-minute): WEL 50 ppm 154 mg/m³

Sk

HYDROCARBONS, C9, aromatics

Long-term exposure limit (8-hour TWA): OEL 100 mg/m³

CYCLOHEXANONE

Long-term exposure limit (8-hour TWA): WEL 10 ppm 41 mg/m³ Short-term exposure limit (15-minute): WEL 20 ppm 82 mg/m³ Sk

Sk

2, 6 di-tert-butyl-p-cresol (BHT)

Long-term exposure limit (8-hour TWA): 10 mg/m³

WEL = Workplace Exposure Limit.
OEL = Occupational Exposure Limit.
Sk = Can be absorbed through the skin.

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

DNEL Industry - Dermal; Long term systemic effects: 44 mg/kg/day

Industry - Inhalation; Long term systemic effects: 330 mg/m³ Consumer - Dermal; Long term systemic effects: 26 mg/kg/day Consumer - Inhalation; Long term systemic effects: 71 mg/m³ Consumer - Oral; Long term systemic effects: 26 mg/kg/day

PNEC PNEC is not meaningful for petroleum substances.

Aquatic PNECs for hydrocarbon blocks are derived using HC5 method and target

lipid model using representative structures.

CYCLOHEXANONE (CAS: 108-94-1)

Ingredient comments WEL = Workplace Exposure Limits

DNEL Industry - Dermal; Short term : 100 mg/kg/day

Industry - Inhalation; Short term: 100 mg/m³ Industry - Dermal; Long term: 10 mg/kg/day Industry - Inhalation; Long term: 80 mg/m³ Consumer - Dermal; Short term: 30 mg/kg/day Consumer - Inhalation; Short term: 50 mg/m³ Consumer - Oral; Short term: 10 mg/kg/day Consumer - Dermal; Long term: 20 mg/kg/day Consumer - Inhalation; Long term: 20 mg/m³

PNEC - Fresh water; 0.0329 mg/l

- marine water; 0.00329 mg/l

- STP; 10 mg/l

- Sediment; Freshwater 0.0951 mg/kg

- Soil; 0.0143 mg/kg

8.2. Exposure controls

Protective equipment





Appropriate engineering

controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. Use explosion-proof general and local exhaust ventilation.

Eye/face protection

Wear chemical splash goggles. Personal protective equipment that provides appropriate eye

and face protection should be worn.

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn. To protect hands from chemicals, wear gloves that are proven to be impervious to the chemical and resist degradation. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Other skin and body

protection

Use barrier creams to prevent skin contact. Provide eyewash station and safety shower. Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station and safety shower. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes wet or contaminated. Eating, smoking and water fountains prohibited in immediate work area. Do not smoke in work area.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. Check that the respirator fits tightly and the filter is changed regularly.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Clear liquid.

Colour Colourless.

Odour Characteristic.

Flash point 32°C Closed cup.

Vapour density >1

BRUSH MATE FLUID

Relative density 0.808 @ 20°C

Solubility(ies) Slightly soluble in water.

Specific Gravity

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Acids

10.6. Hazardous decomposition products

Hazardous decomposition

products

Thermal decomposition or combustion products may include the following substances: Oxides

of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects ASPIRATION HAZARD - do not breath vapour or spray. May cause lung damage if material

gets into the lungs after accidental swallowing or vomiting of ingested material.

Acute toxicity - oral

ATE oral (mg/kg) 3,004.81

Acute toxicity - dermal

ATE dermal (mg/kg) 66,265.06

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 662.65

Skin corrosion/irritation

Skin corrosion/irritation Irritating to skin.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye damage.

Respiratory sensitisation

Respiratory sensitisation Not expected to be a respiratory sensitizer.

Skin sensitisation

Skin sensitisation May cause an allergic skin reaction.

Carcinogenicity

Carcinogenicity Suspected of causing cancer.

Specific target organ toxicity - repeated exposure

BRUSH MATE FLUID

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways.

General information Prolonged and repeated contact with solvents over a long period may lead to permanent

health problems. Extensive use of the product in areas with inadequate ventilation may result

in the accumulation of hazardous vapour concentrations.

Inhalation Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause

chemical pneumonitis. Overexposure may depress the central nervous system, causing

dizziness and intoxication.

Ingestion Harmful: may cause lung damage if swallowed. Pneumonia may be the result if vomited

material containing solvents reaches the lungs.

Skin contact Harmful in contact with skin. May cause sensitisation by skin contact.

Eve contact Irritation of eyes and mucous membranes.

Acute and chronic health

hazards

Prolonged or repeated exposure to vapours in high concentrations may cause the following

adverse effects: Central and/or peripheral nervous system damage. Brain damage.

Route of exposure Inhalation Skin and/or eye contact

Target organs Respiratory system, lungs Skin Eyes

Medical symptoms Skin irritation. Irritation of eyes and mucous membranes. Gas or vapour in high concentrations

may irritate the respiratory system. Symptoms following overexposure may include the

following: Headache. Fatigue. Nausea, vomiting.

Medical considerations Skin disorders and allergies. Convulsions. Central nervous system depression. Aspiration

hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical

pneumonitis.

Toxicological information on ingredients.

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

Other health effects There is no evidence that the product can cause cancer.

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

15,000.0

Species Rat

ATE oral (mg/kg) 15,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 3,400.0

mg/kg)

Species

Rat

ATE dermal (mg/kg) 3,400.0

Acute toxicity - inhalation

Acute toxicity inhalation

13,100.0

(LC₅₀ vapours mg/l)

BRUSH MATE FLUID

Species Rat

ATE inhalation (vapours

mg/l)

13,100.0

Skin corrosion/irritation

Animal data Erythema/eschar score: Very slight erythema - barely perceptible (1). Oedema

score: Very slight oedema -barely perceptible (1). Not irritating.

Extreme pH Not irritating. Non Corrosive to skin.

Serious eye damage/irritation

Serious eye

Not irritating.

damage/irritation

Respiratory sensitisation The

Respiratory sensitisation

There is no evidence that the material can lead to respiratory hypersensitivity.

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro: Negative.

Genotoxicity - in vivoChromosome aberration: Negative.

Carcinogenicity

Carcinogenicity NOAEL 300 mg/kg, Oral, Rat Highly unlikely to be carcinogenic and are not

classifiable as carcinogens.

Reproductive toxicity

Reproductive toxicity -

fertility

Screening: - NOAEC >300 11.7 - 12.5, Inhalation, Rat P Units ppm.

Reproductive toxicity -

development

Fetotoxicity: - NOAEC: >300, Inhalation, Rat Units ppm. No evidence of

developmental toxicity.

Specific target organ toxicity - single exposure

STOT - single exposure Central nervous system depression including narcotic effects such as drowsiness,

narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 1056 mg/kg, Oral, Rat

Aspiration hazard

Aspiration hazard The fluid can enter the lungs and cause damage (chemical pneumonitis, possibly

fatal). Kinematic viscosity ≤ 20.5 mm²/s.

Inhalation Vapours have a narcotic effect and may cause headache, fatigue, dizziness and

nausea. Unconsciousness.

Ingestion If swallowed accidentally, the product may enter the lungs due to its low viscosity

and lead to the rapid development of very serious pulmonary lesions (medical

survey during 48 hours). May cause stomach pain or vomiting.

BRUSH MATE FLUID

Skin contact Prolonged or repeated exposure may cause the following adverse effects: Dry skin.

Irritation.

Eye contact May cause temporary eye irritation. Redness.

Route of exposure Skin and/or eye contact Inhalation

Target organs Central nervous system

HYDROCARBONS, C9, aromatics

Respiratory sensitisation

Respiratory sensitisation Not classified as a sensitizer.

Skin sensitisation

Skin sensitisation Not classified as a sensitizer.

Germ cell mutagenicity

Genotoxicity - in vitro : Negative.

Genotoxicity - in vivo : Negative.

Carcinogenicity

Carcinogenicity Not classified carcinogenic.

Reproductive toxicity

Reproductive toxicity -

fertility

No effects on fertility

Reproductive toxicity -

development

No evidence of developmental toxicity.

Specific target organ toxicity - single exposure

STOT - single exposure Vapours may cause drowsiness and dizziness. Irritating to respiratory system.

Target organs Central nervous system Respiratory system, lungs

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No known effects based on information supplied.

Aspiration hazard

Aspiration hazard The fluid can enter the lungs and cause damage (chemical pneumonitis, possibly

fatal).

Inhalation Vapours have a narcotic effect. Symptoms following overexposure may include the

following: Headache. Fatigue. Dizziness. Nausea, vomiting. Vapour may irritate

respiratory system/lungs.

Ingestion Harmful if swallowed. Pneumonia may be the result if vomited material containing

solvents reaches the lungs. Gastrointestinal symptoms, including upset stomach.

Skin contact Skin irritation should not occur when used as recommended. Repeated exposure

may cause skin dryness or cracking. Frequent or prolonged contact with the skin

destroys cutaneous lipoacidic film, which can lead to localised irritation.

Eye contact May cause temporary eye irritation. Irritating to eyes. Symptoms following

overexposure may include the following: Redness. Pain.

BRUSH MATE FLUID

CYCLOHEXANONE

Acute toxicity - oral

Acute toxicity oral (LD50

mg/kg)

1.620.0

Species

Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 1,100.0

mg/kg)

Species Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation

(LC50 vapours mg/l)

11.0

Species Rat

ATE inhalation (vapours

mg/l)

11.0

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro : Not mutagenic.

Carcinogenicity

Carcinogenicity Highly unlikely to be carcinogenic and are not classifiable as carcinogens.

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations.

Inhalation Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting

may cause chemical pneumonitis. Overexposure may depress the central nervous

system, causing dizziness and intoxication. Harmful by inhalation.

Ingestion Harmful: may cause lung damage if swallowed. Pneumonia may be the result if

vomited material containing solvents reaches the lungs.

Skin contact Repeated exposure may cause skin dryness or cracking.

Eye contact Irritation of eyes and mucous membranes.

Acute and chronic health

hazards

Prolonged contact may cause dryness of the skin. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: Central and/or peripheral nervous system damage. Brain damage.

Route of exposure Ingestion. Inhalation

Target organs Brain Respiratory system, lungs Mucous membranes

BRUSH MATE FLUID

Medical symptoms Skin irritation. Irritation of eyes and mucous membranes. Gas or vapour in high

concentrations may irritate the respiratory system. Symptoms following

overexposure may include the following: Headache. Fatigue. Nausea, vomiting.

Medical considerations Skin disorders and allergies. Convulsions. Central nervous system depression.

Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting

may cause chemical pneumonitis.

N,N-Diethylhydroxylamine

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,001.0

mg/kg)

Species Rat

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

ATE inhalation (vapours 11.0

mg/l)

SECTION 12: Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Ecological information on ingredients.

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

Ecotoxicity Dangerous for the environment if discharged into watercourses.

CYCLOHEXANONE

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

Toxicity Not stated

Ecological information on ingredients.

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 10 - 30 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 10 - 22 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

IC₅o, 72 hours: 4.6 - 10 mg/l, Pseudokirchneriella subcapitata

Chronic aquatic toxicity

Chronic toxicity - fish early NOELR, 28 days: 0.13 mg/l, Oncorhynchus mykiss (Rainbow trout)

life stage

Chronic toxicity - aquatic NOELR, 21 days

invertebrates

NOELR, 21 days: 0.28 mg/l, Daphnia magna

BRUSH MATE FLUID

HYDROCARBONS, C9, aromatics

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 9.2 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 3.2 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅₀, 72 hours: 2.9 mg/l, 11.7 - 12.5

Chronic aquatic toxicity

Chronic toxicity - aquatic

invertebrates

, 21 days: 2.14 mg/l, Daphnia magna

CYCLOHEXANONE

Acute aquatic toxicity

LC50, 96 hours: ~ 500 mg/l, Pimephales promelas (Fat-head Minnow) Acute toxicity - fish

2, 6 di-tert-butyl-p-cresol (BHT)

Acute aquatic toxicity

 $0.1 < L(E)C50 \le 1$ LE(C)50

M factor (Acute) 1

Chronic aquatic toxicity

NOEC 0.01 < NOEC ≤ 0.1

Degradability Non-rapidly degradable

M factor (Chronic) 1

12.2. Persistence and degradability

Ecological information on ingredients.

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

Persistence and degradability

The product is readily biodegradable.

Phototransformation Scientifically unjustified.

> This substance does not have the potential to undergo photolysis in water and soil, and this fate process will not contribute to a measurable degradative loss of this

substance from the environment.

Stability (hydrolysis) Scientifically unjustified.

Biodegradation - Degradation (%) 75: 28 days

HYDROCARBONS, C9, aromatics

Persistence and

degradability

Readily biodegradable.

Biodegradation - Degradation (%) 78: 28 days

CYCLOHEXANONE

BRUSH MATE FLUID

Persistence and degradability

There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Ecological information on ingredients.

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

Bioaccumulative potential Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended

for single substances and are not appropriate for this complex substance.

Partition coefficient Technically not feasible. Substance is a UVCB. Standard tests for this endpoint are

intended for single subtances, and are not appropriate for this complex substance.

HYDROCARBONS, C9, aromatics

Bioaccumulative potential Substance is a UVCB. Standard tests for this endpoint are not appropriate.

Partition coefficient Not applicable.

CYCLOHEXANONE

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient : 0.86

12.4. Mobility in soil

Ecological information on ingredients.

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

Mobility Given its physical and chemical characteristics, the product has no soil mobility.

The product evaporates readily in air. The product is insoluble in water. Floats on

water.

Adsorption/desorption

coefficient

Scientifically unjustified. Substance is a UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.

Henry's law constant Scientifically unjustified. Volatilisation is dependent on Henry's Law constant (HLC)

which is not applicable to complex substances.

HYDROCARBONS, C9, aromatics

Mobility Substance is a UVCB. Standard tests for this endpoint are not applicable.

CYCLOHEXANONE

Adsorption/desorption

coefficient

Not available.

12.5. Results of PBT and vPvB assessment

Ecological information on ingredients.

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

Results of PBT and vPvB This substance is not classified as PBT or vPvB according to current UK criteria. assessment

HYDROCARBONS, C9, aromatics

BRUSH MATE FLUID

Results of PBT and vPvB

This substance is not classified as PBT or vPvB according to current UK criteria.

assessment

CYCLOHEXANONE

Results of PBT and vPvB assessment

This substance is not classified as PBT or vPvB according to current UK criteria.

12.6. Other adverse effects

Ecological information on ingredients.

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

Other adverse effects This substance may contribute to ozone formation in the near surface atmosphere.

> However, the photochemical formation of ozone depends on a complex interaction of other atmospheric pollutent sources and environmental conditions. Therefore, the contribution of this substance to ozone formation is outside the scope of this substsance assessment and is more appropriately addressed via EU air quality

directives.

HYDROCARBONS, C9, aromatics

Other adverse effects Not available.

CYCLOHEXANONE

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Contaminated packages must be completely emptied before sending away for laundering and

re-use.

Disposal methods Confirm disposal procedures with environmental engineer and local regulations. Dispose of

waste to licensed waste disposal site in accordance with the requirements of the local Waste

Disposal Authority. Do not allow runoff to sewer, waterway or ground.

Waste class Hazardous Waste EWC NUMBER: Allocation of a waste code number in accordance with the

European Waste Catalogue, should be carried out in agreement with an EA authorised waste

disposal company.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1993

UN No. (IMDG) 1993

UN No. (ICAO) 1993

UN No. (ADN) 1993

14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%),

aromatics)

Proper shipping name (IMDG) FLAMMABLE LIQUID, N.O.S.

BRUSH MATE FLUID

Proper shipping name (ICAO) FLAMMABLE LIQUID, N.O.S.

Proper shipping name (ADN) FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group

ADN packing group

ICAO packing group

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 3

Emergency Action Code •3Y

Hazard Identification Number 30

(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 CLP.

Regulation (EC) No 1907/2006 REACH.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information Only trained personnel should use this material. Since empty containers retain product

residue, follow label warnings, even after container is emptied. For further Health and Safety information contact: Health and Safety Officer. Labels should not be removed from containers

until they have been cleaned and no product remains within.

Revision comments Product code added.

Issued by Compliance Department

Revision date 21/02/2022

Revision 2

Supersedes date 08/09/2021

SDS number 22527

SDS status Approved.

Hazard statements in full H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.