



## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

### SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : OWATROL SEASONITE  
Product code : SEAS01.

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

New Wood Protection.

#### 1.3. Details of the supplier of the safety data sheet

Registered company name : DURIEU S.A..  
Address : Z.I. "La Marinière" 2 bis, rue Charles de Gaulle.91070.BONDOUFLE.FRANCE.  
Telephone : + 33 (0)1.60.86.48.70. Fax : + 33 (0)1.60.86.84.84.  
info@durieu.com  
www.durieu.com

#### 1.4. Emergency telephone number : + 33 (0)1.45.42.59.59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

#### Other emergency numbers

UNITED KINGDOM :UK National poisons emergency number: +44 (0) 870 600 6266 IRELAND, EIRE: Ireland National Poisons Information Centre: +353 (0) 1 8379964 AUSTRALIA: Poison Information Centre: 131 126 NEW ZEALAND: Poison Information Centre 0 800 764 766:

### SECTION 2 : HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

##### In compliance with EC regulation No. 1272/2008 and its amendments.

May produce an allergic reaction (EUH208).  
Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).  
This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

#### 2.2. Label elements

##### In compliance with EC regulation No. 1272/2008 and its amendments.

Additional labeling :  
EUH208 Contains 3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC). May produce an allergic reaction.  
EUH208 Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE. May produce an allergic reaction.  
EUH208 Contains REACTION MASS OF 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1). May produce an allergic reaction.

#### Hazard statements :

H412 Harmful to aquatic life with long lasting effects.

#### Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

#### Precautionary statements - Prevention :

P273 Avoid release to the environment.

#### Precautionary statements - Disposal :

P501 Dispose of contents / container in a waste collection point.

#### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>  
The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

### SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2. Mixtures

##### Composition :

Identification	(EC) 1272/2008	Note	%
INDEX: 061 CAS: 55406-53-6 EC: 259-627-5 REACH: 01-2120762115-60  3-iodo-2-propynyl butylcarbamate (IPBC)	GHS06, GHS05, GHS09, GHS08 Dgr Acute Tox. 4, H302 Skin Sens. 1, H317 Eye Dam. 1, H318 Acute Tox. 3, H331 STOT RE 1, H372 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1	[1]	0 <= x % < 0.5
INDEX: 199 CAS: 2634-33-5 EC: 220-120-9 REACH: 01-2120761540-60  1,2-benzisothiazol-3(2H)-one	GHS07, GHS05, GHS09 Dgr Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Chronic 2, H411 Aquatic Acute 1, H400 M Acute = 1		0 <= x % < 0.05
INDEX: 111 CAS: 71786-60-2 EC: 276-014-8 REACH: 01-2119957489-17-0000  FATTY AMINE ETHOXYLATE	GHS08, GHS07, GHS05, GHS09 Dgr Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Repr. 2, H361fd Aquatic Acute 1, H400 M Acute = 10 Aquatic Chronic 1, H410 M Chronic = 10	[2]	0 <= x % < 2.5
INDEX: 613-167-00-5 CAS: 55965-84-9  REACTION MASS OF 5-CHLORO-2-METHYL-2H-ISOTHIAZOL -3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)	GHS06, GHS05, GHS09 Dgr Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Eye Dam. 1, H318 Acute Tox. 2, H330 Aquatic Acute 1, H400 M Acute = 100 Aquatic Chronic 1, H410 M Chronic = 100 EUH:071	B	0 <= x % < 0.05

(Full text of H-phrases: see section 16)



#### Information on ingredients :

- [1] Substance for which maximum workplace exposure limits are available.  
[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

## SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.  
NEVER induce swallowing by an unconscious person.

### 4.1. Description of first aid measures

#### In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.  
In case of long exposure, without any protection, can cause temporary irritation.

#### In the event of splashes or contact with eyes :

Wash thoroughly with soft clean water for 15mn holding the eyelids open.

Refer to an ophthalmologist in particular if there is any redness, pain or visual impair.

**In the event of splashes or contact with skin :**

In the event of an allergic reaction, seek medical attention.  
Wash thoroughly with soft clean water.

**In the event of swallowing :**

Seek medical attention, showing the label.  
If swallowed accidentally, refer to a doctor and show him the label.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

## SECTION 5 : FIREFIGHTING MEASURES

This product is not classed as flammable.

**5.1. Extinguishing media**

**Suitable methods of extinction**

In the event of a fire, use :  
- sprayed water or water mist  
- water with AFFF (Aqueous Film Forming Foam) additive  
- foam  
- multipurpose ABC powder  
- carbon dioxide (CO<sub>2</sub>)

**Unsuitable methods of extinction**

Direct water jet.

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.  
Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)  
- carbon dioxide (CO<sub>2</sub>)

The combustion of the plastic container may cause some discomfort.

**5.3. Advice for firefighters**

Bring independent breathing apparatus.

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

**6.4. Reference to other sections**

No data available.

## SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

**7.1. Precautions for safe handling**

Always wash hands after handling.  
Remove and wash contaminated clothing before re-using.  
Keep containers tightly closed.

**Fire prevention :**

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

Opened container must be thoroughly closed and kept in vertical position.

Do not keep in metallic container because of corrosion.

Stock between +5°C and +30°C in a dry, well ventilated place.

**Storage**

Keep out of reach of children.

**Packaging**

Always keep in packaging made of an identical material to the original.

Recommended types of packaging :

- Vats

- Buckets

Suitable packaging materials :

- Plastic

Unsuitable packaging materials :

- Metal

**7.3. Specific end use(s)**

No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters****Occupational exposure limits :**

- Germany - AGW (BAuA - TRGS 900, 08/08/2019) :

CAS	VME :	VME :	Excess	Notes
55406-53-6		0.005 ppm 0.058 mg/m <sup>3</sup>		2 (I)

**8.2. Exposure controls****Personal protection measures, such as personal protective equipment**

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

Use personal protection equipment.

**- Hand protection**

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVC (polyvinyl chloride)

- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN ISO 374-2

Wear neoprene rubber or nitrile rubber gloves.

**- Body protection**

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

After contact with the product, soiled clothing must be removed and the skin must be cleaned with soap and water or a suitable cleaner for skin.

**- Respiratory protection**

Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149.

Category :

- FFP2

Type of mask with combined filters :

Wear a half mask in accordance with standard EN140.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

- AX (Brown)

Particle filter according to standard EN143 :

- P2 (White)

Respiratory protective gears to absorb the aerosols must be carried when the product is sprinkled insofar as the exposure cannot be controlled to be in lower part of the limiting risk of exposure.

## SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

#### General information :

Physical state :	Fluid liquid.
Colour :	Amber

#### Important health, safety and environmental information

pH :	8.50 .
	Slightly basic.
Boiling point/boiling range :	Not specified.
Flash point interval :	Not relevant.
Vapour pressure (50°C) :	Not relevant.
Vapour density :	>1
Density :	1.004
Water solubility :	Dilutable.
Viscosity :	<25s (n°3 - ISO2431)
Melting point/melting range :	Not specified.
Self-ignition temperature :	Not relevant.
Decomposition point/decomposition range :	Not specified.
% VOC :	<1%

### 9.2. Other information

VOC (g/l) :	10
-------------	----

## SECTION 10 : STABILITY AND REACTIVITY

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

Avoid :

- frost

Always stock in its original packaging. Do not transfer in another package.

### 10.5. Incompatible materials

No data available.

### 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO<sub>2</sub>)

## SECTION 11 : TOXICOLOGICAL INFORMATION

Can cause severe eye irritation.

### 11.1. Information on toxicological effects

No data available.

**11.1.1. Substances****Acute toxicity :**

1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5)

Oral route : LD50 = 597 mg/kg  
Species : Rat  
OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)

Dermal route : LD50 > 2000 mg/kg  
Species : Rat  
OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)

3-iodo-2-propynyl butylcarbamate (IPBC) (CAS: 55406-53-6)

Oral route : LD50 = 1056 mg/kg  
Species : Rat  
OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)

Dermal route : LD50 > 2000 mg/kg  
Species : Rat  
OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)

**11.1.2. Mixture****Respiratory or skin sensitisation :**

Contains at least one sensitising substance. May cause an allergic reaction.

 **Monograph(s) from the IARC (International Agency for Research on Cancer) :**

CAS 111-76-2 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

 **SECTION 12 : ECOLOGICAL INFORMATION**

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

**12.1. Toxicity**

Probably low dangerous to aquatic organisms

Do not leave this product, not diluted or in great quantity, penetrate the ground water, waters or the drains.

 **12.1.1. Substances**

FATTY AMINE ETHOXYLATE (CAS: 71786-60-2)

Fish toxicity : 0.01 < LC50 <= 0.1 mg/l  
Factor M = 10  
Duration of exposure : 96 h

0,001 < ECx <= 0,01 mg/l  
Factor M = 10

0,001 < NOEC <= 0,01 mg/l  
Factor M = 10

Crustacean toxicity : 0.01 < EC50 <= 0.1 mg/l  
Factor M = 10  
Duration of exposure : 48 h

0,001 < ECx <= 0,01 mg/l  
Factor M = 10

0,001 < NOEC <= 0,01 mg/l  
Factor M = 10

Algae toxicity : 0.01 < ECr50 <= 0.1 mg/l  
Factor M = 10  
Duration of exposure : 72 h

0,001 < ECx <= 0,01 mg/l  
Factor M = 10

	0,001 < NOEC <= 0,01 mg/l Factor M = 10
Aquatic plant toxicity :	0.01 < ECr50 <= 0.1 mg/l Factor M = 10 Duration of exposure : 72 h
	0,001 < ECx <= 0,01 mg/l Factor M = 10
	0,001 < NOEC <= 0,01 mg/l Factor M = 10
1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5) Fish toxicity :	LC50 = 0.74 mg/l Duration of exposure : 96 h
Crustacean toxicity :	EC50 = 2.44 mg/l Species : Daphnia magna Duration of exposure : 48 h
3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC) (CAS: 55406-53-6) Fish toxicity :	LC50 = 0.067 mg/l Species : Others Duration of exposure : 96 h
	NOEC = 0.0084 mg/l Factor M = 1 Species : Pimephales promelas Duration of exposure : 35 jours
Crustacean toxicity :	EC50 = 0.16 mg/l Species : Daphnia magna Duration of exposure : 48 h
	EC50 mg/l Species : Daphnia magna Duration of exposure : 21 jours
	Species : Others
Algae toxicity :	ECr50 = 0.022 mg/l Species : Scenedesmus subspicatus Duration of exposure : 72 h
	NOEC = 0.0046 mg/l Factor M = 1 Species : Scenedesmus subspicatus

### 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

### 12.2. Persistence and degradability

#### 12.2.1. Substances

FATTY AMINE ETHOXYLATE (CAS: 71786-60-2)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5)

Biodegradability : Rapidly degradable.

3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC) (CAS: 55406-53-6)

Biodegradability : Rapidly degradable.

### 12.3. Bioaccumulative potential

#### 12.3.1. Substances

1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5)

Octanol/water partition coefficient : log K<sub>ow</sub> = 0.4

Bioaccumulation : BCF = 1.4

3-IODO-2-PROPYNYL BUTYLCARBAMATE (IPBC) (CAS: 55406-53-6)

Octanol/water partition coefficient : log K<sub>ow</sub> = 2.81

### 12.4. Mobility in soil

Contains a solid phase.

This product is dilutable in water in all proportion.

### 12.5. Results of PBT and vPvB assessment

No data available.

### 12.6. Other adverse effects

No data available.

## SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

### 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

#### Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

#### Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

15 01 10 \* packaging containing residues of or contaminated by dangerous substances

08 01 11 \* waste paint and varnish containing organic solvents or other dangerous substances

## SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

### 14.1. UN number

-

### 14.2. UN proper shipping name

-

### 14.3. Transport hazard class(es)

-

### 14.4. Packing group

-

### 14.5. Environmental hazards

-

### 14.6. Special precautions for user

-

## SECTION 15 : REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### - Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/1182 (ATP 15)

#### - Container information:

No data available.



**- Labelling for VOCs present in varnishes, paints and in vehicle refinishing products (2004/42/EC) :**

The permitted European level of VOC in this ready-to-use product is limited to 10 g/l.

The permitted European levels of VOC in the ready-to-use product (category II Af) are 150 g/l maximum in 2007 and 130 g/l maximum in 2010.

**- Particular provisions :**

No data available.

**15.2. Chemical safety assessment**

No data available.

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

A symbol shown on the side of the page, indicates that the paragraph has been modified and supersedes all previous versions of the same paragraph.

**Wording of the phrases mentioned in section 3 :**

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure .
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

**Abbreviations :**

CMR: Carcinogenic, mutagenic or reprotoxic.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.