

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : OWATROL PREPDECK Product code : prep01. UFI : Q502-109C-A00F-3XKK

- 1.2. Relevant identified uses of the substance or mixture and uses advised against
 - Stripper / Cleaner for exterior woods

1.3. Details of the supplier of the safety data sheet

Registered company name : DURIEU S.A.: Siège Social. Address : 2 bis, rue Charles de Gaulle.91070.BONDOUFLE.FRANCE. Telephone : + 33 (0)1.60.86.48.70. Fax : + 33 (0)1.60.86.84.84. reglementaire@durieu.com www.durieu.com

1.4. Emergency telephone number : + 33 (0)1.45.42.59.59.

Association/Organisation : INRS / ORFILA www.centres-antipoison.net.

Other emergency numbers

UNITED KINGDOM :UK National poisons emergency number: +44 (0) 870 600 6266 IRELAND, EIRE: Ireland National Poisons Information Centre: +353 (0) 1 8379964 AUSTRALIA: Poison Information Centre: 131 126 NEW ZEALAND: Poison Information Centre 0 800 764 766:

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Substance that is corrosive to metals, Category 1 (Met. Corr. 1, H290).

Skin corrosion, Category 1A (Skin Corr. 1A, H314).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

May produce an allergic reaction (EUH208).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



Signal Word : DANGER Product identifiers :	
011-002-00-6	SODIUM HYDROXIDE
Additional labeling :	
EUH208	Contains LIMONENE. May produce an allergic reaction.
Hazard statements :	
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
Precautionary statements - 0	General :
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
Precautionary statements - F	Prevention :

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) OWATROL PREPDECK - PREP01

P234	Keep only in original packaging.					
P280	Wear protective gloves / protective clothing / eye protection / face protection.					
Precautionary statements - F	Response :					
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.					
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water					
	[or shower].					
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if					
	present and easy to do. Continue rinsing.					
Precautionary statements - Disposal :						

Dispose of contents / container in a waste collection point.

2.3. Other hazards

P501

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006. The mixture does not contain substances> = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

dentification	(EC) 1272/2008	Note	%
NDEX: 603-057-00-5	GHS07	[1]	2.5 <= x % < 10
CAS: 100-51-6	Wng		
EC: 202-859-9	Acute Tox. 4, H332		
REACH: 01-2119492630-38	Acute Tox. 4, H302		
BENZYL ALCOHOL			
NDEX: 011-002-00-6	GHS05	[1]	2.5 <= x % < 10
CAS: 1310-73-2	Dgr		
EC: 215-185-5	Skin Corr. 1A, H314		
REACH: 01-2119457892-27			
SODIUM HYDROXIDE			
NDEX: 008		[1]	2.5 <= x % < 10
AS: 34590-94-8			
C: 252-104-2			
REACH: 01-2119450011-60			
2-METHOXYMETHYLETHOXY)PROPANC	L		
NDEX: 109	GHS07, GHS05		0 <= x % < 2.5
AS: 68154-97-2	Dgr		
	Acute Tox. 4, H302		
LCOHOL, C10-C12, ETHOXYLATED, ROPOXYLATED	Eye Dam. 1, H318		
NDEX: 094	GHS07, GHS09, GHS08, GHS02		0 <= x % < 0.5
CAS: 8028-48-6	Dgr		
C: 232-433-8	Flam. Lig. 3, H226		
	Asp. Tox. 1, H304		
IMONENE	Skin Irrit. 2, H315		
	Skin Sens. 1, H317		
	Aquatic Chronic 2, H411		
ecific concentration limits:			
dentification	Specific concentration limits	ATE	
NDEX: 011-002-00-6	Skin Corr. 1A: H314 C>= 5%		
CAS: 1310-73-2	Skin Corr. 1B: H314 2% <= C < 5%		

SODIUM HYDROXIDE

REACH: 01-2119457892-27

EC: 215-185-5

Information on ingredients :

Skin Irrit. 2: H315 0.5% <= C < 2%

Eye Dam. 1: H318 C>= 2% Eye Irrit. 2: H319 0.5% <= C < 2%

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open. Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

In the event of splashes or contact with skin :

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated aera is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

In case of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

This product is not classed as flammable.

5.1. Extinguishing media

Suitable methods of extinction

- In the event of a fire, use : - spraved water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)
- water with AFFF (Aqueous Film Forming Foam) additive
- CO2, extinguishing powder or pulverized water.

Unsuitable methods of extinction

Direct water jet.

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

Smoke and vapors, carbon oxides, incomplete combustion products.

5.3. Advice for firefighters

Boot, gloves and glasses.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Neutralise with an acidic decontaminant.

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Keep containers tightly closed.

Fire prevention :

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

Keep only in the original container

Keep away from corrosive agents such as strong acids or alkalines to avoid possible leakage or self combustion.

Keep container tighly closed in a dry place.

Stock between +5°C and +30°C in a dry, well ventilated place.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

- Recommended types of packaging :
- Vats
- Buckets
- Suitable packaging materials :
- Plastic

Unsuitable packaging materials :

- Steel
- Metal

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (20)19/1831. 2017/2398.	2017/164. 2009/161.	2006/15/CE.	2000/39/CE, 98/24/CE):
European ernen (Ee	,		,	2000/00/02/00/2//02//

CAS VME-mg/m3 : VME-ppm : VLE-mg/m3 : VLE-ppm : Notes :	
---	--

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) OWATROL PREPDECK - PREP01

34590-94-8	308	50	-	-	Peau	
- ACGIH TL	V (American Conferent	ence of Governmental	Industrial Hygienists	s, Threshold Limit Valu	ues, 2010) :	
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
1310-73-2			2 mg/m3			
34590-94-8	100 ppm	150 ppm		Skin		
- Germany	- AGW (BAuA - TRG	S 900, 08/08/2019) :				
CAS	VME :	VME :	Excess	Notes		
100-51-6		5 ppm		2 (I)		
		22 mg/m ³				
34590-94-8		50 ppm		1(I)		
		310 mg/m ³				
- France (IN	NRS - ED984 / 2020-	1546) :				
CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
1310-73-2	-	2	-	-	-	-
34590-94-8	50	308	-	-	*	84
- UK / WEL	. (Workplace exposur	e limits, EH40/2005, F	ourth Edition 2020)	:		
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :	
1310-73-2		2 mg/m ³				
34590-94-8	50 ppm			Sk		
	308 mg/m ³					

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)
- Neoprene® (Polychloroprene)

Permeability time : >480 min for a thickness >0.75 mm

CEN recommendations : EN 420 and EN 374/3

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact. Wear suitable protective clothing, in particular overalls and boots. These items must be kept in good condition and cleaned after use. Suitable type of protective boots :

In the event of minor spatter, wear protective boots or half-boots against chemical risks in accordance with standard EN13832-2.

In the event of prolonged contact, wear boots or half-boots with liquid-chemical-resistant and waterproof soles and uppers in accordance with standard EN13832-3.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

Respiratory protection

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) OWATROL PREPDECK - PREP01

Category :

- FFP2

- - - -

Type of mask with combined filters :

Wear a half mask in accordance with standard EN140.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

- AX (Brown)

Particle filter according to standard EN143 :

- P2 (White)

CEN recommendations : EN 136, EN 140, EN 405 for masks and EN 143, EN 149 for filters.

Respiratory protective gears to absorb the aerosols must be carried when the product is sprinkled insofar as the exposure cannot be controlled to be in lower part of the limiting risk of exposure.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

2	Physical state							
	Physical state :	Viscous liquid.						
2	Colour							
	Colour :	Amber						
2	Odour							
	Odour threshold :	Not stated.						
2	Melting point							
	Melting point/melting range :	Not relevant.						
2	Freezing point							
	Freezing point / Freezing range : Not stated.							
2	Boiling point or initial boiling point and boiling range							
	Boiling point/boiling range :	Not relevant.						
2	Flammability							
	Flammability (solid, gas) :	Not stated.						
2	Lower and upper explosion limit							
	Explosive properties, lower explosivity limit (%) :	Not stated.						
	Explosive properties, upper explosivity limit (%) :	Not stated.						
2	Flash point							
_	Flash point interval :	Not relevant.						
2	Auto-ignition temperature							
	Self-ignition temperature :	Not relevant.						
2								
	Decomposition point/decomposition range :	Not relevant.						
2								
	pH (aqueous solution) :	Not stated.						
	pH :	13.30 .						
A	Kinomotio viecosity	Strongly basic.						
2	Kinematic viscosity	70 -04 (00%0)						
	Viscosity :	70 cSt (23°C)						
~	Solubility Water solubility :	Soluble.						
	Fat solubility :	Not stated.						
2	Partition coefficient n-octanol/water (log value)							
· · · · · · · · · · · · · · · · · · ·	Partition coefficient: n-octanol/water :	Not stated.						
2	Vapour pressure							
1	Vapour pressure (50°C) :	Not relevant.						
2								
	Density :	1.05						
2								
	Vapour density :	Not stated.						
2								
	VOC (g/l) :	182						
	% VOC :	<18%						
1								

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY

Shake product well before using.

10.1. Reactivity

Mixture which by chemical action can corrode and even destroy metals.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Avoid :

- frost

Keep away from corrosive agents such as strong acids or alkalines to avoid possible leakage or self combustion.

Always stock in its original packaging. Do not transfer in another package.

10.5. Incompatible materials

Acids and oxidizing agents.

10.6. Hazardous decomposition products

- The thermal decomposition may release/form :
- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure for up to three minutes.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

11.1.1. Substances

No toxicological data available for the substances.

11.1.2. Mixture

Skin corrosion/skin irritation :

Corrosive classification is based on an extreme pH value.

Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

11.2. Information on other hazards

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

Do not leave this product, not diluted or in great quantity, penetrate the ground water, waters or the drains.

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

Biodegradable

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

This product is dilutable in water in all proportion.

- 12.5. Results of PBT and vPvB assessment
 - No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

15 01 10 * packaging containing residues of or contaminated by dangerous substances

06 02 04 * sodium and potassium hydroxide

Note: Section 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 - ICAO/IATA 2021).

14.1. UN number or ID number

1719

14.2. UN proper shipping name

UN1719=CAUSTIC ALKALI LIQUID, N.O.S.

(sodium hydroxide, benzyl alcohol)

14.3. Transport hazard class(es)

- Classification :



14.4. Packing group

II

14.5. Environmental hazards

.

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	
	8	C5	II	8	80	1 L	274	E2	2	
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage	Segregati	
								Handling	on	
	8	-	II	1 L	F-A. S-B	274	E2	Category	SGG18	
								A	SG22 SG35	
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	8	-	II	851	1 L	855	30 L	A3 A803	E2	
	8	-	II	Y840	0.5 L	-	-	A3 A803	E2	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG. **14.7. Maritime transport in bulk according to IMO instruments**

()

No data available.

NECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/643 (ATP 16)
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/849 (ATP 17)

- Container information:

Packaging to be fitted with child-resistant fastenings (see EC Regulation No. 1272/2008, Annex II, Part 3).

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.

Abbreviations :

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

UFI : Unique formulation identifier.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS05 : Corrosion

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.