



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SAFETY DATA SHEET

SMOOTH MASONRY PAINT MAGNOLIA

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

: SMOOTH MASONRY PAINT MAGNOLIA **GHS** product identifier

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product use : Vaterborne coating for exterior use.

1.3. Details of the supplier of the safety data sheet

ICI Paints AkzoNobel, Wexham Road,

Slough, Berkshire, SL2 5DS, U.K.

Tel.: +44 (0) 333 222 70 70 www.armsteadtrade.co.uk

e-mail address of person responsible for this SDS

: armstead.advice@akzonobel.com

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : +44 (0)344 892 0111

Supplier

Telephone number : T +44 (0) 1753 550000

Version : 3

15-12-2022 Date of previous issue

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

Hazard statements : H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Date of issue/Date of revision 1/20 : 6-6-2023 : 15-12-2022 Version : 3 Date of previous issue

SMOOTH MASONRY PAINT MAGNOLIA

SECTION 2: Hazards identification

: P102 - Keep out of reach of children. General

P101 - If medical advice is needed, have product container or label at hand.

Prevention : P273 - Avoid release to the environment.

Response : Not applicable. Storage : Not applicable.

: P501 - Dispose of contents and container in accordance with all local, regional, Disposal

national or international regulations.

Supplemental label

elements

: Contains 1,2-benzisothiazol-3(2H)-one and C(M)IT/MIT(3:1). May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when

sprayed. Do not breathe spray or mist.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Special packaging requirements

Containers to be fitted with child-resistant

fastenings

: Not applicable.

Tactile warning of danger: Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

Other hazards which do

: None known.

not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤15	Carc. 2, H351 (inhalation)	-	[1] [*]
bronopol (INN)	EC: 200-143-0 CAS: 52-51-7 Index: 603-085-00-8	≤0.1	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400	ATE [Oral] = 500 mg/kg ATE [Dermal] = 1100 mg/kg M [Acute] = 10	[1]
IPBC	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	<0.1	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1,	ATE [Oral] = 500 mg/kg ATE [Inhalation (gases)] = 700 ppm M [Acute] = 10 M [Chronic] = 1	[1]

Date of issue/Date of revision : 6-6-2023 Date of previous issue : 15-12-2022 2/20 Version : 3

🖊 SMOOTH MASONRY PAINT MAGNOLIA

SECTION 3: Composition/information on ingredients

<u> </u>			<u> </u>	T	
			H410		
isoproturon (ISO)	EC: 251-835-4 CAS: 34123-59-6 Index: 006-044-00-7	≤0.048	Carc. 2, H351 STOT RE 2, H373 (blood) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 10 M [Chronic] = 10	[1]
1,2-Benzisothiazol-3(2h)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400	ATE [Oral] = 500 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1	[1]
Terbutryn	EC: 212-950-5 CAS: 886-50-0 Index: self classification	≤0.016	Acute Tox. 4, H302 Skin Sens. 1B, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/kg M [Acute] = 100 M [Chronic] = 100	[1]
C(M)IT/MIT(3:1)	REACH #: 01-2120764691-48 CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Skin Irrit. 2, H315: $0.06\% \le C < 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision : 6-6-2023 Date of previous issue : 15-12-2022 Version : 3 3/20

SMOOTH MASONRY PAINT MAGNOLIA

SECTION 4: First aid measures

4.1 Description of first aid measures

Eve contact : In

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention if irritation occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen

tight clothing such as a collar, tie, belt or waistband.

Skin contact: Wash with plenty of soap and water. Remove contaminated clothing and shoes.

Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before

reuse. Clean shoes thoroughly before reuse.

Ingestion: Wash out mouth with water. Remove dentures if any. If material has been

swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such

as a collar, tie, belt or waistband.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear

gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2-octyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one, C(M)IT/MIT(3:1). May produce an allergic reaction.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion: No specific data.

Date of issue/Date of revision : 6-6-2023 Date of previous issue : 15-12-2022 Version : 3 4/20

SMOOTH MASONRY PAINT MAGNOLIA

SECTION 4: First aid measures

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide metal oxide/oxides

5.3 Advice for firefighters

Special protective actions

for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is

inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the

information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and materials for containment and cleaning up

Date of issue/Date of revision : 6-6-2023 : 15-12-2022 Version : 3 5/20 Date of previous issue

SMOOTH MASONRY PAINT MAGNOLIA

SECTION 6: Accidental release measures

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4 Reference to other sections

: See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8.2 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.
Industrial sector specific : Not available.
solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
diuron (ISO)	EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 10 mg/m³ 8 hours.

🖊 SMOOTH MASONRY PAINT MAGNOLIA

SECTION 8: Exposure controls/personal protection

procedures

Recommended monitoring : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
bronopol (INN)	DNEL	Short term Dermal	0.004 mg/ cm ²	General population	Local
	DNEL	Long term Dermal	0.004 mg/ cm ²	General population	Local
	DNEL	Short term Dermal	0.008 mg/ cm ²	Workers	Local
	DNEL	Long term Dermal	0.008 mg/ cm ²	Workers	Local
	DNEL	Long term Oral	0.18 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	0.6 mg/m ³	General population	Local
	DNEL	Long term Inhalation	0.6 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	0.7 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	1.8 mg/m³	General population	Systemic
	DNEL	Long term Dermal	2 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	2.1 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	2.5 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	2.5 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	3.5 mg/m ³	Workers	Systemic
	DNEL	Short term Dermal	6 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	10.5 mg/m³	Workers	Systemic
diuron (ISO)	DNEL	Long term Inhalation	0.17 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	5.79 mg/ kg bw/day	Workers	Systemic
pyrithione zinc	DNEL	Long term Dermal	0.01 mg/ kg bw/day	Workers	Systemic
1,2-Benzisothiazol-3(2h)-one	DNEL	Long term Dermal	0.345 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.966 mg/ kg bw/day	Workers	Systemic
te of issue/Date of revision : 6-	-6-2023	Date of previous issue	: 15-12-2		rsion : 3 7/20

Date of issue/Date of revision : 6-6-2023 Date of previous issue : 15-12-2022 Version : 3

SMOOTH MASONRY PAINT MAGNOLIA

SECTION 8: Exposure controls/personal protection

	DNEL	Long term	1.2 mg/m ³	General	Systemic
		Inhalation		population	
	DNEL	Long term	6.81 mg/m ³	Workers	Systemic
		Inhalation			
C(M)IT/MIT(3:1)	DNEL	Long term	0.02 mg/m ³	General	Local
		Inhalation		population	
	DNEL	Long term	0.02 mg/m ³	Workers	Local
		Inhalation			
	DNEL	Short term	0.04 mg/m ³	General	Local
		Inhalation		population	
	DNEL	Short term	0.04 mg/m ³	Workers	Local
		Inhalation	· ·		
	DNEL	Long term Oral	0.09 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Short term Oral	0.11 mg/	General	Systemic
			kg bw/day	population	

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

 Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton @ or Nitrile, thickness ≥ 0.38 mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended.

Recommended gloves: Nitrile, thickness \geq 0.12 mm.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Date of issue/Date of revision : 6-6-2023 Date of previous issue : 15-12-2022 Version : 3 8/20

🖊 SMOOTH MASONRY PAINT MAGNOLIA

SECTION 8: Exposure controls/personal protection

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of

use, as included in the user's risk assessment.

: Personal protective equipment for the body should be selected based on the task **Body protection**

being performed and the risks involved and should be approved by a specialist

before handling this product.

: Appropriate footwear and any additional skin protection measures should be Other skin protection

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

: Based on the hazard and potential for exposure, select a respirator that meets the Respiratory protection appropriate standard or certification. Respirators must be used according to a

respiratory protection program to ensure proper fitting, training, and other important

aspects of use.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

Color : Various: See label.

Odor : Not available. **Odor threshold** : Not available. Melting point/freezing point : Not available. **Boiling point, initial boiling** : 100°C (212°F) point, and boiling range

Flammability

limit

: Not available.

Lower and upper explosion : Not available.

: Not available. Flash point

Auto-ignition temperature

Ingredient name	°C	°F	Method
2-(2-butoxyethoxy)ethanol	210	410	DIN 51794
2,2' -oxybisethanol	229	444.2	DIN EN 14522-S
2-ethoxyethanol	235	455	EU A.15
Paraffin waxes and Hydrocarbon waxes	244.85	472.7	
2-ethylhexyl acrylate	252	485.6	
n-butyl acrylate	275	527	
glyoxal	285	545	DIN 51794
2-methoxyethanol	285	545	
N-(2,3-dihydro-2-oxo-1H-benzimidazol-5-yl)-3-oxo-2-[[2-(trifluoromethyl)phenyl]azo]butyramide	290	554	
Polypropylene glycol #800	305	581	EU A.15
glycerol	370	698	

Date of issue/Date of revision : 6-6-2023 : 15-12-2022 Version : 3 9/20 Date of previous issue

SMOOTH MASONRY PAINT MAGNOLIA

SECTION 9: Physical and chemical properties

Cellulose,2-hydroxyethylether	380	716	
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	393	739.4	
ethanediol	398	748.4	
Methyl methacrylate	400	752	DIN 51794
diuron (ISO)	401	753.8	EU A.16
vinyl acetate	402	755.6	
ETHYL ALCOHOL	455	851	DIN 51794
styrene	490	914	
p-toluenesulphonic acid, containing a maximum of 5 % H2SO4	>465	>869	EU A.15
m-xylene	527	980.6	

Decomposition temperature: Not available.

pH : 8 [Conc. (% w/w): 100%] [DIN EN 1262] **Viscosity** : Kinematic: 529 mm²/s [DIN EN ISO 3219]

Solubility(ies) :

Media	Result
cold water	Soluble [OESO (TG 105)]

Partition coefficient: n-octanol/ : Not applicable.

water

Vapor pressure :

	V	apor Press	ure at 20°C	Vapor pressure at 50		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
ammonia	360.03	48				
vinyl acetate	84.76	11.3				
ETHYL ALCOHOL	42.95	5.7				
Methyl methacrylate	27.75	3.7				
Water	23.8	3.2				
glyoxal	15.15	2	EU A.4			
styrene	6.4	0.85				
2-methoxyethanol	6.23	0.83				
m-xylene	6	0.8				
n-butyl acrylate	3.75	0.5				
2-ethoxyethanol	3.75	0.5				
2-ethylhexyl acrylate	0.18	0.024				
ethanediol	0.09	0.012				
Distillates (petroleum), solvent- refined heavy paraffinic	<0.08	<0.011	ASTM D 5191			
Distillates (petroleum), hydrotreated heavy paraffinic	<0.08	<0.011	ASTM D 5191			
aluminium hydroxide	<0.075	<0.01				
2-(2-butoxyethoxy)ethanol	0.022	0.0029				

Date of issue/Date of revision : 6-6-2023 Date of previous issue : 15-12-2022 Version : 3 10/20

SMOOTH MASONRY PAINT MAGNOLIA

SECTION 9: Physical and chemical properties

2,2' -oxybisethanol	0.01	0.0013				
1-isopropyl- 2,2-dimethyltrimethylene diisobutyrate	<0.011	<0.0015	EU A.4			
isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	0.0098	0.0013	EU A.4			
glycerol	0.000075	0.00001		0	0	
Polyethylene glycol 20	0.0000003	0.00000004				
pyrithione zinc	<0.00000008	<0.000000011	OECD 104			
diuron (ISO)	0.000000006	0.0000000008	OECD 104	0.0000013	0.00000017	OECD 104
propylidynetrimethanol	0	0				
bronopol (INN)	0	0		0	0	
C(M)IT/MIT(3:1)	0	0				
Polypropylene glycol #800	0	0	OECD 104			

Relative density : 1.325

Density : 1.324 g/cm³ [DIN EN ISO 2811-1]

Vapor density : Not available.

Particle characteristics

Median particle size : Not applicable.

Percentage of particles with aerodynamic diameter ≤ 10

μm

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Conclusion/Summary: Not available.

Acute toxicity estimates

Date of issue/Date of revision : 6-6-2023 Date of previous issue : 15-12-2022 Version : 3 11/20

🖊 SMOOTH MASONRY PAINT MAGNOLIA

SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
bronopol (INN)	500	1100	N/A	N/A	N/A
diuron (ISO)	500	N/A	N/A	N/A	N/A
OIT	100	300	N/A	N/A	0.05
pyrithione zinc	100	N/A	N/A	N/A	0.05
1,2-Benzisothiazol-3(2h)-one	500	N/A	N/A	N/A	N/A
C(M)IT/MIT(3:1)	100	50	N/A	N/A	0.05

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
bronopol (INN)	Skin - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Moderate irritant	Human	-	10 mg	-
	Skin - Moderate irritant	Rabbit	-	80 mg	-
OIT	Eyes - Severe irritant	Rabbit	-	100 mg	-
1,2-Benzisothiazol-3(2h)-one	Skin - Mild irritant	Human	-	48 hours 5 %	-
C(M)IT/MIT(3:1)	Skin - Severe irritant	Human	-	0.01 %	-

Conclusion/Summary

: Not available.

Sensitization

Conclusion/Summary: Not available.

<u>Mutagenicity</u>

Conclusion/Summary: Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary: Not available.

Teratogenicity

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
bronopol (INN)	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
diuron (ISO)	Category 2	-	-
pyrithione zinc	Category 1	-	-

Aspiration hazard

Not available.

Information on the likely routes of exposure

: Not available.

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Date of issue/Date of revision : 6-6-2023 Date of previous issue : 15-12-2022 Version : 3 12/20

SMOOTH MASONRY PAINT MAGNOLIA

SECTION 11: Toxicological information

Skin contact: May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Not available.

General: Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Date of issue/Date of revision : 6-6-2023 Date of previous issue : 15-12-2022 Version : 3 13/20

SMOOTH MASONRY PAINT MAGNOLIA

SECTION 12: Ecological information

Product/ingredient name	Result	Species	Exposure
bronopol (INN)	Acute EC50 0.02 ppm Fresh water	Algae - Desmodesmus	96 hours
	Acute FOFO 4 Comme Freeh weter	subspicatus	40 h a : : : : :
	Acute EC50 1.6 ppm Fresh water Acute LC50 11.17 ppm Fresh water	Daphnia - Daphnia magna Fish - Lepomis macrochirus	48 hours 96 hours
	Chronic NOEC 1.94 ppm	Fish - Oncorhynchus mykiss	49 days
diuron (ISO)	Acute EC50 0.0023 mg/l Fresh water	Algae - Chlorella pyrenoidosa	96 hours
	Acute EC50 0.0027 mg/l Fresh water	Algae - Scenedesmus	96 hours
	The state 2000 crools might be seen that ex-	quadricauda	
	Acute EC50 7.6 µg/l Fresh water	Aquatic plants - Lemna	72 hours
		aequinoctialis	
	Acute EC50 0.005 mg/l Fresh water	Aquatic plants - Lemna sp.	96 hours
	Acute EC50 7.2 mg/l Fresh water	Daphnia - Daphnia magna -	48 hours
	A	Neonate	40.1
	Acute EC50 8.6 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 8.6 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute EC50 8.4 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute IC50 3.4 ppm Fesh water	Aquatic plants - Halodule	72 hours
	Addit 1000 2.41 µg/1 Marine Water	uninervis	72 110013
	Acute IC50 5.89 μg/l Marine water	Aquatic plants - Halodule	72 hours
		uninervis	
	Acute IC50 2.47 μg/l Marine water	Aquatic plants - Zostera muelleri	72 hours
	Acute LC50 3044 μg/l Marine water	Crustaceans - Palaemon serratus - Zoea	48 hours
	Acute LC50 2900 µg/l Fresh water	Fish - Cyprinus carpio - Fry	96 hours
	Acute LC50 3100 µg/l Fresh water	Fish - Morone saxatilis	96 hours
	Acute LC50 1.95 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic EC10 0.76 µg/l Fresh water	Algae - Fragilaria capucina ssp.	96 hours
		rumpens	
	Chronic EC10 0.11 µg/l Fresh water	Algae - Fragilaria capucina -	96 hours
		Exponential growth phase	
	Chronic IC10 0.47 µg/l Marine water	Aquatic plants - Halodule uninervis	72 hours
	Chronic IC10 0.7 µg/l Marine water	Aquatic plants - Halodule	72 hours
		uninervis	
	Chronic IC10 0.49 µg/l Marine water	Aquatic plants - Zostera muelleri	72 hours
	Chronic NOEC 0.283 µg/l Marine water	Algae - Nitzschia pungens	96 hours
	Chronic NOEC 0.34 µg/l Marine water	Aquatic plants - Halodule uninervis	72 hours
	Chronic NOEC 0.34 µg/l Marine water		72 hours
	Chronic NOEC 26.4 ppb	Fish - Pimephales promelas	60 days
	Chronic NOEC 26.4 ppb	Fish - Pimephales promelas	60 days
	Chronic NOEC 26.4 ppb	Fish - Pimephales promelas	60 days
	Chronic NOEC 33.4 µg/l Fresh water	Fish - Pimephales promelas - Embryo	63 days
OIT	Acute EC10 0.000224 mg/l	Algae - Navicula peliculosa	48 hours
	Acute EC50 0.084 mg/l	Algae - Desmodesmus	72 hours
	l	subspicatus	
	Acute EC50 0.00129 mg/l	Algae - Navicula peliculosa	48 hours
	Acute EC50 0.42 mg/l	Daphnia	48 hours
	Acute EC50 107 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 47 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 74 ppb Fresh water	Daphnia - Daphnia magna	21 days
nyrithione zinc	Chronic NOEC 8.5 ppb	Fish - Pimephales promelas	35 days 96 hours
pyrithione zinc	Acute EC50 0.51 μg/l Marine water	Algae - Thalassiosira pseudonana	30 HOURS
	Acute EC50 8.25 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 2.68 ppb Fresh water	Fish - Pimephales promelas	96 hours
		. '	
Date of issue/Date of revision	: 6-6-2023 Date of previous issue	· 15-12-2022 Version	• 3 14/20

Date of issue/Date of revision : 6-6-2023 Date of previous issue : 15-12-2022 Version : 3 14/20

SMOOTH MASONRY PAINT MAGNOLIA

SECTION 12: Ecological information

	. 0	Algae - Thalassiosira pseudonana	96 hours
	Chronic NOEC 2.7 ppb Fresh water	Daphnia - Daphnia magna	21 days
1,2-Benzisothiazol-3(2h)-one	Acute EC50 1.5 mg/l	Daphnia - Daphnia magna	48 hours
	Acute EC50 0.4 mg/l	Daphnia - Pseudomonas putia	16 hours
	•	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute LC50 1.3 mg/l	Fish - Ochorhyncus mykiss	96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
bronopol (INN)	0.18	-	low
diuron (ISO)	2.84	5.2	low
OIT	2.45	-	low
pyrithione zinc	0.9	11	low

12.4 Mobility in soil

Soil/water partition

coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

Date of issue/Date of revision : 6-6-2023 : 15-12-2022 Version : 3 15/20 Date of previous issue

SMOOTH MASONRY PAINT MAGNOLIA

SECTION 13: Disposal considerations

Disposal considerations

: Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no

longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 01 12 waste paint and varnish other than those mentioned in 08 01 11	

Packaging

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations

: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or

national legal provisions.

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG
14.1 UN number	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-
14.3 Transport hazard class(es)	-	-
14.4 Packing group	-	-
14.5 Environmental hazards	No.	No.

Additional information

IMDG

: Emergency schedules Not applicable.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

Date of issue/Date of revision : 6-6-2023 : 15-12-2022 Version : 3 16/20 Date of previous issue

🖊 SMOOTH MASONRY PAINT MAGNOLIA

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB) /REACH

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

VOC : Not available. : Not applicable. **VOC for Ready-for-Use**

Mixture

Industrial emissions

: Not listed

(integrated pollution prevention and control) -

Air

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Water

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Date of issue/Date of revision : 6-6-2023 :15-12-2022 Version : 3 17/20 Date of previous issue

🖊 SMOOTH MASONRY PAINT MAGNOLIA

SECTION 15: Regulatory information

Not listed.

15.2 Chemical Safety

: No Chemical Safety Assessment has been carried out.

Assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1, H317 Aquatic Chronic 3, H412	Calculation method Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H360FD	May damage fertility. May damage the unborn child.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated
	exposure.
H373	May cause damage to organs through prolonged or repeated
	exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Date of issue/Date of revision : 6-6-2023 :15-12-2022 Version : 3 18/20 Date of previous issue

🖊 SMOOTH MASONRY PAINT MAGNOLIA

SECTION 16: Other information

Acute Tox. 2 ACUTE TOXICITY - Category 2 Acute Tox. 3 **ACUTE TOXICITY - Category 3** Acute Tox. 4 **ACUTE TOXICITY - Category 4** Aquatic Acute 1 AQUATIC HAZARD (ACUTE) - Category 1 Aquatic Chronic 1 AQUATIC HAZARD (LONG-TERM) - Category 1 Aquatic Chronic 3 AQUATIC HAZARD (LONG-TERM) - Category 3 Asp. Tox. 1 ASPIRATION HAZARD - Category 1 Carc. 2 CARCINOGENICITY - Category 2 Eve Dam. 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eve Irrit. 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Liq. 2 FLAMMABLE LIQUIDS - Category 2 Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3 Met. Corr. 1 **CORROSIVE TO METALS - Category 1** Repr. 1B TOXIC TO REPRODUCTION - Category 1B Repr. 2 TOXIC TO REPRODUCTION - Category 2 Skin Corr. 1 SKIN CORROSION/IRRITATION - Category 1

Met. Corr. 1
Repr. 1B
Repr. 2
Skin Corr. 1
Skin Corr. 1A
Skin Corr. 1B
Skin Corr. 1C
Skin Irrit. 2
SKIN CORROSIVE TO METALS - Category 1
TOXIC TO REPRODUCTION - Category 2
SKIN CORROSION/IRRITATION - Category 1
SKIN CORROSION/IRRITATION - Category 1A
SKIN CORROSION/IRRITATION - Category 1B
SKIN CORROSION/IRRITATION - Category 1C
SKIN CORROSION/IRRITATION - Category 2

Skin Sens. 1
Skin Sens. 1A
Skin Sens. 1A
Skin Sens. 1B
SKIN SENSITIZATION - Category 1
SKIN SENSITIZATION - Category 1A
SKIN SENSITIZATION - Category 1B

STOT RE 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED

EXPOSURE) - Category 1

STOT RE 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED

EXPOSURE) - Category 2

STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -

Category 3

Date of printing : 14-6-2023 Date of issue/ Date of : 6-6-2023

revision

Date of previous issue : 15-12-2022

Version : 3

Notice to reader

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Safety Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.

Head Office

AkzoNobel Decorative Coatings BV, Christian Neefestraat 2, 1077 WW Amsterdam, The Netherlands

Date of issue/Date of revision : 6-6-2023 Date of previous issue :15-12-2022 Version : 3 19/20

SMOOTH MASONRY PAINT MAGNOLIA

Date of issue/Date of revision : 6-6-2023 Date of previous issue : 15-12-2022 Version : 3 20/20