

## DESCRIPTION

Johnstone's Flortred is a solvent based semi-gloss coating which is resistant to mild chemicals, water, oil and grease. Suitable for use on concrete, steel and wooden floors, in light to medium traffic areas. In areas prone to slip risk, the slip resistance of all Johnstone's floor coatings can be improved with the Anti-Slip Additive.

## RECOMMENDED USES



For light to medium traffic areas.

## SPECIAL PROPERTIES

Resistant to mild chemicals, water, oil and grease spillage.

## COLOUR RANGE

Black; Clear; Dark Green (14C39); Dark Grey (18B25); Morning Mist (10A03); Princess Grey (00A05); Sherwood Green; Safety Yellow (08E51); Safety Red (04E53); Safety Blue (18E53); Tile Red; White.

## FINISH

Semi-gloss.

## VOLUME SOLID

48%

## COVERAGE



Johnstone's Flortred will cover at the rate of approximately 11 square metres per litre depending on the nature and porosity of the surface being painted.

## DRYING TIME



Recoat after 16–24 hours under normal drying condition.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

## THINNER

TC2 Thinner and Cleaner.

## VOC CONTENT

HIGH VOC CONTENT 25–50%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/i): 500g/l (2010). This product contains max 500g/l VOC.

## FILM THICKNESS

Wet: 90µm, dry: 44µm.

## SIZE

Size: 2.5 Litre and 5 Litre. Note, some colours are only available in 5 Litre.

## PREPARATION

All surfaces to be painted should be clean, dry and free from dust, laitance and loose or flaking material. New concrete or cement should be allowed to mature for several months before painting. Very dense smooth concrete surfaces, such as power floated concrete, normally need to be acid etched before painting in order to promote satisfactory adhesion.

## APPLICATION



Stir well before use. Apply by brush or roller which should be fully loaded for best results. Apply evenly and avoid overspreading. First coat can be thinned up to 5% by volume of TC2 Thinner & Cleaner. Allow to dry overnight before applying a second coat if required. If more than one can of a colour is to be used in the same area, intermix before use.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with TC2 Thinner and Cleaner. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- **WARNING**
- Flammable liquid and vapour.
- Contains 2-butanone oxime. May produce an allergic reaction.
- Safety data sheet available on request.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- **IF ON SKIN:** Wash with plenty of water. Do not use solvent thinners or White Spirit.
- **IF SWALLOWED:** Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- When applying to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory protective equipment.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.