



Exterior Wood Protector

- Protects vertical and horizontal exterior wood from weathering
- Contains UV filters to help prevent fading from sunlight
- Long lasting protection
- Quick drying, non-drip formula
- Resistant to extreme temperatures -10°C - +35°C
- Clear finish



USAGE

Exterior

COVERAGE

1 Litre

10-12 m²

APPLICATION

Brush or roller

DRYING TIME

2 hours between coats, 24 hours final

TOOL CLEANING

Water

Product use

Liberon exterior wood protector is a versatile product which gives a water and UV resistant finish to most types of exposed timber. The clear finish will not alter the natural colour of the wood, but will form a protective barrier against weathering, sunlight and extreme temperatures of -10°C to +35°C. It is also ideal for use on both horizontal and vertical timber, making it suitable for pergolas, balustrades, fences, garden furniture and summer houses. Offering long lasting protection for up to 3 years on vertical timber in most climates and up to 18 months on horizontal timber, it is quick drying and easy to apply.

Preparation

Ensure the surface is clean, dry and free from previous finishes and dust. Lightly sand new wood and clean old wood with Liberon Tough Deck Clean and Revive or Liberon Garden Furniture Cleaner for wood.

Hardwoods: It is recommended to leave the wood exposed for up to 12 months before applying this product. This allows the grain in the wood to open and breathe and aids adhesion of the product.

Application

Stir very well before use to disperse all the ingredients in the tin. Ensure the weather conditions will be dry for 24 hours before application. Apply a generous, but not too thick, coat of exterior wood protector with a paint brush or roller. Allow to dry for 2 hours then apply a second coat. A third coat may be necessary on very porous timbers. Any unabsorbed product remaining on the surface should be evened out with a brush to avoid unsightly marks. Leave to dry for at least 24 hours before use.

Cleaning and maintenance

Liberon Ltd, Mountfield Industrial Estate, New Romney, Kent, TN28 8XU
Tel: 01797 367555 Fax: 01797 367575



For general maintenance clean with water. We recommend applying a further coat of exterior wood protector in heavy usage areas as and when required.

Precautions

- Wear suitable clothing and protective gloves.
- Store Liberon exterior wood protector at a temperature above 5°C. Always replace the lid otherwise the product can deteriorate.
- May not be suitable for some foreign hardwoods, test first on an inconspicuous area.
- On exterior oak we recommend the use of Liberon Pure Tung Oil.

Health and Safety

EUH208: Contains hydroxyphenyl benzotriazole and benzisothiazolinone. May produce an allergic reaction.

P102: Keep out of reach of children.

P271: Use only outdoors in a well-ventilated area.

P501: Dispose of contents/container to a waste collection centre. Do not leave impregnated cloths in bundles. Before discarding lay them flat outside to dry to avoid a fire hazard.

VOC information

EU limit for this product (CatA/f): 130 g/L (2010)

This product contains max 20 g/L VOC.

This product should be used in accordance with the manufacturer's instructions.

Recommendations are for guidance only since conditions of use are completely beyond our control. For technical advice please contact us on 01797 367555.

Liberon Limited
Mountfield Industrial Estate
New Romney
Kent
TN28 8XU
Tel: 01797 367555
Fax: 01797 367575
www.liberon.co.uk

Liberon Ltd is a V33 Group Company.