



## Quick Drying Tung Oil

- High quality natural oil for protecting interior wood
- Fast drying; 4 hours per coat
- Ideal for use on food contact surfaces – kitchen worktops, chopping boards and salad bowls
- Provides a long lasting matt finish
- Water, heat and alcohol resistant
- EN71 Approved – safe for toys



### USAGE

Interior

### COVERAGE

1 Litre

10-12 m<sup>2</sup>

### APPLICATION

Brush or cloth

### DRYING TIME

4 hours per coat, 24 hours final

### TOOL CLEANING

White Spirit

### Product use

Liberon Quick Drying Tung Oil is highly resistant to water, alcohol and food acids. Providing a hard wearing finish it is ideal for surfaces such as kitchen worktops, tables and all high quality interior wood. With each coat drying in just 4 hours, items such as worktops, salad bowls, chopping boards, furniture and other items in regular use can be quickly protected and brought back in to use. Being a penetrating oil it allows the wood to age gracefully and develop a natural patina.

### Preparation

Ensure the wood surface is bare: remove any wax finishes with Liberon Wax and Polish Remover and any varnish or oil finishes with Liberon Fine Wood Stripper. Clean, dry and ensure the surface is dust free.

### Application

Apply Quick Drying Tung Oil using a brush or lint-free cotton cloth. Allow the oil to penetrate for 20 minutes then wipe off the excess oil using a clean lint-free cloth. Allow to dry for 4 hours.

Apply further coats of Quick Drying Tung Oil as above, we recommend at least 4 coats on most woods. To check the surface is protected drop some water onto the wood and if the water beads, the surface is sealed. Allow 24 hours for the final coat to dry.

For best results gently rub with Liberon Ultra Fine Steel Wool (0000) between coats.

Furniture items may be finished with Liberon Wax Polish Black Bison for an improved lustre.



**Important:** Oil finishes bring out the natural colours of timber. A wet surface will be an indication of the final colour. Always test product on a spare surface or inconspicuous area for colour, compatibility and end result.

### **Cleaning and maintenance**

Quick Drying Tung Oil must be maintained on a regular basis. Apply at least once or twice a year or more if required, depending upon usage.

### **Precautions**

- Wear suitable clothing and protective gloves.
- Tung Oil is extracted from nuts and may cause an allergic reaction.
  - Store Liberon Tung Oil at a temperature above 5 °C. Always replace the lid otherwise the oil can deteriorate.
  - Oily cloths can self combust. Do not leave impregnated cloths in bundles. Before discarding lay them flat outside to dry to avoid a fire hazard.
  - If the excess is not removed and the surface becomes sticky, wipe with white spirit to remove the sticky film and allow to dry before continuing.

### **Health and Safety**

H226: Flammable liquid and vapour.

H226: Flammable liquid and vapour.

P102: Keep out of reach of children.

P210: Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P271: Use only in a well-ventilated area.

P501: Dispose of contents/container to a waste collection center

Oily cloths may self combust. Do not leave impregnated cloths in bundles. Before discarding lay them flat outside to dry to avoid a fire hazard.

This product should be used in accordance with the manufacturer's instructions.

Recommendations are for guidance only since conditions of use are completely beyond our control. For technical advice please contact us on 01797 367555.

Liberon Limited  
Mountfield Industrial Estate  
New Romney  
Kent  
TN28 8XU  
Tel: 01797 367555  
Fax: 01797 367575  
[www.liberon.co.uk](http://www.liberon.co.uk)