

MYLANDS

MASONRY PAINT FOR EXTERIOR USE

PRODUCT NAME	CODE SHEEN LEVEL
Masonry Paint (Pure White)	50 745 0001 8-10 %
PRODUCT DETAILS	PRODUCT BENEFITS
A waterbased acrylic for use on masonry.	Excellent coverage properties
NOT suitable over limewash or lime based renders. This paint is available in white only from stock, but may be tinted to a colour on request.	 Fast drying two coats can be applied in one day. Washable
APPLICATION	🛞 Low odour
• Ensure all surfaces are clean, dry and free of contamination.	Excellent stain and chemical resistance
 If painting over powdery or porous surfaces use stabilising solution. 	COVERAGE
 Treat algal/fungal contaminated surfaces with dilute 	On average per litre 15 m ² dependant on substrate exture and porosity.
bleach or with a proprietary wash.	DRYING TIME
 Do not use in extremes of temperature. Use between 8°C and 30°C. 	Touch dry inRecoat in1-2 hours.4 hours.
• Do not apply if there is likelihood of rain.	
	CLEANING
THINNING If necessary to thin, water should be used up to 10%.	Wash brushes/rollers immediately after use, in warm water containing a little detergent.
HEALTH & SAFETY	STORAGE
Refer to Mylands MSDS before use.	This product must be protected from frost. Store at temperature above 5° C.
	Use within 18 months. $+5^{\circ}C$

SIZES AVAILABLE





By Appointment to Her Majesty Queen Elizabeth II Manufacturers of French Polishes, Stains and Wax Polishes John Myland Limited, London