

PRODUCT DATA SHEET

No. 11157

OCTOBER 2008

RONSEAL DECKING END GRAIN PRESERVER

Ronseal End Grain Preserver has been specially formulated to preserve and protect the cross cut ends of timber against wood rotting fungi and wood destroying insects.

INTRODUCTION

Ronseal Decking End Grain Preserver is a highly effective preservative for use against wood rotting fungi and wood destroying insects, it completely protects and preserves even the most porous end grains. Thompson's End Grain Preserver is ideal for decking timber but is also suitable for all types of hardwood and softwood timber.

Ronseal Decking End Grain Preserver has a low solvent, low odour formulation with easy brush clean up.

Ronseal Decking End Grain Preserver is approved under The Control of Pesticides Regulation 1986 for use as directed. HSE No. 6991.

COMPOSITION

An aqueous solution of wood preservatives and other ingredients.

PROPERTIES

Appearance – Blue liquid, green when dry.

VOC Content – Minimal (0-0.29% w/v).

Viscosity – Slightly viscous.

Solubility - Miscible with water

FIELDS OF APPLICATION

Ronseal Decking End Grain Preserver is suitable for treating the end cuts of all types of hardwood and softwood and decking timber, including pre-treated, and preservative impregnated timber.

PREPARATION

Ensure all surfaces are clean, dry and free from dust, mildew, algae, oil deposits or other material which may interfere with the penetration of the preserver.

APPLICATION

A two coat application by brush is recommend.

COVERAGE

Ronseal Decking End Grain Preserver will coat approximately 3-4m² per litre per coat depending on the absorbency of the end grain.

DRYING TIME

Allow 24 hours between coats, and 3 days before overcoating.

CLEANING OF TOOLS

Clean equipment immediately after use with water and detergent. Remove as much product as possible from equipment before cleaning.

Do not empty Ronseal Decking End Grain Preserver into drains or water courses. Some local authorities have special facilities for disposal of waste coatings.

IMPORTANT NOTES

Refer to instructions on the pack before use.

This product is approved under The Control of Pesticides Regulations 1986 for use as directed. HSE No.6991.

Contains Boric Acid 0.494% w/w, Copper Carbonate Hydroxide 2.250% w/w and Propiconazole 0.050% w/w.

Read the label before you buy. Use pesticides safely.

Use only as a wood preservative.

HEALTH & SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

WEAR SUITABLE PROTECTIVE CLOTHING (COVERALLS) AND SYNTHETIC RUBBER/PVA GLOVES when using.

DO NOT CONTAMINATE FOODSTUFFS, EATING UTENSILS OR FOOD CONTACT SURFACES.

COVER WATER STORAGE TANKS before application.

THIS MATERIAL AND ITS CONTAINER must be disposed of in a safe way.

UNPROTECTED PERSONS AND ANIMALS SHOULD BE KEPT AWAY FROM TREATED AREAS FOR 48 HOURS OR UNTIL SURFACES ARE DRY.

DANEROUS TO FISH AND OTHER AQUATIC LIFE.

REMOVE OR COVER FISH TANKS AND BOWLS before application.

DO NOT CONTAMINATE watercourses or ground.

AVOID ALL CONTACT WITH PLANT LIFE.

ALL BATS ARE PROTECTED UNDER THE WILDLIFE AND COUNTRYSIDE ACT 1981. BEFORE TREATING ANY STRUCTURE USED BY BATS, CONSULT ENGLISH NATURE, SCOTTISH NATURAL HERITAGE OR THE COUNTRYSIDE COUNCIL FOR WALES.

READ THE PRECAUTIONS BEFORE USE. HSE No. 6991

WASH SPLASHES, from skin or eyes immediately.

WASH HANDS AND EXPOSED SKIN before meals and after use.

KEEP AWAY FROM FOOD, DRINK AND ANIMAL FEEDING STUFFS.

KEEP OUT OF REACH OF CHILDREN.

IF SWALLOWED, seek medical advice immediately and show the container or label.

KEEP IN ORIGINAL CONTAINER tightly closed in a safe place.

STORAGE

Store in a cool, dry, well ventilated place away from heat and sources of ignition.

Ensure container is fully re-sealed after use.

To avoid the risk of spillage always store and transport in a secure and upright position.

Store in original container.

FLAMMABILITY

Non-flammable product.
Flash point above 61°C.

SUPPLY

Obtainable from selected DIY retailers.

SIZES

Available in 250ml & 1 litre resealable containers.

DISPOSAL

Some local authorities have special facilities for disposal of waste products.

Dispose of in accordance with Local Authority requirements.

Do not empty product into drains or watercourses.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate results depend on factors beyond our direct control. Standard codes of painting practice should be followed.

INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

DATA SHEETS

Data sheets on other Ronseal products are available on request from our Technical Services Department.

Ronseal Ltd. has been registered to BS EN ISO 9000 1994 (Registered Firm No. FM 1669/1).

Ronseal Ltd. operates an Environmental Management System that complies with the requirements of BS 7750:1994, certificate No. EMS 35924.

Ronseal Ltd. has achieved Investors in People certification, (certificate number 59586).

©RONSEAL LTD.,

Thornclyffe Park,
Chapelton,
Sheffield.
S35 2YP

Tel:

+44 (0114) 240 9469 (Technical Services)

+44 (0114) 246 7171 (Main Switchboard)

Fax:

+44 (0114) 245 5629

E. Mail: enquiry@ronseal.co.uk

Website: www.ronseal.co.uk

Ronseal and Thompson's are registered trademarks of the Sherwin Williams Company.

OCTOBER, 2008. ISSUE 1