

## INT/EXT READY MIXED QUICK DRY FILLER



### GENERAL INFORMATION

#### Description

Ready mixed quick dry filler

#### Intended use

Interior/exterior  
• Minor surface repairs



### PRODUCT ADVANTAGES

- + Ready to sand & paint in 15 min\*
- + Excellent adhesion to substrates
- + Water and humidity resistant
- + White

### USE

#### DILUTION

Ready mixed

#### APPLICATION

##### - Conditions

Do not apply at temperatures of below +5°C or above +35°C, or at a relative humidity of above 80% H.R.

##### - Equipment

Blade, filling knife.

##### -Operational mode

Massage tube before use. Fill the cavity thoroughly, taking care to line the bottom while chasing air and level off with spatula.

##### - Equipment cleaning

With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

#### RECOMMANDATIONS

Apply two or more layers when filling deeper cavities. For filling large holes and cracks, it is recommended to use a PRESTONETT powder filler.

#### APPLICATION THICKNESS

3 mm

#### AVERAGE CONSUMPTION

130 ml/m<sup>2</sup>/mm thickness

#### SUBSTRATES

Concrete, cellular concrete, cement, concrete block, brick, plaster, plasterboard, gypsum board, primed wood, stone, polystyrene, old painted substrates, glass cloth.  
*Substrates must be hard, cohesive, clean, sound and dry according to the local standards.*

#### OVERCOAT


Primer, interior conventional paint, light-weight wall coverings.

\*Depending on substrate & atmospheric conditions



# INT/ EXT READY MIXED QUICK DRY FILLER

## TECHNICAL DATA

<b>COMPONANTS</b>	Based on water-soluble polymers.
<b>DENSITY</b>	1.55 ± 0.1
<b>pH</b>	8 ± 0.5
<b>COLOUR</b>	White
<b>WORKING TIME AT 20°C</b>	Unlimited
<b>WAITING TIME BEFORE OVERCOATING</b>	Once completely dry
<b>CLASSIFICATION</b>	NFT 36 005 famille IV class 4b
<b>V.O.C</b>	< 30 g/l (Ready mixed)
<b>HEALTH AND SAFETY</b>	 Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust. In case of prolonged contact, it is recommended to wear suitable gloves. Safety data sheet available on <a href="http://www.beissier.eu">www.beissier.eu</a> or <a href="http://www.quickfds.com">www.quickfds.com</a>
<b>PACKAGING</b>	200 ml tube
<b>STORAGE</b>	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : April 2017

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.