



Contractor Expanding Foam

POLYURETHANE EXPANDING FOAM FILLER



- Suitable for filling gaps & voids in and around the home
- Expands to fill all surface irregularities
- Can be cut, sawn, sanded, painted or plastered over
- Typical applications include gaps around door & window frames, pipe entries through brickwork & walls, insulating water pipes & tanks, & gaps around floor boards & skirting boards

HOW TO APPLY

- Ensure gaps to be filled are free from dust, dirt and loose particles.
- Surfaces to be sealed should be moistened prior to application (a water mister is ideal for this purpose).
- Wear gloves and protective eyewear during use.
- Shake the can vigorously to mix the contents.
- Screw the applicator nozzle onto the valve.
- Holding the can in the upside down position, press the trigger on the applicator nozzle to extrude foam. Only fill the cavity, as the foam will expand further after application.
- The foam will be cured in 2 hours, excess foam can be cut away if required.
- After application, remove the nozzle and clean
- If used externally, this product should be protected from U.V light. This can be achieved by painting, sealing or plastering over the cured material.

Pack Size: 750ml

Box Quantity: 12

To be stored upright in a cool, dry place. If product does not flow easily, do not force product out of can.

Health and Safety data sheet available on request



Geocel Limited

Western Wood Way, Langage Science Park,
Plympton, Plymouth, Devon PL7 5BG

Tel: 01752 334350

Fax: 01752 202065