BLACKFRIAR A TRADITION OF EXCELLENCE SINCE 1894

## **Technical Data Sheet**

Blackfriar Brick & Tile Paint

A matt red finish for application to red brick and tiles. This product restores faded colour, is self cleaning and weather resistant. Can be used for both interior and exterior projects. Ideal for doorsteps, roof tiles, bricks and masonry.

## Performance characteristics -

- Revives faded red brickwork and tiles.
- Self-cleaning.
- Weather resistant.
- Interior and exterior use.

**Preparation -** Ensure surface to be coated is clean, dry, sound and free from wax, grease or any other contamination. Treat any mould growth with Blackfriar Anti-Mould Solution, which should be allowed to dry completely before applying Blackfriar Brick and Tile Paint.

**Application** - Stir thoroughly prior to use with a broad stirrer. The product may be applied by brush, roller or spray. For best results we recommend applying by brush, working the paint into the tile or brick profile. Two coats are recommended to give best protection.

Thinning - Maximum 5% white spirit.

**Limitations -** Not suitable for use on quarry tiles. Blackfriar have specific products for floors and steps. Do not use under cold (less than 5°C), damp or humid conditions. Spreading rate of the first coat may be reduced on porous surfaces.

**Coverage -** Up to 14m<sup>2</sup> per litre per coat.

**Drying Time -** Touch dry in 2 - 4 hours. Recoat after 16 hours and within 3 days. Drying times are based on an ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the drying and overcoating times.

**Clean Up -** Remove as much product as possible from application equipment before washing with white spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

**Storage -** Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

## Warning

## Contains: naphtha (petroleum), hydrotreated heavy.

Flammable liquid and vapour.

May cause drowsiness or dizziness.

Keep out of reach of children.

Read label before use. If medical advice is needed, have product container or label at hand.

Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

Avoid breathing vapour or spray.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Call a doctor if you feel unwell.

Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains: Neodecanoic acid, cobalt salt. May produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking. EU limit values: 600g/l (2007) 500g/l (2010.) This product contains a maximum of 500g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.