



# Technical Data Sheet

## Blackfriar Enamel Paint

**Blackfriar Enamel Paint** is a tough, hard-wearing gloss enamel finish. Suitable for use on wood, metal and plaster. Ideal for garden tools, plaques and models.

### Performance characteristics –

- High gloss.
- Interior and exterior use.
- For use on wood, metal and plaster.
- Hard-wearing, tough and durable.

**Preparation** - Ensure the surface to be painted is clean, dry, and free from any rust, oils, wax or any other surface contamination. Remove any loose or flaking paint back to a firm edge, abrade any existing coating to provide a key. Rusty metals should be wire-brushed to a clean bright surface and primed immediately with Blackfriar Anti-Rust Primer. Galvanized metal should be degreased and primed with Blackfriar Multi-Surface Primer. New and bare surfaces should be primed with an appropriate primer such as Blackfriar Multi-Surface Primer.

**Application** - Stir thoroughly prior to use. The product may be applied by brush, roller or spray. Two coats are recommended to give best protection.

**Thinning** - Not recommended.

**Limitations** - Do not use under cold (less than 5°C), damp or humid conditions. Blackfriar Enamel Paint is not resistant to petrol or fuel oil (use Blackfriar Quick Drying Metal Paint). Not suitable for direct application to galvanised metal, use Blackfriar Multi-Surface Primer first.

**Coverage** - Up to 14m<sup>2</sup> per litre per coat.

**Drying Time** - Touch dry in 4-6 hours. Recoat after 12 hours and within 3 days. Drying times are based on an ambient temperature of 20°C and 50% relative humidity. Lower temperatures or higher humidity will prolong the

drying and overcoating times.

**Clean Up** - Remove as much product as possible from application equipment before washing with white spirit. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

**Storage** - Store in a dry, safe place. Do not store in environments where extreme temperatures may occur. Keep within 5-30°C. Do not store in direct sunlight.

### Warning

**Contains: Naphtha (petroleum), hydrotreated heavy.**

Flammable liquid and vapour. May cause drowsiness or dizziness.

Keep out of reach of children.

Read label before use.

If medical advice is needed, have product container or label at hand.

Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Avoid breathing vapour or spray.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Call a doctor if you feel unwell.

Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains neodecanoic acid, cobalt salt and 2-butanone oxime.

May produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking.

EU limit values: 400g/l (2007) 300g/l (2010.) This product contains a maximum of 300g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.