



## HICKSON<sup>®</sup> DECOR WOOD STAIN

### MICROPOROUS, TRANSLUCENT FINISH FOR WOOD

Hickson Decor Wood Stain is a range of translucent finishes which will enhance the beauty of wood, allowing its natural grain to show through. All are high build, coat-on-coat products - complete finishes from a single can. They can eliminate the need for a separate primer or undercoat, although they are fully compatible with Hickson Decor Predec Primers, if required. A high solids content compared with alternative wood finishes provides a superior spreading capacity and also gives a greater film thickness and increased durability of the coating.

#### AREAS OF USE

All interior and exterior softwood/hardwood applications.

#### MAIN FEATURES

- Repels water but allows wood to breathe
- Resists cracking, peeling and fading
- A complete protective finish in one can
- No primer or undercoat required
- Low maintenance

#### COLOUR AND CAN SIZES

Available in a range of translucent wood shade colours. A full display of all Hickson Decor Wood Stain colours is available in an accompanying leaflet. Hardwood shades available in dark and light.

Available in 0.5, 1.0, 2.5, 5.0 litres

#### METHODS OF APPLICATION

New timber should be well sanded, clean, non-oily and thoroughly dry. Brush apply evenly, 2-3 coats for exterior application or interior work, leaving 24 hours between coats.

Joinery supplied with a basecoat such as Hickson Predec – apply 2 brush coats leaving 24 hours between coats.

Previously stained wood should be clean. Lightly sand and apply 2 coats as required, leaving 24 hours between coats.

Old paint or varnish - strip back to bare wood, sand, clean and apply 2 to 3 coats leaving 24 hours between coats.

Stir thoroughly before and during use.

#### MAINTENANCE AND CLEANING

Remove dust and dirt by washing. remove loose material with a stiff brush. Mould and algae growth should be removed with a suitable fungicide. Recoat every 3-8 years as required.

Clean brushes and spillages with white spirit. Remove as much paint as possible from brush before washing. Some Local Authorities have special facilities for disposing of waste coatings. Do not empty paint into drains and watercourse. Do not use white spirit on skin. A proprietary hand cleaner should be used.

Protect from extremes of temperature during storage and application.



## HICKSON® DECOR WOOD STAIN

### MICROPOROUS, TRANSLUCENT FINISH FOR WOOD

#### DATA

<i>Solids (%w/w):</i>	59%-61% depending on colour
<i>Number of coats:</i>	3 coats to new bare timber 2-3 coats to timber where a translucent basecoat has been applied
<i>Drying time:</i>	Touch dry: 12 hours at 20°C Overcoating: after 24 hours
<i>Coverage:</i>	Up to 15 m <sup>2</sup> per litre depending on the texture of the substrate and timber species. A rough surface will reduce this figure. A test application is recommended.
<i>VOC</i>	EU Limit value for this product (cat A/e): 500 g/l (2007) / 400 g/l (2010). This product contains max. 389 g/l VOC.

#### FURTHER INFORMATION

Read the following prior to use:  
Hickson Decor - How to achieve the perfect longer lasting finish  
Hickson Decor - Code of Practice  
Hickson Decor Wood Stain Health & Safety Sheet

This is just one of a wide range of industrial wood coatings from Polyvine. Should you require any further information on this, or any other product within our range, simply contact us at the address below.



#### POLYVINE LIMITED

Severn Distribution Park,  
Sharpness, Gloucestershire,  
GL13 9UQ  
Tel: 0845 017 1671  
Fax: 0845 017 1670  
E-mail: [info@polyvine.com](mailto:info@polyvine.com)

#### EMERGENCY CONTACT

0208 762 8322  
(Only use this number in  
the event of a health or  
environmental emergency)