


QUICK DRY FILLER

TX 110

QUICK REPAIRS ON WALLS & CEILINGS

- ◆ WILL NOT SHRINK OR SLUMP
- ◆ EXCELLENT ADHESION & EASY TO SAND
- ◆ NO NEED TO SPOT PRIME
- ◆ WILL NOT FLASH OR GRIN



PURPOSE

Quick drying one-coat interior powder filler for filling to any depth. Ready to paint in 3 hours.

SUBSTRATES

Quick Dry Filler can be applied to new or renovated, painted or unpainted substrates:

- Gypsum plaster, plasterboards/drywall lining
- Old painted surfaces, cement, concrete, cellular concrete, breeze blocks, bricks, stone and primed wood.

OVERCOATING

Quick Dry Filler can be overcoated with any type of filler, paint or wall coating.

Do not coat directly with polyurethane paints nor epoxy solvent based paints.

Physical and technical FEATURES

- Quick Dry Filler: interior filler in powder form, made of cement, selected quarry material and resin.
- Characterization (NFT 36-005): Family III - class 3.
- Codification (EN 16-566): $G_3S_2V_0W_0A_0C_0R_0$.
- Mixing rate: add 450ml water per 1kg powder (45%).
- Application thickness: no depth limit.
- Capacity: 1kg fills 1L when mixed.
- Working time: 30 to 40 minutes.
- Setting time: second coat as soon as the filler is dry to the touch and sandable.
- Overcoating: can be painted in 3 hours average time (after complete drying, time relevant to a thickness coat of 1cm).
- Color: white.
- Adhesion: filler/substrate (EN 16-566): > 0.5 Mpa.

USE AND STORAGE CONDITIONS

- Application tools: filling knife, trowel or blade.
- Tool cleaning: after use, product residue can be rubbed off tools when dry (water cleaning is not necessary).
- Preservation: product guaranteed 12 months. Stored away from humidity. If found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase.

PACKAGING

Boxes: 1kg and 2kg.
Bag in bag: 5x1kg and 10x1kg.

RECOMMENDATIONS and care for use

The times mentioned are indicative and depend on the substrate, coat thickness, and the ambient conditions. Do not apply at a temperature below 8°C or above 35°C nor at a relative humidity over 70%.

SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices. Substrates must be hard, cohesive, clean, sound and dry.

NORMATIVE DOCUMENTS to be referred to

- BS EN 16566:2014 (Paints and varnishes. Fillers for internal and/or external works).

HEALTH AND SAFETY

It is recommended to wear gloves and glasses while applying Quick Dry Filler. Always wear a dust mask when sanding. Dispose of unused product and packaging responsibly at your local waste collection centre.

Safety data sheet available at www.toupret.co.uk

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from TOUPRET's experience and knowledge of the products. The product should be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorbency substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.



* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).