

# PRODUCT DATA SHEET

No. 11019

MARCH 2009

## Ronseal Anti-Bacterial Worktop Oil

Ronseal Anti-Bacterial Worktop Oil with Silver Guard technology harnesses the anti-bacterial qualities of Silver in a formulation ideal for enhancing and maintaining hardwood worktops. The waterproofing technology protects the wood's surface from water damage.

### INTRODUCTION

Ronseal Anti-Bacterial Worktop Oil uses Silver Guard anti-bacterial technology with a slow release formulation that delivers long lasting anti-bacterial protection killing E Coli and MRSA on contact and making it ideal for use in food preparation areas.

The highly water resistant formula protects worktops from the damaging effects of water, penetrating deep into the wood to feed and nourish worktops, helping them to resist splitting and cracking. The high quality oil enhances the natural beauty of the hardwood leaving a clear soft sheen finish.

### COMPOSITION

Contains mineral oil and silver containing Biocide.

### PROPERTIES

Appearance-Low viscosity liquid.  
Colour - Colourless.  
Odour- Odourless.  
Solubility - Miscible with water.  
VOC Content - Low (0.3-7.99%w/v).  
Flashpoint - >60CC  
Flammable.

### FIELDS OF APPLICATION

Ronseal Anti-Bacterial Worktop Oil is ideal for use on hardwood worktops.

### PREPARATION

On previously treated worktops ensure worktop surface is clean, dry and in good condition.

With new or untreated worktops it may be necessary to lightly sand the surface of the worktop to remove any loose wood fibres. Avoid inhalation of dust, wear a suitable face mask when sanding.

Further sanding may be required if the wood is heavily stained or discoloured in places. Do not use steel wool or metal brushes for sanding.

Finally, before application wipe down the worktop with white spirit using a cloth to remove any grease, resin or wax which may affect performance. Allow to dry before applying Ronseal Anti-Bacterial Worktop Oil.

### APPLICATION

Shake tin thoroughly for at least one minute before use. Ronseal Anti-Bacterial Worktop Oil can be applied by either brush or cloth. The oil should be at room temperature before application. To achieve the best finish, apply several thin coats. Apply liberally using a soft, dry lint free cloth or soft paint brush. Work lightly into the wood grain. Leave for 10 minutes and then wipe off any excess oil using a clean, lint free cloth. Apply 3-4 coats, leaving 24 hours between coats.

### DRYING TIME

Leave 24 hours between coats.

### CLEAN-UP

Wash brushes out in white spirit. Wash cloths out in warm, soapy water before disposal. Some local authorities have special facilities for disposing of waste products. Do not empty into drains or watercourses. Ensure container is fully re-sealed after use.

### MAINTENANCE

To maintain waterproof and anti-bacterial protection it is recommended to recoat the worktop with one coat, twice a year or more frequently if required. The worktop needs a maintenance coat when water on the worktop surface smudges instead of forming beads of water or when the worktop has lost its sheen.

### IMPORTANT NOTES

Refer to instructions on the pack prior to use.

Whilst building up layers of oil, take care not to stain the worktop.

Final colour will depend on the colour and porosity of the wood. Always try a test area prior to application.

### STORAGE

Ensure container is fully resealed after use.

To avoid the risk of spillage, always store and transport in a secure and upright position.

### HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Keep out of reach of children.

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, was immediately with plenty of water.

Use only in well-ventilated areas.

### FLAMMABILITY

Non-flammable.  
Flashpoint >60°C

### SUPPLY

Obtainable from DIY retailers.

## **SIZES**

Available in a 1 Litre resealable container.

## **DISPOSAL**

Some local authorities have special facilities for disposal of waste products.

Do not empty product into drains or watercourses.

## **LIABILITY**

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate results depend on factors beyond our direct control. Standard codes of painting practice should be followed.

## **INFORMATION AND SERVICE**

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

## **DATA SHEETS**

Data sheets on other Colron products are available on request from our Technical Services Department.

Ronseal Ltd. has been registered to BS EN ISO 9000 1994 (Registered Firm No. FM 1669/1).

Ronseal Ltd. operates an Environmental Management System that complies with the requirements of BS 7750:1994, certificate No. EMS 35924.

Ronseal Ltd. has achieved Investors in People certification, (certificate number 59586).

**©RONSEAL LTD.,**  
Thorncliffe Park,  
Chapelton,  
Sheffield.  
S35 2YP

**Tel:**  
**+44 (0114) 240 9469 (Technical Services)**  
**+44 (0114) 246 7171 (Main Switch board)**  
**Fax:**  
**+44 (0114) 245 5629**

**E. Mail:** [enquiry@ronseal.co.uk](mailto:enquiry@ronseal.co.uk)  
**Website:** [www.ronseal.co.uk](http://www.ronseal.co.uk)

Ronseal and Colron are registered trademarks of the Sherwin Williams Company.

MARCH 2009. ISSUE 1