

VINYL MATT

Dulux Trade Vinyl Matt is a top quality, high opacity emulsion based on unique **AkzoNobel** technology which gives excellent coverage with a high quality finish. **Dulux Trade Vinyl Matt** has a good flow for easy application. Suitable for all normal interior wall and ceiling surfaces. Our formula is 99.9% VOC free, based on in-can VOC content and measured in accordance with ISO 11890-2:2013. It has also been independently tested for emissions, including formaldehyde, TVOC, TSVOC and Cat 1A & 1B carcinogens. Tested and Approved by Professional Decorators, find out more about the process at duluxtrade.co.uk/testedandapproved.

KEY BENEFITS

- High Quality Finish
- Smooth flow for easy application
- Excellent Opacity & Coverage
- Tough, Wipeable Finish

PRODUCT INFORMATION

Typical Use

Suitable for interior use on all normal interior wall and ceiling surfaces.

Where condensation is a problem e.g. some kitchens and bathrooms, use **Dulux Trade Diamond Eggshell**. For interior areas that are likely to suffer from mould growth, use **Dulux Trade Mouldshield Fungicidal Eggshell***.

Pack Size

1L, 2.5L, 5L and 10L.

Colour Range

See appropriate **Dulux Trade** colour literature or visit duluxtrade.co.uk.

Film Properties

Chemical Resistance: Not suitable.

Heat Resistance: Not suitable for use on heated surfaces, such as radiators.

Water Resistance: Where frequent heavy condensation is likely, as in some kitchens and bathrooms, **Dulux Trade Diamond Eggshell** is more suitable.

Composition (nominal)

Pigment: Lightfast Pigments.

Binder: Acrylic Copolymer Emulsion.

Solvent: Water.

Volume Solids

White – 36%, PBW – 36% (nominal). Other colours will vary.

SURFACE PREPARATION

To get the best results with **Dulux Trade Vinyl Matt**, make sure surfaces to be painted are sound, clean, dry (new surfaces particularly must be fully dry).

Remove all loose and defective paint. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Where necessary, wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with

VINYL MATT

clean water and allow to dry. Seal surfaces that remain powdery after thorough preparation with an appropriate plaster sealer.

Where necessary, rub down and then wipe off with a damp, lint free cloth to avoid dust.

Any surface defects should be filled with the appropriate **Polycell Trade Polyfilla**.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Seal new or bare surfaces with a thinned first coat of **Dulux Trade Vinyl Matt** (up to 1 part clean water to 5 parts paint). The normal finishing process is 2 full coats of **Dulux Trade Vinyl Matt**, but on previously painted surfaces in good condition where similar colours are used, 1 coat may be sufficient.

For best colour consistency, purchase sufficient tinted paint for each job including touch-in at one time from the same source.

APPLICATION METHOD

Brush, roller or airless spray.

As with other water-based paints, do not apply at temperatures below 8°C (as recommended by British Standard BS 6150).

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 17m² per litre.

Thinning

Sealing new or bare surfaces: Add up to 1 part clean water to 5 parts paint.

Normal use (not to be exceeded): Add up to 1 part clean water to 10 parts paint.

Airless spray application: For normal use no thinning is required.

Spray Recommendations

Airless Spray: For best results use a 515 or 517 Low Pressure tip @ 1300 -1700 psi (89 – 117 bar). Alternatively use a 515 or 517 tip @ 2200 – 2600 psi (152 – 179 bar).

Please note that the above recommendations are intended as a guideline only and some adjustments may need to be made to accommodate equipment type & age, substrate type and individual site & atmospheric conditions.

Drying Times

Single coat at standard thickness:

Touch Dry: Dependent on temperature and humidity.

Recoat: 2-4 hours.

Cleaning Up

After use, remove as much product as possible from equipment before cleaning with water.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at duluxtrade.co.uk/sustainability.

Transportation & Storage



Issued 01/24

411

VINYL MATT

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

This product contains max. 0.3g/l VOC. VOC content: Trace (<0.1%).

VOC

EU limit value for this product (cat.: A/a): 30g/l (2010).

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

* **Dulux Trade Mouldshield** Fungicidal Eggshell contains: 3-iodo-2-propynyl-n-butyl carbamate.

Use biocides safely. Always read the label and product information before use.

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet (SDS 411) is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting duluxtrade.co.uk.

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Mouldshield, Polycell, Polyfilla and Community RePaint are trademarks of the AkzoNobel group. © AkzoNobel 2024.