

TECHNICAL DATA SHEET

GLITTER TOPCOAT

DESCRIPTION

Acrylic-based wall varnish with glitter gloss. For a sparkling finish for painted walls and wood. Also protects walls painted in a dark colour. For interior use.

USE

Can be applied to painted walls and wood.

COLOUR

Available in gold and disco colours.

APPLICATION AND HANDLING

Stir thoroughly prior to use. Apply 1 to 3 coats using an acrylic paint brush, acrylic paint roller or paint sprayer. Do not dilute. Always apply wet-in-wet to avoid visible strokes.

COVERAGE

Approx. 18 m²/litre per coat depending on the object to be painted and the application method.

DRYING

23°C and 65% relative humidity. Dust-dry after approximately 1 hour. Can be painted over after approximately 4 hours.

APPLICATION ADVICE

GENERAL

Surfaces must be clean, dry and free from dust or grease.

UNTREATED WOOD

- Degrease, sand lightly and remove any dust. Round off sharp edges to maximise adhesion.
- Next apply 2 or 3 coats of the topcoat.

PAINTED WALLS

- Carefully degrease with a degreasing agent and water.
- Next apply 2 or 3 coats of the topcoat.

TECHNICAL DATA

GOLD AND MIX EFFECT

Binding agent	Acrylic emulsion
Pigments	None
Solvent	Water
Solid components	Approx. 26% by volume
Specific mass	Approximately 1 g/ml
Recommended coat thickness	50 micron wet
Degree of gloss	Eggshell gloss, 35% @ 60°
Dilute with	Water
Hazard classification	See MSDS
Tool cleaning instructions	Use water and soap

STORAGE

Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

GENERAL

Stir thoroughly prior to use. We recommend applying at temperatures between 8°C and 30°C. After use, close the container correctly and store in an upright position in a frost-free area.

SURPLUS PRODUCT

This product and the packaging should be disposed of at a collection point for hazardous or special waste.