

## WOOD REPAIR



### GENERAL INFORMATION

#### Description

Powder wood filler

#### Intended use

- Interior/exterior
- Filling holes & cracks in all types of woodwork
- Repair broken angles
- Reconstitute missing wood due to decay

Use



Application thickness



Working time



Dilution



Manual application



### PRODUCT ADVANTAGES

- + Easy to mix
- + Excellent adhesion to substrates
- + No thickness limitation
- + Very hard when dry
- + Can be carved, drilled and painted
- + Can be tinted
- + Easy to sand
- + Fine finish



### USE

#### DILUTION

50% - 0.50 litre of water per 1 kg of powder

#### PREPARATION

Gradually pour the powder into water, stirring until a homogeneous paste is obtained

#### APPLICATION

##### Conditions

Do not apply at temperatures of below +5°C or above +35°C, or at a relative humidity of above 80% H.R.

##### Equipment

Filling knife, blade.

##### Equipment cleaning

With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

#### RECOMMENDATION

On soft or friable wood, it is advised to apply a wood hardener.

#### APPLICATION THICKNESS

Any thickness

#### AVERAGE

#### CONSUMPTION

1 kg of powder fills a volume of 1 litre

#### SUBSTRATES

Most types of wood including chipboard, plywood and exotic species.  
*Substrates must be hard, cohesive, clean, sound and dry according to the local standards.*


#### OVERCOAT

Wood stains, varnishes, primers and conventional interior & exterior paints.

## WOOD REPAIR



### TECHNICAL DATA

<b>COMPONANTS</b>	Polymer base aqueous phase coat mix, mineral fillers, additives.
<b>pH</b>	7 ± 0,5
<b>COLOUR</b>	White
<b>WORKING TIME AT 20°C</b>	35 min
<b>WAITING TIME BEFORE OVERCOATING</b>	Approximately 3 hours (Depending on application thickness, humidity & temperature)
<b>CLASSIFICATION</b>	NF T 36-005 - Family IV, class 4c
<b>NORM</b>	NF EN 16566
<b>V.O.C</b>	< 0,5 g/l (Ready mixed)
<b>HEALTH AND SAFETY</b>	 <p>Use in a well-ventilated place. Avoid direct contact with skin and eyes. Do not breathe dust. In case of prolonged contact, it is recommended to wear suitable gloves. Safety data sheet available on <a href="http://www.beissier.eu">www.beissier.eu</a> or <a href="http://www.quickfds.com">www.quickfds.com</a></p>
<b>PACKAGING</b>	1 kg
<b>STORAGE</b>	12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : February 2019

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.