

PRODUCT DATA SHEET

COLRON REFINED FINISHING WAX

Colron Refined Finishing Wax is a blend of specially selected pure waxes which gives a beautiful soft sheen finish to the wood surface.

INTRODUCTION

Colron Refined Finishing Wax is a blend of pure waxes including beeswax and carnuba wax. Colron Refined Finishing Wax gives a soft sheen finish and will enhance the natural sheen of the wood and provide lasting beauty and protection.

COMPOSITION

An emulsified blend of waxes, containing light fast pigments.

PROPERTIES

Appearance- Paste.
Colour – Fawn to light brown.
Odour- Characteristic solvent type.
Solubility- Immiscible with water.
VOC Content- Very High (>50%w/v).
Flash Point- 41°C.

FIELDS OF APPLICATION

Colron Refined Finishing Wax can be applied directly over previously waxed or polished surfaces but for best results old finishes should be removed. Colron Refined Finishing Wax cannot be used over sealed surfaces such as varnish or paint.

For interior use only.

PREPARATION

Previous coatings such as wax, polish or lacquer should be removed using Colron Wax Remover. Paint or varnish must be removed using Colron Furniture Stripper prior to application.

In both cases the bare wood should be treated with Colron Wood Reviver to feed and nourish the wood.

Ensure all surfaces are clean and dry. Lightly sand and wipe with white spirit.

APPLICATION

Shake well prior to use. If the wax appears solid allow it to reach room temperature before use.

Apply a thin coat onto the surface by rubbing along the direction of the grain with a lint free cloth or Colron Fine Steel Wool (Grade 00000).

When dry buff the surface with a lint free cloth or steel wool along the wood grain.

Apply a second coat as above. Further coats will provide a deeper intensity of colour.

CLEAN-UP

Dispose of application cloths safely.

Some local authorities have special facilities for disposing of waste product. Do not empty into drains or watercourses.

MAINTENANCE

Apply further coats as required as directed above.

IMPORTANT NOTES

Refer to instructions on the pack prior to use.

For best results apply to bare wood.

Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood as they may contain harmful lead. For further advice contact Ronseal Technical Services.

STORAGE

Store upright in a cool, dry, well ventilated area away from heat and sources of ignition.

Ensure container is fully resealed after use.

Always store in ambient conditions away from temperature extremes. Protect from frost. Store above 5°C.

To avoid the risk of spillage, always store and transport in a secure and upright position.

The shelf life of the product in airtight containers will be at least 3 years.

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Specific health and safety data sheets are available on request.

FLAMMABILITY

Flashpoint: 41°C

SUPPLY

Obtainable from DIY retailers, paint suppliers and builders merchants.

SIZES

Available in a 180g resealable container.

DISPOSAL

Some local authorities have special facilities for disposal of waste products.

Do not empty product into drains or watercourses.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate results depend on factors beyond our direct control. Standard codes of painting practice should be followed.

INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

DATA SHEETS

Data sheets on other Colron products are available on request from our Technical Services Department.

Sherwin-Williams Diversified Brands Ltd operates a quality management system that complies with the requirements of ISO 9000:2008 (Certificate No. FM 01669).

Sherwin-Williams Diversified Brands Ltd operates an Environmental Management System that complies with the requirements of ISO 14001:2004 (Certificate No. EMS 35924).

Sherwin-Williams Diversified Brands Ltd
Thornccliffe Park
Chapeltown
Sheffield
S35 2YP

Tel: +44(0)114 246 7171
Fax: +44(0)114 245 5629

Registered in England 2968830

E. Mail: enquiry@ronseal.co.uk
Website: www.ronseal.co.uk

Ronseal is a Registered Trademark of the Sherwin-Williams Company.

JULY, 2017. ISSUE 2.