

# PRODUCT DATA SHEET

## COLRON WOOD REVIVER

Colron Wood Reviver is designed to replenish the essential oils in dry, tired wood after stripping, to help prevent the wood warping and splitting.

### INTRODUCTION

Colron Wood Reviver penetrates deep down, feeding and nourishing wooden furniture which may be old or dry after stripping. Colron Wood Reviver replaces essential oils which are necessary to help prevent the wood from drying, warping and splitting. Colron Wood Reviver dries to form a natural, protective barrier against spills and stains prior to finishing.

### COMPOSITION

A blend of vegetable oils and resins in aromatic hydrocarbon solvents. Contains no added lead.

### PROPERTIES

Appearance-Low viscosity liquid.  
Colour -Medium brown.  
Odour-Characteristic solvent type.  
Solubility-Immiscible with water.  
VOC Content-Very High (>50%w/v).  
Flammable.

### FIELDS OF APPLICATION

Colron Wood Reviver can only be applied to bare interior wooden furniture.

### PREPARATION

Previous coatings such as wax, polish or lacquer should be removed using Colron Wax Remover, Paint or varnish must be removed using Colron Furniture Stripper prior to application.

Ensure all surfaces are clean and dry. Lightly sand and wipe with white spirit.

### APPLICATION

Shake well prior to use. Apply a thin coating Of Colron Wood Reviver with a clean, soft cloth, rubbing the liquid well into the grain, leaving none on the surface. Very old, dry or weathered wood may require a more generous application. Allow to dry for 24 hours before applying a finish.

### DRYING TIME

Allow 24 hours before applying a finish.

### CLEAN-UP

Cloths and soiled rags may self-ignite without warning. Wash out well in warm soapy water before disposal.

Remove as much product as possible from cloths prior to cleaning.

### FINISHING

Finishing with one of the Oils or Waxes from the Colron Furniture Care Range.

### IMPORTANT NOTES

Refer to instructions on the pack prior to use.

Apply only to bare wood.

Cloths and soiled rags may self-ignite without warning. Wash out well in warm soapy water before disposal.

Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood as they may contain harmful lead. For further advice contact Ronseal Technical Services.

### STORAGE

Store upright in a cool, dry, well ventilated area away from heat and sources of ignition.

Ensure container is fully resealed after use.

Always store in ambient conditions away from temperature extremes. Protect from frost. Store above 5°C.

To avoid the risk of spillage, always store and transport in a secure and upright position.

The shelf life of the product in airtight containers will be at least 3 years.

### HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Specific health and safety data sheets are available on request.

### FLAMMABILITY

Flammable.  
Flashpoint 44°C

### SUPPLY

Obtainable from DIY retailers, paint suppliers and builders merchants.

### SIZES

Obtainable in a 250ml resealable container.

### DISPOSAL

Some local authorities have special facilities for disposal of waste products.

Do not empty product into drains or watercourses.

### LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any

work as the ultimate results depend on factors beyond our direct control. Standard codes of painting practice should be followed.

#### **INFORMATION AND SERVICE**

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

#### **DATA SHEETS**

Data sheets on other Colron products are available on request from our Technical Services Department.

Sherwin-Williams Diversified Brands Ltd operates a quality management system that complies with the requirements of ISO 9000:2008 (Certificate No. FM 01669).

Sherwin-Williams Diversified Brands Ltd operates an Environmental Management System that complies with the requirements of ISO 14001:2004 (Certificate No. EMS 35924).

**Sherwin-Williams Diversified Brands Ltd**  
**Thornccliffe Park**  
**Chapelton**  
**Sheffield**  
**S35 2YP**

Tel: +44(0)114 246 7171  
Fax: +44(0)114 245 5629

*Registered in England 2968830*

E. Mail: [enquiry@ronseal.co.uk](mailto:enquiry@ronseal.co.uk)  
Website: [www.ronseal.co.uk](http://www.ronseal.co.uk)

Ronseal is a Registered Trademark of the Sherwin-Williams Company.

MAY, 2017. ISSUE 2.