

INT/EXT READY MIXED FILLER

GENERAL INFORMATION

Description

Intended use

Ready mixed filler

Interior/exterior

• Filling small holes and cracks











PRODUCT ADVANTAGES

- Excellent adhesion to substrates
- 🕂 Easy to apply
- Dries hard
- Easy to sand
- Odourless

USE

DILUTION Ready mixed

APPLICATION

- Conditions Do not apply at temperatures of below $+5\,^{\circ}\text{C}$ or

above +35°C, or at a relative humidity of above

80% H.R.

- Equipment Filling knife, blade, smoothing trowel.

- Equipment cleaning With water before completely dry.

> Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the

environment.

APPLICATION THICKNESS 1 cm

AVERAGE CONSUMPTION 0.5 kg/m^2

SUBSTRATES Concrete, cement, brick, concrete block, old

> painted substrates, plaster, plasterboard. Substrates must be hard, cohesive, clean, sound

and dry according to the local standards.

OVERCOAT Primer, interior conventional paint, light-weight

wall coverings, fibreglass cloth.

INT/EXT READY MIXED FILLER

TECHNICAL DATA

COMPONANTS Polymer base aqueous phase coat mix, mineral

fillers, additives.

DENSITY 1.7 ± 0.1

pН 8 ± 1

COLOUR White

WORKING TIME AT 20°C Unlimited

WAITING TIME BEFORE OVERCOATING

Once completely dry

CLASSIFICATION NF T 36 005 Family III - class 2

NORM NF EN 16566

V.O.C < 20 g/I (Ready mixed)

HEALTH AND SAFETY





Use in a well-ventilated place. Avoid direct contact with

skin and eyes. Do not breathe dust.

In case of prolonged contact, it is recommended to

wear suitable gloves.

Safety data sheet available at www.brewers.co.uk.

PACKAGING 1 kg bucket

STORAGE 12 months from date of manufacture, in unopened

original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store

in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product.

Date of issue : April 2017
The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.



Help Line: 0845 504 5040