

## DESCRIPTION

Johnstone's Trade Acrylic Satin is a premium quality satin sheen finish that is suitable for use on interior wood and metal surfaces. It provides a low odour, high opacity finish that is quick drying and non-yellowing. Also suitable for exterior use.

## RECOMMENDED USES



Suitable for interior and exterior use.

## TYPE OF SUBSTRATE

Wood and metal.

## COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

## FINISH

Satin.

## VOLUME SOLID

35%

## COVERAGE



Johnstone's Trade Acrylic Satin will cover approximately 12 square metres per litre depending on the nature and porosity of the surface.

## FILM THICKNESS

Wet: 80µm, dry: 28µm.

## DRYING TIME



Touch dry 1-2 hours.  
Recoat after 4 hours.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Do not use empty container for storing food. PROTECT FROM FROST

## THINNER

Thinner: Clean water.

## VOC CONTENT

EU limit value for this product (Cat A/d): 130g/l (2010) This product contains max 50 g/l VOC



## KEY PROPERTIES

- Non-yellowing, high opacity
- Low odour, quick drying satin finish
- For interior and exterior use

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down sound glossy surfaces with fine waterproof abrasive paper and rinse thoroughly before applying a pre-coat of Johnstone's Trade Joncryn Water-Based Primer Undercoat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Treat knots with Johnstone's Trade Woodworks Knotting Solution and prime exposed wood and metal surfaces with an appropriate primer. Special precautions should be taken during the surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).

## APPLICATION



Ensure good ventilation during application and drying. Stir well before use and apply by brush or roller. Apply liberally and evenly for a smooth finish. Two coats are recommended under most conditions. Ensure the room is well ventilated while you are painting and while the paint is drying. Do not apply in temperatures below 10°C or in damp conditions.

## CLEANING



Remove as much paint as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available: [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354

## SIZES

1 Litre, 2.5 Litre, 5 Litre.