

## DESCRIPTION

Johnstone's Trade Advanced Multi Surface Primer is a high performance, anti-corrosive, low odour, water based primer. It has been specially formulated to provide outstanding adhesion over a variety of difficult to adhere to surfaces including, ceramic tiles, galvanised steel, aluminium, melamine and MDF. It also has good anti-corrosive properties making it ideal for use on ferrous metals. It can be overcoated with any Johnstone's Trade undercoat and topcoat. Complies with ISO12944-2:C2-C3 for Atmospheric Corrosivity - suitable for use in urban and industrial atmospheres with moderate sulphur dioxide pollution.

## RECOMMENDED USES



Primes Pine Wood, Steel, Galvanised Steel, aluminium, Copper, PVC\*, Ferrous Metals, MDF, Perspex, Formica, Glass, Old Epoxy Ceramic Tiles, And more...

## COLOUR RANGE

Available in white.

## FINISH

Matt

## VOLUME SOLID

38%

## COVERAGE



Johnstone's Trade Advanced Multi Surface Primer will cover approximately 10-12 square metres per litre depending on the nature and porosity of the surface.

## FILM THICKNESS

Wet: 80µm Dry: 30µm

## DRYING TIME



Under normal conditions, touch dry in 1-2 hours and recoatable after 4 hours. Ensure good ventilation during application and drying.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position. Do not use empty container for storing food. Keep container tightly closed. PROTECT FROM FROST.

## THINNER

Cleaner: Clean water.

## VOC CONTENT

EU limit value for this product (Cat A/i): 140g/l (2010) This product contains max 100 g/l VOC



## KEY PROPERTIES

- Outstanding adhesion
- Coats difficult surfaces
- Anti Corrosive

**Benefits** - Outstanding Adhesion, Quick Drying  
Surfaces Stated - Pine Wood, Steel, Galvanised Steel, aluminium, Copper, PVC\*, Ferrous Metals, MDF, Perspex, Formica, Glass, Old Epoxy Ceramic Tiles, And more...

\*excluding windows and doors

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material, dirt, grease or other surface contaminants. Any existing rust or millscale should be removed. Certain surfaces should be lightly sanded with a fine waterproof abrasive paper and wiped clean. Avoid inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during the surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).

## APPLICATION



Ensure good ventilation during application and drying. Stir well before use. Easy to apply by brush or roller. Do not apply in temperatures below 8°C or externally when rain is imminent.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354

## SIZES

1 Litre and 2.5 Litre.