

DESCRIPTION

Johnstone's Trade Air Pure is an air purifying wall and ceiling paint that improves indoor air quality. Formulated with a biobased binder and contained in 100% recycled packaging, Johnstone's Trade Air Pure is the perfect paint for sustainable projects.

RECOMMENDED USES



Ceiling & walls.

TYPE OF SUBSTRATE

Suitable for all interior walls and ceilings both bare and previously painted including plaster, plasterboard, concrete etc.

COLOUR RANGE

Available in over 6,000 colours via the Johnstone's Tinting System.


FINISH

Matt

VOLUME SOLID

35%

COVERAGE




Johnstone's Trade Air Pure will cover up to 11 square metres per litre depending on the nature and porosity of the surface.

FILM THICKNESS

Wet: 100µm Dry: 35µm

DRYING TIME



Touch dry in 1 hour. Recoatable after 4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position. Do not use empty container for storing food. Keep container tightly closed. PROTECT FROM FROST.

THINNER

Cleaner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/a): 30g/l (2010) This product contains max 1g/l VOC



KEY PROPERTIES

- Air purifying technology logo
- Improved indoor air quality (ISO16000-23)
- Sustainable formulation 45% biobased
- Flat matt finish

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Avoid over spreading. Seal absorbent surfaces such as new plaster with a coat of Johnstone's Trade Air Pure thinned up to 5% with clean water. Do not apply in temperatures below 10°C or in damp conditions.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

5 Litre.