

DESCRIPTION

Johnstone's Trade Aqua Guard is our most durable Water Based Satin paint for interior wood and metal. Innovative surface protection technology provides the ultimate defence against scratches, wear & tear and greasy finger marks for a long-lasting finish. Johnstone's Trade Aqua Guard also has advanced application qualities, excellent hiding power and long-lasting whiteness*.

RECOMMENDED USES



- For interior wood and metal
- Apply by brush/roller
- Water Based
- Coverage up to 14 m²/l
- Recoat 4hrs

COLOUR RANGE

Over 16,000 colours are available via the Johnstone's tinting system.

*Long-lasting whiteness is applicable to Brilliant White only.

FINISH

Satin Finish.

VOLUME SOLID

36%

COVERAGE



Johnstone's Trade Aqua Guard Satin will cover up to 14 m²/l depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet 100 microns and Dry 35 microns.

DRYING TIME



Touch dry in 1-2 hours
Recoat after 4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.


THINNER

Cleaner: Clean Water

*Long-lasting whiteness is applicable to Brilliant White only.

VOC CONTENT

EU limit value for this product (Cat A/d): 130g/l (2010) This product contains max 80g/l VOC



KEY PROPERTIES

- Ultimate durability
- Resists grease, stains and scratches
- Outstanding covering power and long-lasting whiteness*

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Prime bare wood with Johnstone's Trade Aqua Water Based Undercoat. Prime all other bare surfaces with the appropriate Johnstone's Trade primer. Apply one full coat of Johnstone's Trade Aqua Water Based Undercoat to all correctly prepared and primed surfaces before application of Johnstone's Trade Aqua Guard Satin. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonetrade.com

APPLICATION



Ensure good ventilation during application and drying. Stir well. Easy to apply by brush or roller. If more than one can of a colour is to be used in the same area, intermix before use. When attempting a wide colour change additional coats may be required. Do not apply in temperatures below 8°C.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonetrade.com or call 01924 354354

SIZES

1, 2.5 and 5 litre