

DESCRIPTION

Johnstone's Trade Aqua Undercoat Water Based Undercoat is an innovative, water based undercoat ideal for interior and exterior wood and metals. It looks, feels and applies more like a traditional undercoat but is quick drying - reducing application times, has a low odour and contains less atmosphere polluting VOC's.

RECOMMENDED USES



Suitable for interior and exterior use.

TYPE OF SUBSTRATE

Ideal for interior and exterior wood and metal.

COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

FINISH

Undercoat.

VOLUME SOLID

39%

COVERAGE



Johnstone's Trade Water Based Aqua Undercoat will cover approximately 10-12 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 100µm, dry: 39µm.

DRYING TIME



Touch dry in 1-2 hours. Recoatable after 4-6 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.


CLEANER

Cleaner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/d): 130g/l (2010).

This product contains max 10g/l VOC.



KEY PROPERTIES

- Low odour, water based technology
- Excellent application & finish
- Quick drying

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare wood surfaces with Johnstone's Trade Aqua Water Based Undercoat. Prime all other bare surfaces with the appropriate Johnstone's Trade primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Stir well before use. Easy to apply by brush. Avoid overspreading. Do not apply in temperatures below 10°C or externally when rain is imminent. For best results use a synthetic brush.

CLEANING



Remove as much product as possible from application equipment before cleaning. To maintain brushes, do not allow paint to dry out on bristles. Regularly wash in clean, cold soapy water throughout use. Following prolonged use, clean with Clean water, Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available: www.johnstonestrade.com or call 01924 354354

SIZES

1 Litre, 2.5 Litre, 5 Litre.