

DESCRIPTION

Johnstone's Trade Woodworks Classic Matt Woodstain has been formulated to provide an easy maintenance protective matt finish for above the ground exterior timber such as rough sawn decking and cladding. Ideal for new or bare timber it protects the wood providing a microporous finish which resists cracking, blistering and peeling. It can be used on its own (2-3 coats) or as part of a system (1 coat Classic Matt Woodstain, 2 coats Classic Satin Woodstain) to provide up to 5 years weather protection. For maximum protection on new, bare and untreated wood first apply a suitable wood preserver.

COLOUR RANGE

Clear; Light Oak; Jacobean Oak; Redwood; Mahogany; Ebony; Medium Oak; Walnut; Pine; Antique Pine; Rosewood; and Teak. A Range of colours available in 2.5 litre and 5 litre only via the Johnstone's CMS2010 Tinting System.

RECOMMENDED USES



Suitable for interior & exterior use.

TYPES OF SUBSTRATE

Rough sawn timber, barge boards, cladding, garden furniture, decking.

COVERAGE



Johnstone's Trade Woodworks Classic Matt Woodstain will cover at a rate of approximately 15 square metres per litre depending on the nature and porosity of the timber.

DRYING TIME



Recoat after 16-24 hours under normal conditions. Allow longer in adverse conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position.

STORE AWAY FROM HEAT AND FLAME.

CLEANER

Cleaner: White Spirit.

VOC CONTENT

EU limit value for the product (Cat A/e): 400g/l (2010). This product contains max 400g/l VOC.



KEY PROPERTIES

- Excellent durability & weather protection
- Resists cracking, blistering & peeling
- Traditional stain for bare & previously stained wood

PREPARATION

Ensure all surfaces to be stained are sound, clean, dry and free from dust, grease, polish or any other surface contaminant. Treat any mould or lichen with Johnstone's Trade Sterilisation Wash as directed. Remove any flaking or cracked varnish and fill any cracks or joints with filler. Sound, existing varnish should be rubbed down with fine waterproof abrasive paper, rinsed thoroughly and allowed to dry. Previously painted wood should have all traces of previous treatments removed using a Paint & Varnish Stripper. Avoid inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure maximum ventilation during application and drying. When applying by brush to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory protective equipment. Stir Johnstone's Trade Woodworks Classic Matt Woodstain thoroughly prior to use. Apply evenly by brush along the wood grain, as required, paying particular attention to the end grain. New, untreated soft wood should first be treated with a suitable wood preserver. On new or bare wood, apply at least two coats of Johnstone's Trade Woodworks Classic Matt Woodstain to give maximum durability. Lightly sand between coats. **PLEASE NOTE:** The final colour will depend on the original colour of the wood and the number of coats applied. The colour label on this tin indicates approximate colour only.

CLEANING



Remove as much product as possible from application equipment before cleaning. Clean application equipment immediately after use in White Spirit or Turpentine substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

750ml, 2.5 litre and 5 litre sizes.