

## DESCRIPTION

Johnstone's Trade Flame Retardant Durable Matt is a water-borne, flame retardant coating designed to maintain or upgrade a surface to inhibit the spread of flame. For use over new non-combustible or previously painted surfaces, the quick dry, low odour formulation makes it ideal for use on internal wall surfaces and ceiling areas where a durable, washable hard wearing finish is required.

## RECOMMENDED USES



Recommended to maintain or upgrade a surface to inhibit the spread of flame. For use over new non-combustible or previously painted surfaces.

## TYPE OF SUBSTRATE

For use on internal linings, broad wall and ceilings.

## COLOUR RANGE

Available in over 16,000 colours via the Johnstone's Tinting System.

## FINISH

Matt

## VOLUME SOLID

34%

## COVERAGE



Johnstone's Trade Flame Retardant Durable Matt must cover a maximum of 10 square metres per litre. To comply with the flame testing report, it is critical that this coverage is not exceeded.

## FILM THICKNESS

Wet: 83µm Dry: 28µm

## DRYING TIME



Touch dry in 1-2 hours. Recoatable after 4 hours. Do not apply when air or surface temperature is below 10°C or in damp conditions.

## TRANSPORTATION & STORAGE


To avoid the risk of spillage, always store and transport in a secure, upright position. PROTECT FROM FROST.

## THINNER

Cleaner: Clean water.

## VOC CONTENT

EU limit value for this product (Cat A/i): 140g/l (2010). This product contains max 10g/l VOC.



## KEY PROPERTIES

- Flame Retardant Durable Matt
- Tough, durable & washable
- Inhibits the spread of flame
- Tested in accordance with BS476 Parts 6 & 7

## PREPARATION

Surfaces must be sound, clean, dry and free from all loose and flaking materials, dirt, grease or other surface contaminants. Rub down previously painted surfaces with a fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. New or bare surfaces should be coated with a mist coat of Johnstone's Trade Flame Retardant Durable Matt thinned with up to 10% clean water. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).

## APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir thoroughly before use. Apply by brush, roller or spray as required. For spray applications, thinning may be required. Airless Spray = 017-019 thou tip, 200 bar (2000-3000 psi). An additional coat may be required if thinning to meet the required film build for the flame testing. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply in temperatures below 10°C or in damp conditions.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with clean water. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354

## SIZES

5 Litre.