

DESCRIPTION

Johnstone's Trade MDF Primer is a high performance, water borne, combined primer and undercoat specifically formulated for use on medium density fibre boards. It provides a low odour, quick drying alternative to conventional solvent borne primers producing an ideal surface for overcoating with subsequent topcoat. Primer for MDF, chipboard, blockboard, smooth planed timber and other wood composites. Seals routed MDF effectively.

RECOMMENDED USES



As a primer for MDF, especially routed, to seal prior to application of subsequent topcoat. Also can be used on chipboard, blockboard, planed timber and other wood composites.

SPECIAL PROPERTIES

High build with excellent adhesion. Quick drying and low odour.

COLOUR RANGE

Brilliant White.

FINISH

Matt.

VOLUME SOLID

36%.

COVERAGE



Johnstone's Trade MDF Primer will cover approximately 12-14 square metres per litre, depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 77µm, dry: 27µm.

DRYING TIME



Touch dry in 30 minutes. Recoatable after 1-2 hours under normal conditions.

TRANSPORTATION & STORAGE

To avoid risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

THINNER

Thinner: Clean Water.

VOC CONTENT

EU limit value for this product (Cat A/d): 130g/l (2010). This product contains max 15g/l VOC.



KEY PROPERTIES

- Combined undercoat & primer
- Excellent adhesion
- Seals routed MDF

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare metal surfaces such as nail heads with the appropriate Johnstone's Trade Primer. Rub down previously painted surfaces with fine waterproof abrasive paper. Avoid inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well before use. Easy to apply by brush or roller. Apply liberally, brushing firmly into the surface. Also suitable for application by spray. A second coat serves as an excellent undercoat. Do not apply in temperatures below 10°C.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZE

1 Litre, 2.5 Litre and 5 Litre.