

DESCRIPTION

Johnstone's Trade Woodworks Quick Dry Opaque Wood Finish has been formulated to give a long lasting, all weather protective finish. It is ideal for garden furniture and exterior woodwork of both rough sawn and planed timber. Its quick drying nature means most tasks can be completed in one day. The microporous technology allows moisture to escape and wood to breathe, preventing rot. To ensure maximum protection on new, bare and untreated wood first apply a suitable wood preserver.

COLOUR RANGE

Clear; Light Oak; Jacobean Oak; Redwood; Mahogany; Ebony; Medium Oak; Walnut; Pine; Antique Pine; Rosewood; and Teak.

A Range of colours available in 2.5 litre and 5 litre via the Johnstone's CMS2010 Tinting System.

RECOMMENDED USES

Suitable for exterior use.



TYPES OF SUBSTRATE

Garden furniture, trellis work, gates, sheds, fencing, cladding, fascias, rough sawn and smooth planed timber.

COVERAGE

Johnstone's Trade Woodworks Quick Dry Opaque Wood Finish will cover approximately 12 square metres per litre depending on the nature and porosity of the timber.



DRYING TIME

Touch dry in 1-2 hours. Recoatable after 2-4 hours. Allow first coat to dry before recoating. Conditions of low temperature and high humidity will prolong drying time.



TRANSPORTATION & STORAGE


To avoid the risk of spillage, always store and transport in a secure, upright position. Do not use empty container for storing food. PROTECT FROM FROST.

THINNER

Cleaner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/e): 130g/l (2010). This product contains max 50g/l VOC.



KEY PROPERTIES

- Superior water repellency
- Protects against damaging UV rays
- Microporous technology, allows moisture to escape and wood to breathe

PREPARATION

Ensure that all timber to be treated is sound, dry and free from dust, grease or any other surface contaminants. Treat any mould or lichen with a fungicidal wash as directed. Sand smooth natural planed wood and wipe clean with White Spirit to remove any natural oils or resins and allow to dry. Avoid inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Stir well before and during use. Ensure gloves are worn during application to avoid staining of hands. Apply using brush, working the material well into the timber along the grain. Usually one coat will be sufficient, unless on rough or badly cracked timber when two coats should be applied. The final colour achieved will depend on the colour and porosity of the timber and the number of coats applied. Do not apply when the temperature is below 10°C or when rain is imminent.

CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

2.5 litre and 5 litre.