

DESCRIPTION

Johnstone's Trade Woodworks Shed and Fence Treatment is formulated to be water repellent and resist fading. Suitable for above ground rough sawn timber. This special wax enriched formulation protects exterior timber from the sun's harmful UV rays.

COLOUR RANGE

Acorn Gold; Dark Chestnut; Dark Oak; Green; Light Brown; Rustic Red and Ebony.

RECOMMENDED USES

Suitable for exterior use.



TYPES OF SUBSTRATE

Rough sawn timber, fences and sheds.

COVERAGE

Johnstone's Trade Woodworks Shed and Fence Treatment will cover approximately 6 square metres per litre on rough sawn timber and approximately 12 square metres per litre on planed timber.



DRYING TIME

Allow 2-4 hours between coats.



TRANSPORTATION & STORAGE


To avoid the risk of spillage, always store and transport in a secure, upright position. Do not use empty container for storing food. PROTECT FROM FROST.

THINNER

Cleaner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/e): 130g/l (2010). This product contains max 3g/l VOC.



KEY PROPERTIES

- 3 year colour retention
- Wax enriched to provide excellent water repellency
- Resists harmful UV rays

PREPARATION

Ensure all timber is clean, dry and free from surface coatings, such as paint, varnish or polish. If the timber is affected by mould, lichen, algae or moss, use a fungicidal pre-treatment prior to application of Johnstone's Trade Woodworks Shed and Fence Treatment. Wear a suitable face mask when creating dust. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Stir Johnstone's Trade Woodworks Shed and Fence Treatment well before and during use. Whilst applying ensure gloves are worn to avoid staining hands. Brush liberally and evenly onto exposed surfaces. Wash off any splashes on plants otherwise the foliage may be stained. One coat is required on sound new timber. Old weathered timber or porous timber may require two coats. Do not apply to wet wood, or in temperatures below 10°C or when rain is imminent. Please Note: The final colour will depend on the colour and porosity of the surface.

CLEANING



Remove as much product as possible from application equipment before cleaning. Application equipment should be washed immediately after use in warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

5 litre size and 9 litre (selected colours)