

DESCRIPTION

Johnstone's Trade StainAway is an innovative, high opacity wall and ceiling paint. It contains Stain Blocking Technology[®], permanently isolating and covering even the most persistent stains such as smoke damage, nicotine damage and water stains in one coat*. Johnstone's Trade StainAway is a primer and finish in one product.

RECOMMENDED USES



Stain isolator and finish for all types of interior walls and ceilings both bare and previously painted including plaster, plasterboard, concrete, ceiling tiles and wallcoverings.

TYPE OF SUBSTRATE

Gives the same stain blocking performance when applied to a variety of suitably prepared and primed surfaces such as metal, wood, melamine, glazed tiles etc.

COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

FINISH

Dead Matt Finish.

VOLUME SOLID

43%

COVERAGE



Johnstone's Trade StainAway will cover up to 9 square metres per litre depending on the nature and porosity of the surface.

FILM THICKNESS

Wet 110 microns and Dry 48 microns.

DRYING TIME



Touch dry in 1 hour. Recoatable after 4 hours.

TRANSPORTATION & STORAGE

To avoid risk of spillage, always store and transport in a secure upright position. Keep container tightly closed. PROTECT FROM FROST.

THINNER

Cleaner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/a): 30g/l (2010) This product contains max 2g/l VOC.



KEY PROPERTIES

- Smooth flat matt finish
- Class 1 scrub rating ISO 11998
- Primer and finish in one

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Where water damage has occurred ensure the leak is fixed and the area is dry before painting. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well before use. Easy to apply by brush or roller. Also suitable for application by spray. Seal absorbent surfaces such as new plaster with a coat of Johnstone's Trade StainAway thinned up to 20% with clean water. Do not apply in temperatures below 8°C or in damp conditions. *For best results in one coat, apply the paint generously and evenly in line with the spreading rate of up to 9 square metres per litre. Avoid over spreading. Some strong or contrasting stains may require a further coat.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

CLEANING STAINS

Apply all-purpose cleaner to sponge or soft cloth and wipe away stain from surface and allow to dry.

SIZES

2.5 Litre, 5 Litre and 10 Litre.