

DESCRIPTION

A fast evaporating, aromatic hydrocarbon for thinning and cleaning various Johnstone's Performance Coatings.

RECOMMENDED USES

Thinning and cleaning various Johnstone's Performance Coatings.

SPECIAL PROPERTIES

Not applicable.

COLOUR RANGE

Clear.

FINISH

Not applicable.

VOLUME SOLID

Not applicable.

COVERAGE

Not applicable.

DRYING TIME

Not applicable.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

THINNER

Not applicable.

VOC CONTENT

Not applicable.

FILM THICKNESS

Wet: not applicable, dry: not applicable.

SIZE

5 Litre.

PREPARATION

Not applicable.

APPLICATION

Not applicable.

CLEANING

Not applicable.

PRECAUTIONS

- Xylene UN1307.
- EC Label. EC No. 215-535-7.
- FLAMMABLE.
- HARMFUL BY INHALATION AND IN CONTACT WITH SKIN.
- IRRITATING TO SKIN.
- Keep away from sources of ignition – No smoking.
- Do not breathe vapour.
- Use only in well ventilated areas.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water.
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- In case of insufficient ventilation wear suitable respiratory protective equipment.
- Wear suitable gloves.
- If swallowed, do not induce vomiting, seek medical advice immediately and show the container or label.
- Do not empty into drains.
- Keep out of the reach of children.
- Ingredients: Aromatic hydrocarbon – 30% and more.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

