

DESCRIPTION

Johnstone's Trade Ultra Primer Sealer is a high performance, quick drying, alkali resisting primer sealer manufactured from high quality pigments and tough acrylic resin now with enhanced stain blocking properties. Primes and seals plaster, plasterboard, cement render, timber, bare masonry, interior stone and fibre cement boards, wood panelling, ceramic and glazed tiles, doors, trim, windows and any surface where great adhesion and fast drying properties are needed.

RECOMMENDED USES



Ideal for use in private and public buildings where its low odour properties, combined with ease of application and speed of drying, allow the work to be completed with a minimum of disruption.

SPECIAL PROPERTIES

Primes difficult substrates. Seals porous surfaces. Stain blocks

COLOUR RANGE

Brilliant White.

FINISH

N/A

VOLUME SOLID

45%

COVERAGE



Johnstone's Trade Ultra Primer Sealer will cover approximately 10 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 100µm, dry: 45µm.

DRYING TIME



Touch dry in 30 minutes. Recoatable after 3 hours.

TRANSPORTATION & STORAGE


To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

THINNER

Thinner: Clean Water

VOC CONTENT

EU limit value for this product (Cat A/g): 30g/l (2010). This product contains max 10g/l VOC.



SIZE

1 Litre, 2.5 Litre and 5 Litre.

KEY PROPERTIES

- Primes difficult substrates
- Seals porous surfaces
- Stain blocks
- **BENEFITS** - Primes & Seals, Everyday primer
Ideal on - Alkali attack, Melamine/Formica, New Wood Trim/Doors, Plywood, Wood Panelling, Timber, Brick & Concrete, Plaster, Drywall, Cement Board, Ceiling Tiles, Masonry, And more...

PREPARATION

USAGE: Ideal for use in private and public buildings where its low odour properties, combined with ease of application and speed of drying, allow the work to be completed with minimum disruption.

All surfaces to be painted should be clean, dry and free from loose and flaking material. Surfaces should be suitably prepared before application. Rub down previously painted surfaces with fine waterproof abrasive paper. Hard wall plasters should be scored with coarse glasspaper. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well before use. Apply one full coat, brushing firmly into the surface. Porous surfaces should be sealed with a first coat of Johnstone's Trade Ultra Primer Sealer thinned with up to 20% clean water. Allow 3 hours to dry under normal conditions before applying the required paint finish. For best results, apply by brush as this assists the primer to penetrate the surface. Alternatively Johnstone's Trade Ultra Primer Sealer can be applied by airless spray. Allow fresh plaster to dry thoroughly before application. Do not apply when air or surface temperature is below 10°C.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354