



Universal Primer

DESCRIPTION

Johnstone's Trade Universal Primer is a solvent-borne primer. Specially formulated for interior and exterior use on new or bare wood and metal. It is suitable for multi surface work and areas of high corrosion.

RECOMMENDED USES



Suitable for interior and exterior use.

TYPE OF SUBSTRATE

Wood, metal, plaster and masonry.

COLOUR RANGE

White and Red Oxide.

FINISH

Not applicable.

VOLUME SOLID

61%

COVERAGE



Johnstones Trade Universal Primer will cover approximately 12 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 85µm, dry: 52µm.

DRYING TIME



Recoat after 16-24 hours under normal conditions.

TRANSPORTATION & STORAGE

STORE AWAY FROM HEAT AND FLAME.

To avoid the risk of spillage, always store and transport in a secure upright position.

CLEANER

Cleaner: White spirit.

VOC CONTENT

EU limit value for this product (Cat A/d): 300g/l (2010). This product contains max 300g/l VOC.



KEY PROPERTIES

- Multi surface primer
- Anti-corrosive, Ideal for metals

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. When painting iron and steel remove all mill scale and rust. Wear a suitable face mask if creating dust. Special precautions should be taken during the surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure maximum ventilation during application and drying. Not recommended for interior use on large surface areas, or in confined spaces. Stir well before use. Easy to apply by brush or roller. Apply liberally and evenly brushing firmly onto the surface.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty products into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

1 Litre, 2.5 Litre, 5 Litre.



For more information on our products and services call 01924 354354 or visit www.johnstonestrade.com.