



Stormshield Jontex High Build Textured Masonry

DESCRIPTION

Johnstone's Trade Stormshield Jontex High Build Textured Masonry is a high build, heavily textured, one coat finish formulated for exterior use on cement rendering, rough cast, brick, concrete, cement sheeting and suitably prepared plywood panels. It provides heavy duty, flexible, long term protection which covers small cracks and is suitable for application to badly weathered masonry surfaces.

RECOMMENDED USES



Suitable for exterior use.

TYPE OF SUBSTRATE

Concrete, cement rendering, brick, stone, blockwork and plywood panels.

COLOUR RANGE

Brilliant White, County Cream and Magnolia.

FINISH

Textured.

VOLUME SOLID

61%

COVERAGE



Johnstone's Stormshield Jontex High Build Textured Masonry will cover approximately 0.5-1 square metre per litre depending on the nature and porosity of the surface being painted and the texture required.

FILM THICKNESS

Wet: 1000µm, dry: 614µm.

DRYING TIME



Touch dry in 3-5 hours. Through dry in 48-72 hours depending on temperature and humidity.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position.

Do not use empty container for storing food.


PROTECT FROM FROST

THINNER

Thinner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/c): 40g/l (2010). This product contains max 10g/l VOC.



KEY PROPERTIES

- Ideal for badly weathered surfaces
- Heavy duty protection
- 15 year life expectancy

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Repair large cracks and defective areas paying particular attention to those that may lead to moisture penetration. Treat fungal or algal growth with Johnstone's Trade Sterilisation Wash as directed. Stabilise masonry surfaces of a highly porous or friable nature with Johnstone's Trade Stormshield Stabilising Solution as directed. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. On previously painted surfaces all loose and flaking material must be removed. Wear a suitable face mask when creating dust. Prime bare plywood panels with Johnstone's Trade Jontex Primer Undercoat. Do not apply to Fletton common bricks. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Ensure sufficient material is available to complete each elevation or area. Maintain a working edge finishing only at design features, wall ends etc. Do not apply in temperatures below 10°C or when there is risk of rain, dew or frost before the coating has had time to dry. Apply by 1. Roller: A self-textured finish is achieved by using an open-structure foam roller. Keep the roller head fully loaded and apply a thick even film overlapping each stroke as necessary to produce a uniform texture. 2. Trowel: Apply a thick even film and texture with a sponge, comb, spatula or patterned roller. 3. Air Assisted Spray: With a hopper gun use a 6mm tip at 40 psi and produce an even coat via small circular movements. 4. By brush: use a well-worn wall brush with a bristle length not exceeding 3". In one application apply a thick, even film. After this has been applied and whilst it is still in a fluid condition create a texture pattern by means of rotating action with the flat side of the brush. A priming coat of Johnstone's Stormshield Smooth or Textured Masonry Finish in a similar colour will assist coverage when applying by spray.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

10 Litre.



The British Board of Agrément is designated by Government to issue European Technical Approvals based on the assessment of products for construction. Johnstone's products carrying this logo have undergone rigorous independent testing and received approval from the BBA.



For more information on our products and services call 01924 354354 or visit www.johnstonestrade.com.